

JOTUN Industri Opaque Primer

Product description

Features and benefits

Water soluble special primer which contains effective film conserving agents against fungus and algae. Protects against decay caused by UV light and moisture, and ensures good adhesion for further treatment.

Recommended use

Developed for industrial application on cladding.

Treatment after assembly

The cladding is mounted in accordance with the current norms and standards for carpentry. The cladding must be clean, sound and dry before further treatment.

When mounting:	Prime cut surface, end grains and other untreated wood with VISIR Oljegrunning wet-on-wet 3-4 coats when the cladding is mounted.
Within 1 year after the cladding has been mounted:	Treat surface within 12 months. For best possible protection of the woodwork it is recommended to finish the treatment when the cladding is installed and no later than within the first painting season. Repainting recommended to be done with DRYGOLIN Nordic Extreme Oljeglans , but other outdoor paints from Jotun can also be used.
Maintenance interval:	The cladding should be inspected annually, by the homeowner. It is the owners responsibility to repair any damages. The product will naturally be degraded by external influences. Maintenance interval is influenced by local climatic conditions and stain or paint must be applied as needed and desire for appearance.
Subsequent maintenance is recommended performed using:	Wash the house with JOTUN 2-i-1 Husvask og soppfjerner / JOTUN 2-i-1 Husvask och mögeldesinfektion / JOTUN 2-i-1 Husvask/Træ- og Murrens when necessary. Further maintenance is recommended with DRYGOLIN Nordic Extreme Oljeglans , but other outdoor paints from Jotun can also be used. Follow the instruction manual of the product you choose.
Maintenance repair:	Loose fibres to be removed down to bare wood. Prime bare wood, any damages and end grains immediately with 3-4 coats VISIR Oljegrunning , wet-on-wet. Apply DRYGOLIN Nordic Extreme Oljeglans / the product previously used as topcoat. If other products are used, documentation must be presented as proof, that they are the same type of product as first used.

Comments

In case of poor adherence to knots: The nature of the substrate affects how well the treatment will adhere. Knots and hard glossy surfaces with higher content of resins, phenols and terpenes adversely affect the adhesion of paint. This may cause flaking. Flaking is treated by removing loose paint with steel brushing / scraping before re-painting the area.

Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

Environmental labelling

Green Building Standards

The declared product meets the following requirements:

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/d): 130 g/l. The product contains max 40 g/l VOC.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

Treated surface/substrate type

Painted in colour

Colour name

NCS code

Production number

Management, Operation and Maintenance

JOTUN Industri Opaque Primer



Paint work done by

Date

Signature

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.