

OPTIMAL OptiWhite

Product description

Type

Opaque wood protection for outdoor use, especially designed for white colours.

Features and benefits

Special formulation with extremely low dirt pick-up, which reduce the risk of dirt and grime attaching to the surface. Preserves white colours longer. Contains effective film conserving agents that counteract mould growth. The binder technology in combination with weather resistant pigments protects the wood against sunlight and gives very good weather resistance. Maintains colour and gloss for a long time, dries quickly and is easy to apply.

Recommended use

To be used in combination with VISIR Oljegrunning, as part of a system treatment. To be applied to new, previously stained or painted woodwork, as well as impregnated. Also suitable as a topcoat for previously primed gutters, fascias made of plastic and metal commonly use on buildings. Prime the metal with a suitable primer.

Application methods, recommended use and technical specifications

See the product's Technical Datasheet.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.

Maintenance

Cleaning

Newly painted surfaces must not be cleaned the first 3-4 weeks (the product's curing time).

Recommended detergent

Recommended detergent is JOTUN Husvask. If other detergents are used, the pH value of this must not exceed pH 9. Read the instructions for the detergent, before use.

Recommended cleaning procedure

A suitable detergent is recommended for yearly cleaning. Surfaces with discolouring fungi and algae, should be washed with a suitable cleaning agent and then brushed with a wire brush. Surfaces that are very dirty from pollution and discolouring fungi, must first of all, be cleaned with a suitable cleaning agent. Using JOTUN Kraftvask may cause matting of the surface treatment and window glass.

Maintenance interval

Maintenance intervals are influenced by local climatic conditions and repainting must be made when needed. The product will naturally be degraded by external influences. This will appear as gloss sheen and colour change.

Maintenance repair

Damages or repairs must be carried out, using the same product, used when the painting was done. If other products are used, documentation must be presented as proof, that they are the same type of product as first used. Repair of damages, shall be carried out, so that they do not deviate from current treatments. See project/specification form for information about products used for preparation and pretreatment. When repainting, use the same product. For advice speak to your dealer or painting contractor.

Environmental labelling



Miscellaneous

NOBB number

This document covers the following NOBB-numbers:

50428560, 50428556

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/d): 130g/l. The product contains max 50 g/l VOC.

Contact information

Jotun A/S
Box 2021, NO-3202 Sandefjord
Tel.: +47 33 45 70 00

Disclaimer

Management, Operation and Maintenance

OPTIMAL OptiWhite



The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Treated surface

Painted in colour

Colour name

NCS code

Production number

Paint work done by

Date

Signature