

JOTUN Industri Treolje

Product description

Type

Waterborne oil.

Features and benefits

Has very good penetrating ability and provides good protection against decay from light and fungal attack. The product has good water-repellant effect. Contains pigments and light filters that protect the wood against decay caused by UV light. Contains effective film conserving agent that counteract mould growth.

Recommended use

For industrial application on impregnated cladding. **JOTUN Industri Treolje** provides a transparent natural appearance. **JOTUN Industri Treolje** should not form a film, but be absorbed well into the substrate. Over time, the product will wear away and the substrate will have a natural gray appearance. If you want to maintain a colored appearance, the facade must be painted or stained.

Treatment after assembly for impregnated cladding pretreated with 1 coat JOTUN Industri Treolje

The substrate must be clean, sound and dry.

Immediately:	Loose fibres to be removed down to bare wood. Prime cut surface, end grains, screw / nail holes and any damages with TREBITT Terrassebeis 3-4 coats wet-on-wet. Please note that the color gets darker for each coat applied. TREBITT Terrassebeis is supplied in the same colors as JOTUN Industri Treolje . Choose color from TREBITT Terrassebeis Color chart or get color code from the cladding manufacturer.
At the earliest 12 months after installation:	Further treatment with paint or stain must not be carried out until at least 12 months after the cladding was mounted.

Subsequent maintenance

JOTUN Industri Treolje is maintained as needed and desire for appearance. **JOTUN Industri Treolje** will for some time provide protection against water penetration even if the color is worn away. Depending on local climatic conditions, after 3-5 years, **JOTUN Industri Treolje** will no longer provide protection for the wood and the wood will get a naturally weathered appearance. For continued good protection and an attractive appearance, paint or stain is recommended as desired.

Cladding treated with JOTUN Industri Treolje	Treatment
Transparent further treatment with stain:	Wash the cladding with JOTUN 2-i-1 Kraftvask og soppfjerner / JOTUN 2-i-1 Kraftvask och mögeldesinfektion / JOTUN 2-i-1 Kraftvask og Træ og Murrens . Use steel brushing to remove loose wood fibers and weathered wood to fresh wood. Bare wood is stained with TREBITT Oljebeis , before the entire cladding is given 1 or 2 coats of TREBITT Oljebeis . The color will be more opaque for each coat applied. It is recommended to perform a test application.
Opaque further treatment with paint or opaque wood stain:	Wash the cladding with JOTUN 2-i-1 Kraftvask og soppfjerner / JOTUN 2-i-1 Kraftvask och mögeldesinfektion / JOTUN 2-i-1 Kraftvask og Træ og Murrens . Use steel brushing to remove loose wood fibers and weathered wood to fresh wood. Bare wood is primed with VISIR Oljegrunning , before the entire cladding is given 2 coats of DRYGOLIN Ultimat or OPTIMAL .

Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

Maintenance

Please note that if the cladding is stained then the color expression may become stronger and more opaque since one pigmented coat has already been applied.

Cleaning

The cladding must not be cleaned the first 4 weeks.

Recommended cleaning procedure

JOTUN 2-i-1 Husvask og soppfjerner / JOTUN 2-i-1 Husvask och mögeldesinfektion / JOTUN 2-i-1 Husvask/Træ- og Murrens is recommended for yearly cleaning.

Maintenance interval

The cladding should be inspected annually, by the homeowner. It is the owners responsibility to repair any damages. The product will naturally be degraded by external influences. Maintenance interval is influenced by local climatic conditions and stain or paint must be applied as needed and desire for appearance.

Maintenance repair

Damages or repairs to be improved with **TREBITT Terrassebeis**. Repair of damages, shall be carried out, so that they do not deviate from current treatments.

Environmental labelling

Green Building Standards

The declared product meets the following requirements:

- Property criteria in BETA (2018:A2)

BREEAM® NOR (2016)

Mat 01: Product-specific Type III EPD (ISO 14025;21930, EN 15804) for Scandinavia.

Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

BREEAM® NOR (2012)

Mat 1.3: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Scandinavia.

Mat 1.5: This product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional certificates and approvals may be available on request.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/e): 130 g/l. The product contains max 10 g/l VOC.

Miscellaneous

Contact information

Jotun A/S
Box 2021, NO-3202 Sandefjord
Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Treated surface/substrate type

Painted in colour

Colour name

NCS code

Production number

Paint work done by

Date

Signature