

## JOTUN Industri Treolje

### Product description

#### Type

Waterborne oil.



#### Features and benefits

Has very good penetrating ability and provides good protection against decay from light and fungal attack. The product has good water-repellant effect. Contains pigments and light filters that protect the wood against decay caused by UV light. Contains effective film conserving agent that counteract mould growth.

**JOTUN Industri Treolje** provides a transparent natural appearance.

Over time, the product will wear away and the substrate will have a natural gray appearance. If you want to maintain a colored appearance, the facade must be painted or stained.

### Treatment after assembly for impregnated cladding pretreated with 1 coat JOTUN Industri Treolje

The substrate must be clean, sound and dry.

Immediately:	Loose fibres to be removed down to bare wood. Prime cut surface, end grains, screw / nail holes and any damages with <b>TREBITT Terrassebeis</b> 3-4 coats wet-on-wet. Please note that the color gets darker for each coat applied. <b>TREBITT Terrassebeis</b> is supplied in the same colors as <b>JOTUN Industri Treolje</b> . Choose color from <b>TREBITT Terrassebeis</b> Color chart or get color code from the cladding manufacturer.
At the earliest 12 months after installation:	Further treatment with paint or stain must not be carried out until at least 12 months after the cladding was mounted.

#### Subsequent maintenance

**JOTUN Industri Treolje** is maintained as needed and desire for appearance. **JOTUN Industri Treolje** will for some time provide protection against water penetration even if the color is worn away. Depending on local climatic conditions, after 3-5 years, **JOTUN Industri Treolje** will no longer provide protection for the wood and the wood will get a naturally weathered appearance. For continued good protection and an attractive appearance, paint or stain is recommended as desired.

Cladding treated with JOTUN Industri Treolje	Treatment
Transparent further treatment with stain:	Wash the cladding with <b>JOTUN3-i-1 Kraftvask og Træ- og Murrens</b> . Use steel brushing to remove loose wood fibers and weathered wood to fresh wood. Bare wood is stained with <b>TREBITT Oljebeis</b> , before the entire cladding is given 1 or 2 coats of <b>TREBITT Oljebeis</b> . The color will be more opaque for each coat applied. It is recommended to perform a test application.
Opaque further treatment with paint or opaque wood stain:	Wash the cladding with <b>JOTUN3-i-1 Kraftvask og Træ- og Murrens</b> . Use steel brushing to remove loose wood fibers and weathered wood to fresh wood. Bare wood is primed with <b>VISIR Oljegrunning</b> , before the entire cladding is given 2 coats of <b>DRYGOLIN Ultimatt</b> or <b>OPTIMAL</b> .

### Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

### Environmental labelling

#### Green Building Standards

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).

The declared product meets the following requirements:

- Property criteria in BETA (2018:A2)

BREEAM® NOR (2016)

Mat 01: Product-specific Type III EPD (ISO 14025, ISO 21930, EN 15804) for Scandinavia.

Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

BREEAM® NOR (2012)

Mat 1.3: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Scandinavia.

Mat 1.5: This product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional certificates and approvals may be available on request.

---

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

Safety rules

**00-1**

Product registration number: 4220052

## VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/e): 130 g/l. The product contains max 10 g/l VOC.

---

## Contact information

Jotun Danmark A/S  
Jernet 6  
6000 Kolding

Tel: +45 76 30 32 00  
mail@jotun.dk

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

---

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).

## Treated surface/substrate type

**Painted in colour**

**Colour name**

**NCS code**

**Production number**

**Paint work done by**

**Date**

**Signature**

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).

## **Management, Operation and Maintenance**

### **JOTUN Industri Treolje**

