

# **JOTUN Industri LADY Pure Nature**

# **Product description**

#### **Type**

Waterborne oil stain for interior use. Developed specifically for industrial application to the panel board.



#### **Features and benefits**

Gives a naturally beautiful finish that will enhance the woodwork. Contains light filter which effectively reduces yellowing.

#### **Recommended use**

For industrial application on interior pine panel.

# Installation of factory-treated wood panel

The panel is mounted in accordance with the current norms and standards for carpentry.

Proper cleaning with clean hands and clean tools to avoid putting finger, dirt and grease marks on the panel is recommended. If necessary, use a mild synthetic detergent to wash away dirt and grease marks from the assembly work. Avoid using green soap and ammonia.

The substrate must be clean, sound and dry before further treatment.

# Treatment after assembly of wooden panels that are applied JOTUN Industry Lady Pure Nature

When mounting	Cut surfaces and bare wood can be treated with <b>LADY Pure Nature</b> from your local paint dealer.	
Cleaning:	Stained surfaces must not be cleaned the first four weeks. If cleaning is necessary, the pH of the detergent must not exceed pH 9.	
Cleaning agent:	JOTUN Spesialvask før maling is recommended.	
Maintenance:	The maintenance interval is affected by mechanical conditions, and retreatment must therefore be done when required.  The panel can be stained with <b>LADY Pure Nature</b> or recoated with Jotun's interior paints adapted to wood.	
Damages or repairs	Damages or repairs to be rectified with the same product as used when the work was done. If other products are used, documentation must be presented as proof, that they are the same type of product as first used. Repair of damages, shall be carried out, so that they do not deviate from current treatments.	

#### Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

# **Health and safety**

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

**Regulatory information**, refer to section 15.

Date of issue: 28.11.2022 Product code: 46262 Product family 6H5 Page: 2/3

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

#### **VOC for Ready-for-Use Mixture**

EU limit value for the product (cat. A/e): 130 g/l. The product contains max 130 g/l VOC.

### **Contact information**

Jotun Sverige AB Box 151 421 22 Västra Frölunda Tlf.: 031 69 63 00

#### **Disclaimer**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue: 28.11.2022 Product code: 46262 Product family 6H5 Page: 3/3 code:

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

# **Treated surface/substrate type**

Painted in colour	
C	olour name
N	CS code
Production number  Paint work done by	
Paint work dolle by	
Date	
Signature	

