

JOTUN Industri kraftvask

Product description

Type

Strong detergent based on alkalis and other biological raw material degraders. Detergent for cleaning paint lines. **JOTUN Industri kraftvask** can also be used for other tasks that require a powerful detergent with a matting effect.



Features and benefits

JOTUN Industri kraftvask is a powerful detergent which loosens dirt that can't be removed with mild detergents. **JOTUN Industri kraftvask** loosens and removes effectively wet paint, oil, grease, salt, dirt etc. Given adequate working time, **JOTUN Industri kraftvask** may re-solve dry paint (one component paints).

At weaker solution, **JOTUN Industri kraftvask** can be used for easier cleaning tasks.

Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Safety rules

Product registration number: 4321910

00-4

Contact information

Jotun Danmark A/S
Jernet 6
6000 Kolding

Tel: +45 76 30 32 00
mail@jotun.dk

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Treated surface/substrate type

Painted in colour

Colour name

NCS code

Production number

Paint work done by

Date

Signature

Management, Operation and Maintenance
JOTUN Industri kraftvask



Jotun Protects Property