

## JOTUN Industri Drygolin Color Expert

### Product description

#### Type

**JOTUN Industri Drygolin Color Expert** is made with specially composed raw materials that give the cladding a beautifully subdued silky matte look with long-lasting good protection.

Developed specifically for industrial application to the cladding.



### Features and benefits

**JOTUN Industri Drygolin Color Expert** has extreme color durability. The paint has a beautifully muted silk matte appearance and is self-cleaning. **JOTUN Industri Drygolin Color Expert** is particularly effective against black fungus and provides long-term protection for the façade with a freshly painted appearance.

High solids provide fast drying and efficient industrial handling.

**JOTUN Industri Drygolin Color Expert** applied as primer and mid coat can stand up to 3 years before before recoating.

**JOTUN Industri Drygolin Color Expert** applied as primer (40 µm) can stand up to 12 months before before recoating.

### Treatment after assembly

The cladding is mounted in accordance with the current norms and standards for carpentry. The substrate must be clean, sound and dry before further treatment.

Treatment after mounting is determined by factory pre-treatment:

### Maintenance

Maintenance interval:	The cladding should be inspected annually, by the homeowner. It is the owners responsibility to repair any damages. The product will naturally be degraded by external influences. Maintenance intervals are influenced by local climatic conditions and repainting must be made when needed.
Maintenance must be performed using:	Wash the house with NO: <b>JOTUN 3-i-1 Kraftvask og soppfjerner</b> / SE: <b>JOTUN 3-i-1 Kraftvask och mögeldesinfektion</b> diluted 1:15 when necessary.  Before further treatment (apply additional paint), the cladding should be washed with NO: <b>JOTUN 3-i-1 Kraftvask og soppfjerner</b> / SE: <b>JOTUN 3-i-1 Kraftvask och mögeldesinfektion</b> . This is to ensure good adhesion for the next coat and long maintenance intervals. Further maintenance is recommended with <b>DRYGOLIN Color Expert</b> , but other outdoor paints from Jotun can also be used. Follow the instruction manual of the product you choose.
Maintenance repair:	Loose fibres to be removed down to bare wood. Prime bare wood, any damages and end grains immediately with 3-4 coats <b>VISIR Oljegrunning</b> , wet-on-wet. Apply <b>DRYGOLIN Color Expert</b> as topcoat.

### Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

### Environmental labelling

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Green Building Standards

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

- Swan (2097 0002)

BREEAM® International (2021)

- Mat 01: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Jotun A/S.

BREEAM® NOR (2022/2016)

- Mat 01: Product-specific Type III EPD (ISO 14025, ISO 21930, EN 15804) for Scandinavia.

- Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional information: Certificates and approvals may be available on request.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/d): 130 g/l. The product contains max 30 g/l VOC.

## Contact information

Jotun Sverige AB  
Box 151  
421 22 Västra Frölunda  
Tlf.: 031 69 63 00

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).

## Treated surface/substrate type

**Painted in colour**

**Colour name**

**NCS code**

**Production number**

**Paint work done by**

**Date**

**Signature**

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).

## **Management, Operation and Maintenance**

### **JOTUN Industri Drygolin Color Expert**

