

JOTUN Industri Drygolin Power Clean

Product description

Type

JOTUN Industri Drygolin Power Clean is made with specially composed raw materials that give the cladding a beautifully subdued silky matte look with long-lasting good protection. Developed specifically for industrial application to the cladding.

Features and benefits

JOTUN Industri Drygolin Power Clean has extreme color durability. The paint has a beautifully muted silk matte appearance and is self-cleaning. **JOTUN Industri Drygolin Power Clean** is particularly effective against black fungus and provides long-term protection for the façade with a freshly painted appearance. High solids provide fast drying and efficient industrial handling.

JOTUN Industri Drygolin Power Clean applied as primer and mid coat can stand up to 3 years before before recoating.

JOTUN Industri Drygolin Power Clean applied as primer (40 µm) can stand up to 12 months before before recoating.

Treatment after assembly

The cladding is mounted in accordance with the current norms and standards for carpentry. The substrate must be clean, sound and dry before further treatment.

Treatment after mounting is determined by factory pre-treatment:

Maintenance

Maintenance interval:	The cladding should be inspected annually, by the homeowner. It is the owners responsibility to repair any damages. The product will naturally be degraded by external influences. Maintenance intervals are influenced by local climatic conditions and repainting must be made when needed.
Maintenance must be performed using:	Wash the house with NO: JOTUN 3-i-1 Kraftvask og soppfjerner / SE: JOTUN 3-i-1 Kraftvask och mögeldesinfektion diluted 1:15 when necessary. Before further treatment (apply additional paint), the cladding should be washed with NO: JOTUN 3-i-1 Kraftvask og soppfjerner / SE: JOTUN 3-i-1 Kraftvask och mögeldesinfektion . This is to ensure good adhesion for the next coat and long maintenance intervals. Further maintenance is recommended with DRYGOLIN Power Clean , but other outdoor paints from Jotun can also be used. Follow the instruction manual of the product you choose.
Maintenance repair:	Loose fibres to be removed down to bare wood. Prime bare wood, any damages and end grains immediately with 3-4 coats VISIR Oljegrunning , wet-on-wet. Apply DRYGOLIN Power Clean as topcoat.

Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

Environmental labelling

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



2097 0022

The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/d): 130 g/l. The product contains max 30 g/l VOC.

Contact information

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Tel: 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Treated surface/substrate type

Painted in colour

Colour name

NCS code

Production number

Paint work done by

Date

Signature

Management, Operation and Maintenance
JOTUN Industri Drygolin Power Clean



Jotun Protects Property