

## Pilot WF

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Pilot WF  
**Product code** : 12660  
**Product description** : Paint.  
**Product type** : Liquid.  
**Other means of identification** : Not available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use  
Use in coatings - Professional use

#### 1.3 Details of the supplier of the safety data sheet

Jotun Ibérica S.A.  
Poligon Industrial  
Santa Rita  
Calle Estàtica, no 3  
08755 - Castellbisbal Barcelona

Tel: +34 93 771 18 00  
Fax: +34 93 771 18 01  
SDSJotun@jotun.com

#### 1.4 Emergency telephone number

Jotun Ibérica S.A. Tel. +34 93 77 11 800 (8.00-17.00)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.  
See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning.

**Pilot WF**

## SECTION 2: Hazards identification

- Hazard statements** : H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H411 - Toxic to aquatic life with long lasting effects.
- Precautionary statements**
- General** : Not applicable.
- Prevention** : P261 - Avoid breathing vapour or spray.
- Response** : P391 - Collect spillage.  
 P362 + P364 - Take off contaminated clothing and wash it before reuse.  
 P302 + P352 - IF ON SKIN: Wash with plenty of water.  
 P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.  
 Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazardous ingredients** : 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)  
 1,2-benzisothiazol-3(2h)-one (BIT)  
 2-octyl-2h-isothiazol-3-one (OIT)
- Supplemental label elements** : Not applicable.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	Weight %	Regulation (EC) No. 1272/2008 [CLP]	Type
dipropylene glycol methyl ether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤5	Not classified.	[2]
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	EC: 264-843-8 CAS: 64359-81-5	≤0.23	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	[1]

**Pilot WF**

**SECTION 3: Composition/information on ingredients**

3-iodo-2-propynyl butylcarbamate (IPBC)	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (trachea) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
1,2-benzisothiazol-3(2h)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1)	[1]
Amines, C12-18-alkyldimethyl	REACH #: 01-2119485586-22 EC: 269-923-6 CAS: 68391-04-8	≤0.0049	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=1)	[1]
2-octyl-2h-isothiazol-3-one (OIT)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**Pilot WF**

## SECTION 4: First aid measures

- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion may cause nausea, diarrhea and vomiting.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

*Pilot WF*

## SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour, spray or mist.  
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.  
Put on appropriate personal protective equipment (see Section 8).  
Never use pressure to empty. Container is not a pressure vessel.  
Always keep in containers made from the same material as the original one.  
Comply with the health and safety at work laws.  
Do not allow to enter drains or watercourses.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

- Recommendations** : Not available.

**Pilot WF****SECTION 7: Handling and storage****Industrial sector specific solutions** : Not available.**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
dipropylene glycol methyl ether	<b>National institute of occupational safety and health (Spain, 2/2019). Absorbed through skin.</b> TWA: 308 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Exposure	Value	Population	Effects
dipropylene glycol methyl ether	Long term Dermal	65 mg/kg bw/day	Workers	Systemic
	Long term Inhalation	310 mg/m <sup>3</sup>	Workers	Systemic
	Long term Inhalation	37.2 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	Long term Oral	1.67 mg/kg bw/day	General population [Consumers]	Systemic
	Long term Dermal	15 mg/kg bw/day	General population [Consumers]	Systemic
	Long term Oral	0.33 mg/kg bw/day	General population	Systemic
	Long term Inhalation	37.2 mg/m <sup>3</sup>	General population	Systemic
	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	Long term Inhalation	308 mg/m <sup>3</sup>	Workers	Systemic
Amines, C12-18-alkyldimethyl	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	Short term Inhalation	1 mg/m <sup>3</sup>	Workers	Local
	Long term Inhalation	1 mg/m <sup>3</sup>	Workers	Local

**Pilot WF**

## SECTION 8: Exposure controls/personal protection

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
dipropylene glycol methyl ether	Fresh water	19 mg/l	Assessment Factors
	Marine	1.9 mg/l	Assessment Factors
	Fresh water sediment	70.2 mg/kg dwt	Assessment Factors
	Marine water sediment	7.02 mg/kg dwt	Assessment Factors
	Soil	2.74 mg/kg	Assessment Factors
	Sewage Treatment Plant	4168 mg/l	Assessment Factors

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

##### **Gloves**

: There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. Wear suitable gloves tested to EN374. Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber, neoprene, PVC

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Pilot WF**

## SECTION 8: Exposure controls/personal protection

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	: Liquid.
<b>Colour</b>	: A-base, B-base, C-base, Green., orange, White., White., White.
<b>Odour</b>	: Characteristic.
<b>Odour threshold</b>	: Not applicable.
<b>pH</b>	: 8 to 9
<b>Melting point/freezing point</b>	: 0
<b>Initial boiling point and boiling range</b>	: Lowest known value: 100°C (212°F) (water). Weighted average: 105.49°C (221.9°F)
<b>Flash point</b>	: Not applicable.
<b>Evaporation rate</b>	: Highest known value: 0.36 (water) Weighted average: 0.34 compared with butyl acetate
<b>Flammability (solid, gas)</b>	: Not applicable.
<b>Upper/lower flammability or explosive limits</b>	: 1.1 - 14%
<b>Vapour pressure</b>	: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water).
<b>Vapour density</b>	: Highest known value: 5.1 (Air = 1) (dipropylene glycol methyl ether).
<b>Density</b>	: 1.033 to 1.233 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	: Easily soluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/ water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not applicable.
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Kinematic (40°C): >0.205 cm <sup>2</sup> /s (>20.5 mm <sup>2</sup> /s)
<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.



**Pilot WF****SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion may cause nausea, diarrhea and vomiting.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate (IPBC)	LD50 Oral	Rat	1470 mg/kg	-
1,2-benzisothiazol-3(2h)-one (BIT)	LC50 Inhalation Dusts and mists	Rat	40 mg/l	4 hours
2-octyl-2h-isothiazol-3-one (OIT)	LD50 Oral	Rat	485 mg/kg	-
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

**Acute toxicity estimates**

Route	ATE value
Inhalation (dusts and mists)	117.44 mg/l

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
dipropylene glycol methyl ether	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
3-iodo-2-propynyl butylcarbamate (IPBC)	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Irritant	Mammal - species unspecified	-	-	-
1,2-benzisothiazol-3(2h)-one (BIT)	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Eyes - Irritant	Mammal - species unspecified	-	-	-

**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	skin	Mammal - species unspecified	Sensitising
3-iodo-2-propynyl butylcarbamate (IPBC)	skin	Mammal - species unspecified	Sensitising
1,2-benzisothiazol-3(2h)-one (BIT)	skin	Mouse	Sensitising
2-octyl-2h-isothiazol-3-one (OIT)	skin	Mammal - species unspecified	Sensitising

**Mutagenicity**

No known significant effects or critical hazards.

**Carcinogenicity**

**Pilot WF**

## SECTION 11: Toxicological information

No known significant effects or critical hazards.

### Reproductive toxicity

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-iodo-2-propynyl butylcarbamate (IPBC)	Category 1	-	trachea

### Aspiration hazard

Based on available data, the classification criteria are not met.

**Other information** : None identified.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	Acute EC50 0.0057 mg/l	Crustaceans - Daphnia magna	48 hours
	Acute LC50 0.014 mg/l	Fish - Lepomis macrochirus	96 hours
	Acute LC50 0.0027 mg/l	Fish - Onchorhynchus mykiss	96 hours
	Chronic NOEC 0.00056 mg/l	Fish	97 days
	Acute EC50 0.022 mg/l	Algae - Scenedesmus subspicatus	72 hours
3-iodo-2-propynyl butylcarbamate (IPBC)	Acute EC50 0.16 mg/l	Crustaceans - Daphnia magna	48 hours
	Acute LC50 0.067 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 70 ppb Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
		Algae - Slenastrum capricornutum	72 hours
1,2-benzisothiazol-3(2h)-one (BIT)	Acute EC50 0.15 mg/l	Crustaceans - Daphnia magna	96 hours
	Acute EC50 1.05 mg/l	Fish - Onchorhynchus mykiss	96 hours
	Acute EC50 0.0014 mg/l	Algae	72 hours
Amines, C12-18-alkyldimethyl 2-octyl-2h-isothiazol-3-one (OIT)	Acute EC50 0.084 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute EC50 0.32 mg/l	Daphnia	48 hours
	Acute LC50 0.047 mg/l	Fish	96 hours

This material is toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Not available.

**Pilot WF****SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
dipropylene glycol methyl ether	-	-	Readily
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	-	-	Readily
3-iodo-2-propynyl butylcarbamate (IPBC)	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
dipropylene glycol methyl ether	0.004	-	low
Amines, C12-18-alkyldimethyl	2.4	-	low
2-octyl-2h-isothiazol-3-one (OIT)	2.45	-	low

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**European waste catalogue (EWC)**

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

**Packaging**

**Pilot WF**

## SECTION 13: Disposal considerations





**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN3082	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. (paint)	Environmentally hazardous substance, liquid, n.o.s. (paint)	Environmentally hazardous substance, liquid, n.o.s. (paint). Marine pollutant (4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT))	Environmentally hazardous substance, liquid, n.o.s. (paint)
<b>14.3 Transport hazard class(es)</b>	9 	9 	9 	9 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.

### Additional information

**ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Hazard identification number** 90

**Tunnel code** (-)

**ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Emergency schedules** F-A, S-F

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

*Pilot WF*

## SECTION 14: Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not applicable.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Other EU regulations**

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not applicable.

**Europe inventory** : Not determined.

**Ozone depleting substances (1005/2009/EU)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Seveso Directive**

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

**National regulations**

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**International regulations**

**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

*Pilot WF*

## SECTION 15: Regulatory information

### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

**15.2 Chemical safety assessment** : Not applicable.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Calculation method Calculation method Calculation method Calculation method

### [Full text of abbreviated H statements](#)

H301 H302 H311 H314 H315 H317 H318 H319 H330 H331 H372	Toxic if swallowed. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Toxic if inhaled. Causes damage to organs through prolonged or repeated exposure.
H400 H410 H411	Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.

### [Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1 Skin Corr. 1B Skin Irrit. 2 Skin Sens. 1 STOT RE 1	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
--	--

**Date of printing** : 22.04.2021

*Pilot WF*

## **SECTION 16: Other information**

**Date of issue/ Date of revision** : 22.04.2021

**Date of previous issue** : 25.01.2019

**Version** : 2

### **Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.