





# Spontan Varnish AV

## Section 1. Identification

|   |  |
|---|--|
| <b>GHS product identifier</b>                               | : Spontan Varnish AV   |
| <b>Product code</b>   | : 13880  |
| <b>Product description</b>                                  | : Paint.   |
| <b>Other means of identification</b>                        | : Not available.   |
| <b>Product type</b>   | : Liquid.  |
| <b>Supplier's details</b>                                   | : Jotun Paints, Inc.<br>9203 Highway 23<br>Belle Chasse, LA 70037<br>Telephone: (800) 229-3538 or<br>+1 504-394-3538<br>SDSJotun@jotun.com |
| <b>Emergency telephone number (with hours of operation)</b> | : 1-800-424-9300<br>(Staffed 24/7)   |

## Section 2. Hazards identification

|   |  |
|---|--|
| <b>OSHA/HCS status</b>                            | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  |
| <b>Classification of the substance or mixture</b> | : FLAMMABLE LIQUIDS - Category 3<br>TOXIC TO REPRODUCTION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 2   |
| <b>GHS label elements</b>                         |  |
| <b>Hazard pictograms</b>                          | :       |
| <b>Signal word</b>                                | : Danger.  |
| <b>Hazard statements</b>                          | : H226 - Flammable liquid and vapor.<br>H336 - May cause drowsiness or dizziness.<br>H361 - Suspected of damaging fertility or the unborn child.<br>H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS))<br>H411 - Toxic to aquatic life with long lasting effects.   |
| <b>Precautionary statements</b>                   |  |
| <b>Prevention</b>                                 | : P201 - Obtain special instructions before use.<br>P280 - Wear protective gloves, protective clothing and eye or face protection.<br>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P273 - Avoid release to the environment.<br>P260 - Do not breathe vapor or spray.<br>P270 - Do not eat, drink or smoke when using this product. |

## Section 2. Hazards identification

|   |   |
|---|---|
| <b>Response</b>                         | : P391 - Collect spillage.<br>P308 + P313 - IF exposed or concerned: Get medical advice or attention.<br>P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. |
| <b>Storage</b>                          | : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.<br>P403 + P235 - Keep cool.  |
| <b>Disposal</b>                         | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.  |
| <b>Hazards not otherwise classified</b> | : None known.   |

## Section 3. Composition/information on ingredients

|                                      |                  |
|--------------------------------------|------------------|
| <b>Substance/mixture</b>             | : Mixture        |
| <b>Other means of identification</b> | : Not available. |

### CAS number/other identifiers

|                     |                   |
|---------------------|-------------------|
| <b>CAS number</b>   | : Not applicable. |
| <b>Product code</b> | : 13880           |

| Ingredient name   | %         | CAS number |
|---|-----------|------------|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | ≥10 - ≤25 | 8052-41-3  |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | ≤10       | 64742-95-6 |
| xylene  | ≤3        | 1330-20-7  |
| hexanoic acid, 2-ethyl-, zirconium salt                       | ≤0.3      | 22464-99-9 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

|                     |  |
|---------------------|--|
| <b>Eye contact</b>  | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.  |
| <b>Inhalation</b>   | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.  |
| <b>Skin contact</b> | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.   |
| <b>Ingestion</b>    | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

## Section 4. First aid measures

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
  - nausea or vomiting
  - headache
  - drowsiness/fatigue
  - dizziness/vertigo
  - unconsciousness
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
  - carbon dioxide
  - carbon monoxide

## Section 5. Fire-fighting measures

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits   |
|---|---|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene)   | <p><b>ACGIH TLV (United States, 3/2018).</b><br/>TWA: 100 ppm 8 hours.<br/>TWA: 525 mg/m<sup>3</sup> 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b><br/>TWA: 100 ppm 8 hours.<br/>TWA: 525 mg/m<sup>3</sup> 8 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b><br/>TWA: 500 ppm 8 hours.<br/>TWA: 2900 mg/m<sup>3</sup> 8 hours.</p> <p><b>NIOSH REL (United States, 10/2016).</b><br/>TWA: 350 mg/m<sup>3</sup> 10 hours.<br/>CEIL: 1800 mg/m<sup>3</sup> 15 minutes.</p>   |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene) xylene | <p>None</p> <p><b>ACGIH TLV (United States, 3/2020).</b><br/>STEL: 651 mg/m<sup>3</sup> 15 minutes.<br/>STEL: 150 ppm 15 minutes.<br/>TWA: 434 mg/m<sup>3</sup> 8 hours.<br/>TWA: 100 ppm 8 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b><br/>TWA: 435 mg/m<sup>3</sup> 8 hours.<br/>TWA: 100 ppm 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b><br/>STEL: 655 mg/m<sup>3</sup> 15 minutes.<br/>STEL: 150 ppm 15 minutes.<br/>TWA: 435 mg/m<sup>3</sup> 8 hours.<br/>TWA: 100 ppm 8 hours.</p>  |
| hexanoic acid, 2-ethyl-, zirconium salt                         | <p><b>ACGIH TLV (United States, 3/2020). Notes: as Zr</b><br/>STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.<br/>TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.</p> <p><b>NIOSH REL (United States, 10/2016). Notes: as Zr</b><br/>STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.<br/>TWA: 5 mg/m<sup>3</sup>, (as Zr) 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018). Notes: as Zr</b><br/>TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989). Notes: as Zr</b><br/>STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.<br/>TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.</p> |

## Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
- The breakthrough time must be greater than the end use time of the product.
- The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
- Gloves should be replaced regularly and if there is any sign of damage to the glove material.
- Always ensure that gloves are free from defects and that they are stored and used correctly.
- The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
- Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
- Wear suitable gloves tested to EN374.
- Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber, 4H, Teflon
- Not recommended, gloves(breakthrough time) < 1 hour: neoprene, butyl rubber, PVC
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

|  |  |
|--|--|
| Physical state                               | : Liquid.  |
| Color  | : Clear.   |
| Odor   | : Characteristic.  |
| Odor threshold                               | : Not applicable.  |
| pH   | : Not applicable.  |
| Melting point                                | : Not applicable.  |
| Boiling point                                | : Lowest known value: 136.16°C (277.1°F) (xylene). Weighted average: 169.31°C (336.8°F)  |
| Flash point                                  | : Closed cup: 39°C (102.2°F)   |
| Evaporation rate                             | : Highest known value: 0.77 (xylene) Weighted average: 0.16 compared with butyl acetate  |
| Flammability (solid, gas)                    | : Not applicable.  |
| Lower and upper explosive (flammable) limits | : 0.8 - 7.6%   |
| Vapor pressure                               | : Highest known value: 2.7 kPa (20.3 mm Hg) (at 20°C) (Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene)). Weighted average: 2.56 kPa (19.2 mm Hg) (at 20°C) |
| Vapor density                                | : Highest known value: 3.7 (Air = 1) (xylene).   |
| Relative density                             | : 0.954 g/cm <sup>3</sup> 7.96 pounds/gallon   |
| Solubility                                   | : Insoluble in the following materials: cold water and hot water.  |
| Partition coefficient: n-octanol/water       | : Not available.   |
| Auto-ignition temperature                    | : Lowest known value: 280 to 470°C (536 to 878°F) (Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene)).   |
| Decomposition temperature                    | : Not available.   |
| Viscosity                                    | : Kinematic (40°C (104°F)): >0.205 cm <sup>2</sup> /s (>20.5 mm <sup>2</sup> /s)   |

### Aerosol product

## Section 10. Stability and reactivity

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.  |
| Chemical stability                 | : The product is stable.  |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| Conditions to avoid                | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |
| Incompatible materials             | : Reactive or incompatible with the following materials:<br>oxidizing materials   |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name | Result                  | Species | Dose       | Exposure |
|-------------------------|-------------------------|---------|------------|----------|
| xylene                  | LC50 Inhalation Vapor   | Rat     | 20 mg/l    | 4 hours  |
|                         | LD50 Oral               | Rat     | 4300 mg/kg | -        |
|                         | TDL <sub>0</sub> Dermal | Rabbit  | 4300 mg/kg | -        |

#### Irritation/Corrosion

## Section 11. Toxicological information

| Product/ingredient name | Result                                       | Species       | Score  | Exposure                                   | Observation |
|-------------------------|--|---------------|--------|--|-------------|
| xylene                  | Eyes - Mild irritant<br>Skin - Mild irritant | Rabbit<br>Rat | -<br>- | 87 milligrams<br>8 hours 60<br>microliters | -<br>-      |

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

| Name  | Category                 | Route of exposure | Target organs                                    |
|---|--------------------------|-------------------|--|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | Category 3               | -                 | Narcotic effects                                 |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | Category 3               | -                 | Respiratory tract irritation                     |
| xylene  | Category 3<br>Category 3 | -                 | Narcotic effects<br>Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Name  | Category   | Route of exposure | Target organs                |
|---|------------|-------------------|------------------------------|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | Category 1 | -                 | central nervous system (CNS) |

### Aspiration hazard

| Name  | Result                         |
|---|--------------------------------|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | ASPIRATION HAZARD - Category 1 |
| xylene  | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : May cause drowsiness or dizziness.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.



## Section 11. Toxicological information

- Inhalation** : Adverse symptoms may include the following:  
 nausea or vomiting  
 headache  
 drowsiness/fatigue  
 dizziness/vertigo  
 unconsciousness  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

- General** : Causes damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route               | ATE value      |
|---------------------|----------------|
| Dermal              | 54866.95 mg/kg |
| Inhalation (vapors) | 997.58 mg/l    |

## Section 12. Ecological information

### Toxicity

## Section 12. Ecological information

| Product/ingredient name                                       | Result              | Species | Exposure |
|---|---------------------|---------|----------|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | Acute EC50 <10 mg/l | Daphnia | 48 hours |
|   | Acute IC50 <10 mg/l | Algae   | 72 hours |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | Acute LC50 <10 mg/l | Fish    | 96 hours |
|   | Acute EC50 <10 mg/l | Daphnia | 48 hours |
|   | Acute IC50 <10 mg/l | Algae   | 72 hours |
|   | Acute LC50 <10 mg/l | Fish    | 96 hours |

### Persistence and degradability

| Product/ingredient name                                       | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | -                 | -          | Not readily      |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | -                 | -          | Not readily      |
| xylene  | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name                                       | LogP <sub>ow</sub> | BCF         | Potential |
|---|--------------------|-------------|-----------|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | -                  | 10 to 2500  | high      |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | -                  | 10 to 2500  | high      |
| xylene  | 3.12               | 8.1 to 25.9 | low       |
| hexanoic acid, 2-ethyl-, zirconium salt                       | -                  | 2.96        | low       |

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations











**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**United States - RCRA Toxic hazardous waste "U" List**

## Section 13. Disposal considerations

| Ingredient | CAS #     | Status | Reference number |
|------------|-----------|--------|------------------|
| Xylene     | 1330-20-7 | Listed | U239             |

## Section 14. Transport information

|                            | DOT Classification  | TDG Classification  | Mexico Classification  | ADR/RID   | IMDG  | IATA   |
|----------------------------|---|---|--|---|---|--|
| UN number                  | UN1263  | UN1263  | UN1263   | UN1263  | UN1263  | UN1263   |
| UN proper shipping name    | Paint   | Paint   | Paint  | Paint   | Paint   | Paint  |
| Transport hazard class(es) | 3<br><br> | 3<br><br> | 3<br> | 3<br><br> | 3<br><br> | 3<br> |
| Packing group              | III   | III   | III  | III   | III   | III  |
| Environmental hazards      | Yes.  | Yes.  | Yes. The environmentally hazardous substance mark is not required.                     | Yes.  | Yes.  | Yes. The environmentally hazardous substance mark is not required.                       |

### Additional information

#### DOT Classification

- : This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids, that are marine pollutants, are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by vessel. This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a. **Reportable quantity** 4987.9 lbs / 2264.5 kg [627.06 gal / 2373.7 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

#### TDG Classification

- : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.

#### Mexico Classification

- : -

#### ADR/RID

- : Tunnel restriction code: (D/E)  
Hazard identification number: 30

#### IMDG

- : Emergency schedules (EmS): F-E, S-E  
Marine pollutant: Yes.

#### IATA

- : The environmentally hazardous substance mark may appear if required by other transportation regulations.

#### Special precautions for user

- : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 14. Transport information

Transport in bulk according to IMO instruments : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : TSCA 8(a) CDR Exempt/Partial exemption: Not determined  
 United States inventory (TSCA 8b): Not determined.  
 Clean Water Act (CWA) 307: ethylbenzene  
 Clean Water Act (CWA) 311: xylene; ethylbenzene

### Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

| Ingredient name | CAS number | %       |
|-----------------|------------|---------|
| xylene          | 1330-20-7  | 2.0048  |
| ethylbenzene    | 100-41-4   | 0.66828 |

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : FLAMMABLE LIQUIDS - Category 3  
 TOXIC TO REPRODUCTION - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

### Composition/information on ingredients

| Name  | %         | Classification   |
|---|-----------|--|
| Naphtha (petroleum), hydrodesulfurized heavy, (<0.1% Benzene) | ≥10 - ≤25 | FLAMMABLE LIQUIDS - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1<br>ASPIRATION HAZARD - Category 1  |
| Solvent naphtha (petroleum), light arom. (<0,1% Benzene)      | ≤10       | FLAMMABLE LIQUIDS - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>ASPIRATION HAZARD - Category 1   |
| xylene  | ≤3        | FLAMMABLE LIQUIDS - Category 3<br>ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>ASPIRATION HAZARD - Category 1 |
| hexanoic acid, 2-ethyl-, zirconium salt                       | ≤0.3      | TOXIC TO REPRODUCTION - Category 2   |

## Section 15. Regulatory information

### SARA 313

|                                 | Product name | CAS number | %  |
|---------------------------------|--------------|------------|----|
| Form R - Reporting requirements | xylene       | 1330-20-7  | ≤3 |
|                                 | ethylbenzene | 100-41-4   | <1 |
| Supplier notification           | xylene       | 1330-20-7  | ≤3 |
|                                 | ethylbenzene | 100-41-4   | <1 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: XYLENE; DIMETHYLBENZENE  
**New York** : The following components are listed: Xylene mixed  
**New Jersey** : The following components are listed: XYLENES; BENZENE, DIMETHYL-  
**Pennsylvania** : The following components are listed: BENZENE, DIMETHYL-

### California Prop. 65

**WARNING:** This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Ingredient name | Cancer | Reproductive | No significant risk level | Maximum acceptable dosage level |
|-----------------|--------|--------------|---------------------------|---------------------------------|
| ethylbenzene    | Yes.   | No.          | Yes.                      | -                               |

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### International lists

#### National inventory

- Australia** : Not determined.  
**Canada** : Not determined.  
**China** : Not determined.  
**Europe** : Not determined.  
**Japan** : Not determined.  
  
**Malaysia** : Not determined.  
**New Zealand** : Not determined.  
**Philippines** : Not determined.  
**Republic of Korea** : Not determined.  
**Taiwan** : Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | * | 3 |
| Flammability     |   | 2 |
| Physical hazards |   | 0 |
|                  |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



### Procedure used to derive the classification

| Classification   | Justification         |
|--|-----------------------|
| FLAMMABLE LIQUIDS - Category 3   | On basis of test data |
| TOXIC TO REPRODUCTION - Category 2   | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1                  | Calculation method    |
| AQUATIC HAZARD (LONG-TERM) - Category 2  | Calculation method    |

### History

**Date of printing** : 07.05.2021

**Date of issue/Date of revision** : 07.05.2021

**Date of previous issue** : 20.09.2018

**Version** : 1.04

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 UN = United Nations

**References** : Not available.

Indicates information that has changed from previously issued version.

### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

## **Section 16. Other information**

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.