

Jotun Facade 2288

| Section 1. Identification | |
|-------------------------------|--|
| Product identifier | : Jotun Facade 2288 |
| Product code | : 16397 |
| Product type | : Powder coating. |
| Other means of identification | : Not available. |
| Recommended use of the | chemical and restrictions on use |
| Use in coatings - Industrial | use |
| Supplier's details | : JOTUN POWDER COATINGS PAKISTAN (Pvt) Ltd. 2 KM DEFENCE ROAD, OFF 9 KM RAIWIND RD. NEAR VALANCIA HOMES GATE, LAHORE PAKISTAN |
| | Phone : + 92 42 53 20 438 Fax : + 92 42 53 20 468 sdsjotun@jotun.com |
| Emergency telephone number | : Jotun AS, Norway +47 33 45 70 00 |

| Section 2. Hazard identification | |
|---|--|
| Classification of the substance or mixture | : LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| GHS label elements | |
| Signal word | : No signal word. |
| Hazard statements | : H412 - Harmful to aquatic life with long lasting effects. |
| Precautionary statements | |
| General | : Not applicable. |
| Prevention | : P273 - Avoid release to the environment. |
| Response | : Not applicable. |
| Storage | : Not applicable. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Other hazards which do not result in classification | : None known. |

Section 3. Composition/information on ingredients

Substance/mixture

Other means of identification

- : Mixture
- : Not available.

| Ingredient name | % | CAS number |
|--|----|------------|
| 2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis | ≤1 | 26741-53-7 |
| (1,1-dimethylethyl)phenoxy]- | | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. |
|--------------|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. |
| Ingestion | Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. |

Most important symptoms/effects, acute and delayed

| Eye contact | : No known significant effects or critical hazards. |
|--------------------|---|
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : No known significant effects or critical hazards. |
| Ingestion | : No known significant effects or critical hazards. |
| ver-exposure signs | /symptoms |
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |

| Indication of immediate medical attention and special treatment needed, if necessary | | |
|--|--|--|
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. | |
| Specific treatments | : No specific treatment. | |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. | |

See toxicological information (Section 11)

Section 5. Firefighting measures

| Extinguishing media | |
|--|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : Fine dust clouds may form explosive mixtures with air. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides |
| Special protective actions for fire-fighters | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| Personal precautions, protect | ive equipment and emergency procedures |
|--------------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| Methods and material for con | tainment and cleaning up |
| Small spill | : Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. |
| Laws and | · Many southing a frame will and a Annual of the values of frame variant. Descent anter |

Large spill
 Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

 Protective measures
 Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

| | - | • |
|--|---|---|
| Advice on general occupational hygiene | : | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : | Store in accordance with local regulations. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. |

See Technical Data Sheet / packaging for further information.

Section 8. Exposure controls/personal protection

Control parameters

Dust Limit : 10 mg/m³ (TWA of total inhalable dust) and 4 mg/m³ (TWA of respirable)

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

| Appropriate engineering controls | : Good general ventilation should be sufficient to control worker exposure to airborne contaminants. |
|-------------------------------------|---|
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some |

| controls | they comply with the requirements of environmental protection legislation. In some |
|----------|--|
| | cases, fume scrubbers, filters or engineering modifications to the process |
| | equipment will be necessary to reduce emissions to acceptable levels. |

| Individual protection measures | |
|--------------------------------|---|
| Hygiene measures : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection : | Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. |
| Skin protection | |
| Hand protection : | There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. |

| Date of issue/Date of revision | : 12.09.2023 | Date of previous issue | : 12.09.2023 | Version : 1.01 |
|--------------------------------|--------------|------------------------|--------------|----------------|
|--------------------------------|--------------|------------------------|--------------|----------------|

Section 8. Exposure controls/personal protection

| | Wear suitable gloves tested to ISO 374-1:2016. Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber (> 0.75 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm) |
|------------------------|---|
| | For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves. |
| | The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. If dust is generated and ventilation is inadequate, use respirator that will protect against dust/mist. (FFP2 / N95). |
| | |

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

| Appearance | | | |
|--|---|--|--|
| Physical state | : | Solid. Powder. | |
| Colour | : | Various | |
| Odour | : | Odourless. | |
| Odour threshold | : | Not applicable. | |
| рН | : | Not applicable. | |
| Melting point (dust) | : | 85 - 115 °C | |
| Boiling point | : | Not applicable. | |
| Flash point | : | Not applicable. | |
| Evaporation rate | 1 | Not applicable. | |
| Flammability | | Fine dust clouds may form explosive mixtures with air. | |
| Lower explosion limit (dust) | 4 | 30 g/m³ (EN 14034-3) | |
| Minimum ignition energy (mJ) | 1 | 10 - 30 (EN 13821) | |
| Vapour pressure | : | Not applicable. | |
| Vapour density | 1 | Not applicable. | |
| Density | : | 1.2 to 1.9 g/cm ³ | |
| Solubility(ies) | 3 | | |
| Media | | Result | |
| cold water | | Not soluble | |
| hot water | | Not soluble | |
| Partition coefficient: n- octanol/water | 1 | Not applicable. | |
| Auto-ignition temperature | : | : >400°C | |
| Decomposition temperature | : | : 230°C (446°F) | |
| Viscosity | : | Not applicable. | |
| Particle characteristics | | | |
| Median particle size | 3 | Not available. | |
| | | | |

Date of issue/Date of revision

Section 10. Stability and reactivity

| Reactivity | : Fine dust clouds may form explosive mixtures with air. |
|------------------------------------|--|
| Chemical stability | : Stable under recommended storage and handling conditions (see Section 7). |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). |
| | Take precautionary measures against electrostatic discharges. |
| | To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. |
| | Prevent dust accumulation. |
| Incompatible materials | : Not applicable. |
| Hazardous decomposition products | : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. |
| Hazardous decomposition | To avoid fire or explosion, dissipate static electricity during transfer by earthing a bonding containers and equipment before transferring material. Prevent dust accumulation. Not applicable. Decomposition products may include the following materials: carbon monoxide, |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|------------------------|---------|-------|-----------|-------------|
| 2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane, 3,9-bis[2,4-bis (1,1-dimethylethyl)phenoxy]- | Skin - Severe irritant | Rabbit | - | 0.5 Grams | - |

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure Potential acute health effects

| Eye contact | : No known significant effects or critical hazards. |
|--------------|---|
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : No known significant effects or critical hazards. |
| | |

Date of issue/Date of revision

Section 11. Toxicological information

Ingestion

: No known significant effects or critical hazards.

| Symptoms related to the | physical, chemical and t | toxicological characteristics |
|-------------------------|--------------------------|---|
| | phyoroun onormour and t | exite of equal to that a determent of the |

| Eye contact | : No specific data. |
|--------------|---------------------|
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| : Not available. |
|---|
| : Not available. |
| |
| : Not available. |
| : Not available. |
| <u>ects</u> |
| |
| : No known significant effects or critical hazards. |
| : No known significant effects or critical hazards. |
| : No known significant effects or critical hazards. |
| |
| |

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--|---|--------------------------|---------------------------------|
| 2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane, 3,9-bis[2,4-bis (1,1-dimethylethyl)phenoxy]- | Acute EC10 15.4 mg/l | Algae | 72 hours |
| | Acute EC50 97 mg/l Acute LC50 70.7 mg/l Chronic NOEC 0.1 mg/l | Algae Fish Daphnia | 72 hours 96 hours 21 days |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | ΙΑΤΑ |
|-------------------------------|----------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

International regulations

<u>Chemical Weapon Convention List Schedules I, II & III Chemicals</u> Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Date of issue/Date of revision

Section 15. Regulatory information

Not listed.

History

Section 16. Other information

| History | |
|--------------------------------|--|
| Date of printing | : 12.09.2023 |
| Date of issue/Date of revision | : 12.09.2023 |
| Date of previous issue | : 12.09.2023 |
| Version | : 1.01 |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations |

Procedure used to derive the classification

| Classification | Justification |
|---|--------------------|
| LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 | Calculation method |

References

: Not available.

V Indicates information that has changed from previously issued version.

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.