# SAFETY DATA SHEET



# Jotapipe AC 2002 24S

# Section 1. Identification

**GHS** product identifier

: Jotapipe AC 2002 24S

**Product code** 

16426

Other means of identification

: Not available.

**Product type** 

: Powder coating.

Supplier's details

: Jotun Paints, Inc. 9203 Highway 23 Belle Chasse, LA 70037

Belle Chasse, LA 70037 Telephone: (800) 229-3538 or

+1 504-394-3538 SDSJotun@jotun.com

Emergency telephone number (with hours of

: 1-800-424-9300 (Staffed 24/7)

operation)

# Section 2. Hazards identification

#### **OSHA/HCS** status

Classification of the substance or mixture

- : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- : EYE IRRITATION Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION (Fertility) - Category 1B TOXIC TO REPRODUCTION (Unborn child) - Category 1B

AQUATIC HAZARD (LONG-TERM) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity:

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 1.5%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation

toxicity: 1.5%

Percentage of the mixture consisting of ingradient(s) of unknown beyonds to the agust

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 1.5%

# **GHS label elements**

Hazard pictograms







Signal word

: Danger.

**Hazard statements** 

: H319 - Causes serious eye irritation.

H317 - May cause an allergic skin reaction. H360 - May damage fertility or the unborn child.

H351 - Suspected of causing cancer.

H411 - Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

Date of issue : 26.08.2020 1/14

# Section 2. Hazards identification

Prevention : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.

P273 - Avoid release to the environment. P264 - Wash hands thoroughly after handling.

P272 (OSHA) - Contaminated work clothing must not be allowed out of the workplace.

Response : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical attention.

P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse.

P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise classified

identification

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of : Not available.

**CAS** number/other identifiers

**CAS number** : Not applicable.

Product code : 16426

Ingredient name	%	CAS number
zinc	≤5	7440-66-6
titanium dioxide	≤3	13463-67-7
phenol, polymer with formaldehyde, glycidyl ether	≤3	28064-14-4
bisphenol a	<3	80-05-7
zinc oxide	≤0.3	1314-13-2
1h-imidazole, 2-methyl-	≤0.3	693-98-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

# **Description of necessary first aid measures**

Eye contact : Immediately

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Date of issue** : 26.08.2020 **2/14** 

# Section 4. First aid measures

#### **Skin contact**

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

# Most important symptoms/effects, acute and delayed

## Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

**Date of issue** : 26.08.2020 3/14

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Fine dust clouds may form explosive mixtures with air.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

sulfur oxides metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

## Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**Date of issue** :26.08.2020 4/14

# Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

See Technical Data Sheet / packaging for further information.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

## **Occupational exposure limits**

OSHA Nuisance Dust Limit of 15 mg/m³ (total) and 5 mg/m³ (respirable). ACGIH Nuisance Dust Limit of 10 mg/m³ (total) and 3 mg/m³ (respirable).

Ingredient name	Exposure limits
zinc titanium dioxide	None OSHA PEL (United States, 5/2018). TWA: 15 mg/m³ 8 hours. Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2018). TWA: 10 mg/m³ 8 hours.
phenol, polymer with formaldehyde, glycidyl ether bisphenol a zinc oxide	None NIOSH REL (United States, 10/2016). CEIL: 15 mg/m³ Form: Dust TWA: 5 mg/m³ 10 hours. Form: Dust and fumes STEL: 10 mg/m³ 15 minutes. Form: Fume OSHA PEL 1989 (United States, 3/1989). STEL: 10 mg/m³ 15 minutes. Form: Fume TWA: 5 mg/m³ 8 hours. Form: Fume TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 10 mg/m³ 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 5 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2018). STEL: 10 mg/m³ 15 minutes. Form:

**Date of issue** : 26.08.2020 5/14

# Section 8. Exposure controls/personal protection

•	bection of Exposure controls/bersonal brote	Ction
		Respirable fraction TWA: 2 mg/m³ 8 hours. Form: Respirable fraction
	1h-imidazole, 2-methyl-	None

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **Individual protection measures**

# **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to EN374.

Recommended, gloves(breakthrough time) > 8 hours: butyl rubber, nitrile rubber, neoprene, PVC

## **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Date of issue** : 26.08.2020 **6/14** 

# Section 8. Exposure controls/personal protection

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Solid. Powder.

Color : Various
Odor : Odorless.

Odor threshold : Not applicable.
pH : Not applicable.

Melting point (dust) : 85 - 115 °C

Boiling point : Not applicable.

Flash point : Not applicable.

Evaporation rate : Not applicable.

Flammability (solid, gas) : Fine dust clouds may form explosive mixtures with air.

**Lower explosion limit (dust)** : 30 g/m³ (EN 14034-3) **Minimum ignition energy** : 10 - 30 (EN 13821)

(mJ)

Vapor pressure: Not applicable.Vapor density: Not applicable.

**Relative density**: 1.55 to 1.65 g/cm<sup>3</sup> 12.93 to 13.77 pounds/gallon

**Solubility** : Insoluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : > 400°C

**Decomposition temperature** : >250°C (>482°F) **Viscosity** : Not applicable.

# Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous

. The product to classe

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame).

Take precautionary measures against electrostatic discharges.

To avoid fire or explosion, dissipate static electricity during transfer by grounding and

bonding containers and equipment before transferring material.

Prevent dust accumulation.

Incompatible materials

**Hazardous decomposition** 

products

: No specific data.

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

**Date of issue** : 26.08.2020 **7/14** 

# Section 11. Toxicological information

# Information on toxicological effects

# **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1h-imidazole, 2-methyl-	LD50 Oral	Mouse	1400 mg/kg	-

# **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
zinc	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
phenol, polymer with formaldehyde, glycidyl ether	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
bisphenol a	Eyes - Severe irritant	Rabbit	-	24 hours 250 Micrograms	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	250 milligrams	-
	Eyes - Irritant	Mammal - species unspecified	-	-	-
zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

# **Sensitization**

• • • • • • • • • • • • • • • • • • • •	Route of exposure	Species	Result
phenol, polymer with formaldehyde, glycidyl ether	skin	Mammal - species unspecified	Sensitizing
bisphenol a	skin	Mammal - species unspecified	Sensitizing

# **Mutagenicity**

Not available.

# **Carcinogenicity**

Not available.

# **Classification**

Product/ingredient name C	OSHA	IARC	NTP
titanium dioxide -		2B	-
1h-imidazole, 2-methyl		2B	-

# **Reproductive toxicity**

Not available.

# **Teratogenicity**

Not available.

# Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
bisphenol a	Category 3		Respiratory tract irritation

**Date of issue** : 26.08.2020 **8/14** 

# **Section 11. Toxicological information**

# Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

## Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

## Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity**: May damage the unborn child.

**Developmental effects**: No known significant effects or critical hazards.

Fertility effects : May damage fertility.

**Date of issue** : 26.08.2020 9/14

# Section 11. Toxicological information

# Numerical measures of toxicity Acute toxicity estimates

Not available.

# Section 12. Ecological information

# **Toxicity**

Product/ingredient name	Result	Species	Exposure
zinc	Acute LC50 330 μg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.78 mg/l Fresh water	Fish	96 hours
phenol, polymer with formaldehyde, glycidyl ether	Acute EC50 3.3 mg/l	Daphnia	48 hours
	Acute LC50 7.5 mg/l	Fish	96 hours
bisphenol a	Acute EC50 1000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
·	Acute EC50 1.506 mg/l	Algae - Prorocentrum minimum - Exponential growth phase	72 hours
	Acute EC50 7.75 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1.34 mg/l Marine water	Crustaceans - Americamysis bahia - Larvae	48 hours
	Acute LC50 3.5 mg/l Marine water	Fish - Rivulus marmoratus - Embryo	96 hours
	Chronic NOEC 2 mg/l Fresh water	Algae - Chlorolobion braunii - Exponential growth phase	4 days
	Chronic NOEC 0.05 mg/l Fresh water	Crustaceans - Asellus aquaticus - Juvenile (Fledgling, Hatchling, Weanling)	21 days
	Chronic NOEC 30 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.2 µg/l Fresh water	Fish - Carassius auratus - Adult	90 days
zinc oxide	Acute LC50 1.1 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.02 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
1h-imidazole, 2-methyl-	Acute LC50 286000 to 307000 μg/l Fresh water	Fish - Pimephales promelas	96 hours

# Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
zinc phenol, polymer with formaldehyde, glycidyl ether	-		Not readily Not readily
zinc oxide	-	-	Not readily

# **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
bisphenol a zinc oxide	3.4	20 to 67 60960	low high
1h-imidazole, 2-methyl-	0.24	-	low

# **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

**Date of issue** : 26.08.2020 **10/14** 

# Section 12. Ecological information

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN3077	UN3077	UN3077	UN3077	UN3077	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (zinc)					
Transport hazard class(es)	9	9	9	9	9	9
Packing group	III	III	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.	Yes.	Yes.

#### **Additional information**

**DOT Classification** 

: Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg.

**Reportable quantity** 22361.9 lbs / 10152.3 kg. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**TDG Classification** 

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.

**Mexico Classification** 

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

ADR/RID

: Tunnel restriction code: (-)
Hazard identification number: 90

**Date of issue** : 26.08.2020 11/14

Jotapipe AC 2002 24S

# Section 14. Transport information

Emergency schedules (EmS): F-A, S-F

Marine pollutant: Yes.

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and

5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL and

the IBC Code

# Section 15. Regulatory information

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined U.S. Federal regulations

United States inventory (TSCA 8b): Not determined.

Clean Water Act (CWA) 307: zinc oxide; zinc; c.i. pigment green 7

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** 

(Essential Chemicals)

: Not listed

# **SARA 302/304**

#### **Composition/information on ingredients**

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : EYE IRRITATION - Category 2A

> SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION (Fertility) - Category 1B TOXIC TO REPRODUCTION (Unborn child) - Category 1B

# **Composition/information on ingredients**

Name	%	Classification	
titanium dioxide	≤3	CARCINOGENICITY - Category 2	
phenol, polymer with	≤3	SKIN IRRITATION - Category 2	
formaldehyde, glycidyl ether		EYE IRRITATION - Category 2A	
		SKIN SENSITIZATION - Category 1	
bisphenol a	<3	SERIOUS EYE DAMAGE - Category 1	
·		SKIN SENSITIZATION - Category 1	
		TOXIC TO REPRODUCTION (Fertility) - Category 1B	
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)	
		(Respiratory tract irritation) - Category 3	
1h-imidazole, 2-methyl-	≤0.3	ACUTE TOXICITY (oral) - Category 4	
		SKIN CORROSION - Category 1C	
		SERIOUS EYE DAMAGE - Category 1	
		CARCINOGENICITY - Category 2	
		<b>5</b> ,	

**Date of issue** :26.08.2020 12/14 Jotapipe AC 2002 24S

# Section 15. Regulatory information

TOXIC TO REPRODUCTION (Unborn child) - Category 1B

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements		7440-66-6 80-05-7	≤5 <3
Supplier notification		7440-66-6 80-05-7	≤5 <3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### State regulations

Massachusetts : The following components are listed: ZINC; titanium dioxide; BARIUM SULFATE; 4,4'-

ISOPROPYLIDENEDIPHENOL

New York : The following components are listed: Zinc

**New Jersey** : The following components are listed: ZINC; titanium dioxide; barium sulfate; titanium

dioxide; BISPHENOL A; 4,4'-ISOPROPYLIDENEDIPHENOL

Pennsylvania : The following components are listed: ZINC COMPOUNDS; titanium dioxide; BARIUM

SULFATE; titanium dioxide; 4,4'-ISOPROPYLIDENEDIPHENOL

## California Prop. 65

**WARNING**: This product can expose you to chemicals including Titanium dioxide and Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	Cancer	•		Maximum acceptable dosage level
titanium dioxide titanium dioxide		No. No.	-	-

#### **International regulations**

## Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

# **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

# **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

## **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

# **International lists**

#### **National inventory**

Australia: Not determined.Canada: Not determined.China: Not determined.Europe: Not determined.Japan: Not determined.

Malaysia : Not determined.

New Zealand : Not determined.

Philippines : Not determined.

Republic of Korea : Not determined.

**Date of issue** : 26.08.2020 **13/14** 

Jotapipe AC 2002 24S

# Section 15. Regulatory information

Taiwan : Not determined.

# Section 16. Other information

# Procedure used to derive the classification

Classification		Justification	
	Eye Irrit. 2A, H319	Calculation method	
	Skin Sens. 1, H317	Calculation method	
	Carc. 2, H351	Calculation method	
	Repr. 1B, H360 (Fertility)	Calculation method	
	Repr. 1B, H360 (Unborn child)	Calculation method	
Aquatic Chronic 2, H411		Calculation method	

#### **History**

Date of printing : 26.08.2020

Date of issue/Date of : 26.08.2020

revision

Date of previous issue : No previous validation

Version :

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

▼ Indicates information that has changed from previously issued version.

### **Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue : 26.08.2020 14/14