SAFETY DATA SHEET



Tradex T (B006)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Tradex T (B006)

Product code : 22623
Product description : Paint.

Product type : Powder coating.

Other means of : Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use

1.3 Details of the supplier of the safety data sheet

JOTUN CZECH a.s. NA ROVNEM 866 400 04 TRMICE CZECH REPUBLIC

Phone: + 420 477 828 969 Fax.: + 420 477 828 962 sdspowder@jotun.com

1.4 Emergency telephone number

Contact NHS Direct; phone 0845 4647 or 111. Open 24/7.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms







Signal word : Danger.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 1/13

SECTION 2: Hazards identification

Hazard statements : H302 - Harmful if swallowed.

H318 - Causes serious eye damage. H317 - May cause an allergic skin reaction.

H340 - May cause genetic defects.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention: P201 - Obtain special instructions before use.

P280 - Wear protective gloves. Wear eye or face protection. Wear protective

clothing.

P273 - Avoid release to the environment.

Response : P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazardous ingredients: 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1h,3h,5h)-trione

zinc di(benzothiazol-2-yl) disulphide

N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6,6-tetramethylpiperidin-4-yl)amino)

triazin-2-yl)-4,7-diazadecane-1,10-diamine

benzothiazole-2-thiol

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	Weight %	Regulation (EC) No. 1272/2008 [CLP]	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Not classified.	[2]
barium sulfate	EC: 231-784-4 CAS: 7727-43-7	≥10 - ≤25	Not classified.	[2]
1,3,5-tris(oxiranylmethyl)-1,3, 5-triazine-2,4,6(1h,3h,5h)-trione	EC: 219-514-3 CAS: 2451-62-9 Index: 615-021-00-6	<10	Acute Tox. 3, H301 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340	[1] [2]

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 2/13

SECTION 3: Composition/information on ingredients

zinc di(benzothiazol-2-yl) disulphide	EC: 205-840-3 CAS: 155-04-4	<1	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410	[1]
N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6,6-tetramethylpiperidin-4-yl)amino)triazin-2-yl)-4, 7-diazadecane-1,10-diamine benzothiazole-2-thiol	EC: 401-990-0 CAS: 106990-43-6 EC: 205-736-8 CAS: 149-30-4	<1 ≤0.3	STOT RE 2, H373 (lymphatic system) Aquatic Chronic 2, H411	[1]
	Index: 613-108-00-3		Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give
		anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical

water for at least 15 minutes, keeping eyelids open. Seek immediate medica attention.

Inhalation : Remove

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 3/13

SECTION 4: First aid measures

Skin contact

: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion

: Adverse symptoms may include the following:

stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO₂ blanket, water spray or mist.

Unsuitable extinguishing

media

Do not use water iet.

Do not use inert gas under high pressure (e.g. CO2).

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Fine dust clouds may form explosive mixtures with air.

Hazardous combustion products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.

For emergency responders :

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 4/13

SECTION 6: Accidental release measures

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe handling

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Dust Limit: 10 mg/m³ (TWA of total inhalable dust) and 4 mg/m³ (TWA of respirable)

Product/ingredient name	Exposure limit values
titanium dioxide	EH40/2005 WELs (United Kingdom (UK), 8/2018).
	TWA: 10 mg/m³ 8 hours. Form: inhalable dust
	TWA: 4 mg/m³ 8 hours. Form: respirable dust
barium sulfate	EH40/2005 WELs (United Kingdom (UK), 8/2018).
	TWA: 10 mg/m³ 8 hours. Form: inhalable dust
	TWA: 4 mg/m³ 8 hours. Form: respirable dust
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6	EH40/2005 WELs (United Kingdom (UK), 8/2018).
(1h,3h,5h)-trione	TWA: 0.1 mg/m ³ 8 hours.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 5/13

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Gloves

: There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to EN374.

Recommended, gloves(breakthrough time) > 8 hours: PVC

May be used, gloves(breakthrough time) 4 - 8 hours: nitrile rubber, neoprene, polyvinyl alcohol (PVA)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 6/13

SECTION 8: Exposure controls/personal protection

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of

use, as included in the user's risk assessment.

: Personnel should wear protective clothing. Care should be taken in the selection of **Body protection** protective clothing to ensure that inflammation and irritation of the skin at the neck

and wrists through contact with the powder are avoided.

Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: If workers are exposed to concentrations above the exposure limit, they must use a Respiratory protection

respirator according to EN 140. If dust is generated and ventilation is inadequate,

use respirator that will protect against dust/mist. (FFP2 / N95).

Environmental exposure

controls

: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid. Powder.

: Various Colour **Odour** : Odourless. **Odour threshold** Not applicable. pН : Not applicable. : 85 - 115 °C **Melting point (dust)**

Initial boiling point and

boiling range

Not applicable.

Flash point : Not applicable. : Not applicable. **Evaporation rate**

: Fine dust clouds may form explosive mixtures with air. Flammability (solid, gas)

: 30 g/m³ (EN 14034-3) **Lower explosion limit (dust)** Minimum ignition energy (mJ) : 10 - 30 (EN 13821) Vapour pressure : Not applicable. : Not applicable. Vapour density : 1.2 to 1.9 g/cm³ **Density**

Solubility(ies) : Insoluble in the following materials: cold water and hot water.

Partition coefficient: n-octanol/ : Not applicable.

water

: >450°C **Auto-ignition temperature Decomposition temperature** : >230°C

Viscosity : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : Fine dust clouds may form explosive mixtures with air.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions

10.4 Conditions to avoid Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame).

Date of issue/Date of revision : 04.02.2020 Version : 1 7/13 Date of previous issue : No previous validation

SECTION 10: Stability and reactivity

Take precautionary measures against electrostatic discharges.

To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.

Prevent dust accumulation.

10.5 Incompatible materials

10.6 Hazardous

decomposition products

: Not applicable.

Decomposition products may include the following materials: carbon monoxide,

carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3,5-triazine-2,4,6(1h,3h,5h)-	LD50 Oral	Rat	138 mg/kg	-
trione zinc di(benzothiazol-2-yl) disulphide	LD50 Oral	Rat	540 mg/kg	-
benzothiazole-2-thiol	LD50 Dermal	Rabbit	>7940 mg/kg	-

Acute toxicity estimates

Route	ATE value	
	1478.9 mg/kg 44.37 mg/l	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-tris(oxiranylmethyl)-1,3, 5-triazine-2,4,6(1h,3h,5h)- trione	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Eyes - Irritant	Mammal - species unspecified	-	-	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
1,3,5-tris(oxiranylmethyl)-1,3, 5-triazine-2,4,6(1h,3h,5h)- trione	skin	Mammal - species unspecified	Sensitising
zinc di(benzothiazol-2-yl) disulphide	skin	Mammal - species unspecified	Sensitising
N,N,N,N-tetrakis(4,6-bis (butyl-(N-methyl-2,2,6, 6-tetramethylpiperidin-4-yl) amino)triazin-2-yl)-4, 7-diazadecane-1,10-diamine	skin	Mammal - species unspecified	Sensitising
benzothiazole-2-thiol	skin	Mammal - species unspecified	Sensitising

Mutagenicity

May cause genetic defects.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 8/13

SECTION 11: Toxicological information

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1h,3h,5h)-trione	Category 2	Not determined	Not determined
N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6, 6-tetramethylpiperidin-4-yl)amino)triazin-2-yl)-4, 7-diazadecane-1,10-diamine	Category 2	Not determined	lymphatic system

Aspiration hazard

Based on available data, the classification criteria are not met.

Other information : None identified.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
benzothiazole-2-thiol	Acute EC50 230 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 4.19 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Daphnia - Daphnia magna Fish - Oncorhynchus mykiss	48 hours 96 hours

This material is harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzothiazole-2-thiol	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3,5-tris(oxiranylmethyl)-1,3, 5-triazine-2,4,6(1h,3h,5h)- trione	-0.8	-	low
zinc di(benzothiazol-2-yl) disulphide	5.02	<8	low
N,N,N,N-tetrakis(4,6-bis (butyl-(N-methyl-2,2,6, 6-tetramethylpiperidin-4-yl) amino)triazin-2-yl)-4, 7-diazadecane-1,10-diamine	-0.94	-	low
benzothiazole-2-thiol	2.42	18.35	low

12.4 Mobility in soil

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 9/13

SECTION 12: Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

 08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Type of packaging

CEPE Paint Guidelines

15 01 10*

European waste catalogue (EWC)

packaging containing residues of or contaminated by hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 10/13

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
1,3,5-Tris(oxiran-2-ylmethyl)-1,3, 5-triazinane-2,4,6-trione; TGIC	Mutagen	Candidate	ED/87/2012	18.06.2012

Annex XVII - Restrictions : Restricted to professional users.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC : Not available. **VOC for Ready-for-Use** : Not applicable.

Mixture

: Not determined. **Europe inventory**

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Date of issue/Date of revision : 04.02.2020 Version:1 11/13 Date of previous issue : No previous validation

SECTION 15: Regulatory information

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Industrial use

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Product/ingredient name	List name	Name on list	Classification	Notes
1,3,5-tris(oxiranylmethyl)-1, 3,5-triazine-2,4,6(1H,3H,5H) -trione	Exposure Limits EH40 - WEL	triglycidyl isocyanurate; 1,3, 5-triglycidyl isocyanurate	Carc.	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: Not applicable.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Muta. 1B, H340	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision: 04.02.2020Date of previous issue: No previous validationVersion: 1

SECTION 16: Other information

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H340	May cause genetic defects.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 3, H301 Acute Tox. 3, H331 Acute Tox. 4, H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Eye Dam. 1, H318 Muta. 1B, H340 Skin Sens. 1, H317 STOT RE 2, H373	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 ACUTE TOXICITY (oral) - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 GERM CELL MUTAGENICITY - Category 1B SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
---	---

Date of printing : 04.02.2020 Date of issue/ Date of : 04.02.2020

revision

Date of previous issue : No previous validation

Version : 1

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue/Date of revision : 04.02.2020 Date of previous issue : No previous validation Version : 1 13/13