

Jotachar JF750 Comp A

Section 1. Identification

GHS product identifier : Jotachar JF750 Comp A
Product code : 22740
Other means of identification : Not available.
Product type : Liquid.
Product description : Paint.

Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use
Use in coatings - Professional use

Supplier's details : 佐敦涂料（张家港）有限公司
江苏省张家港保税区扬子江化学工业园长江路15号 215634
电话: +86 512 58937988
传真: +86 512 58937986

Jotun Coatings (Zhangjiagang) Co. Ltd
No.15 Changjiang Road Jiangsu Yangtze River International Chemical Industry Park,
Zhangjiagang Free Trade Zone, Jiangsu Province 215634
Tel: +86 512 58937988
Fax: +86 512 58937986

Jotun Paints (Malaysia) Sdn Bhd, Lot 7 Persiaran Perusahaan, Section 23
40300 SHAH ALAM, Selangor Darul Ehsan
Malaysia
Tel: +603 51235500
Fax: +603 51235599

SDSJotun@jotun.com

Emergency telephone number (with hours of operation) : Jotun Coatings (Taiwan) Ltd. Co. Tel: +886 2 87705061

Section 2. Hazards identification

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A
SKIN SENSITISATION - Category 1
REPRODUCTIVE TOXICITY - Category 1B
AQUATIC TOXICITY (ACUTE) - Category 2
AQUATIC TOXICITY (CHRONIC) - Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger.

Section 2. Hazards identification

- Hazard statements** : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H360 - May damage fertility or the unborn child.
H411 - Toxic to aquatic life with long lasting effects.
- Precautionary statements**
- Prevention** : P201 - Obtain special instructions before use.
P280 - Wear protective gloves, protective clothing and eye or face protection.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapour.
- Response** : P391 - Collect spillage.
P308 + P313 - IF exposed or concerned: Get medical advice or attention.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Other hazards which do not result in classification** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

| Product name | % (w/w) | CAS number | Type |
|---------------------------------------|-----------|-------------|------|
| epoxy resin (MW ≤ 700) | ≥25 - ≤50 | 1675-54-3 | [1] |
| Phenol, isobutylated, phosphate (3:1) | ≥10 - <25 | 68937-40-6 | [1] |
| hexaboron dizinc undecaoxide, hydrate | ≥10 - <25 | 138265-88-0 | [1] |
| 产品名称 | % (w/w) | CAS号码 | 类型 |
| 环氧树脂 (MW < 700) | ≥25 - ≤50 | 1675-54-3 | [1] |
| 异丁基化苯酚磷酸酯 (3:1) | ≥10 - <25 | 68937-40-6 | [1] |
| hexaboron dizinc undecaoxide, hydrate | ≥10 - <25 | 138265-88-0 | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Hand protection : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. Wear suitable gloves tested to ISO 374-1:2016. Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber (> 0.4 mm), butyl rubber (> 0.4 mm)

Section 8. Exposure controls/personal protection

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Eye protection : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Colour : Grey

Odour : Characteristic.

Odour threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not applicable.

Boiling point, initial boiling point, and boiling range : Not available.

Flash point :

| Ingredient name | Closed cup | | | Open cup | | |
|---|------------|-------|-----------|----------|-------|--------|
| | °C | °F | Method | °C | °F | Method |
| hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | 39 | 102.2 | ISO 13736 | | | |
| epoxy resin (MW ≤ 700) | | | | 79 | 174.2 | |
| Phenol, isobutylated, phosphate (3:1) | >80 | >176 | | | | |

Flammability : Not available.

Lower and upper explosion limit/flammability limit : Not applicable.

Vapour pressure :

Section 9. Physical and chemical properties and safety characteristics

| Ingredient name | Vapour Pressure at 20 °C | | | Vapour pressure at 50 °C | | |
|---|--------------------------|--------------|--------|--------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | 20.25 | 2.7 | | | | |
| water | 17.5 | 2.3 | | | | |
| Phenol, isobutylenated, phosphate (3:1) | 0.00000031 | 0.000000041 | | | | |
| pentaerythritol | 0.000000026 | 0.0000000035 | | | | |
| epoxy resin (MW ≤ 700) | 0 | 0 | | | | |
| 1,3-propanediol, 2,2'-[oxybis(methylene)]bis[2-(hydroxymethyl)- | 0 | 0 | | | | |

Relative vapour density : Not available.

Density : 1.07 g/cm³

Solubility(ies) :

| Media | Result |
|------------|-------------|
| cold water | Not soluble |
| hot water | Not soluble |

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

| Ingredient name | °C | °F | Method |
|---|------------|------------|---------|
| carbon | <200 | <392 | |
| hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | 280 to 470 | 536 to 878 | |
| pentaerythritol | >400 | >752 | EU A.16 |
| 1,3-propanediol, 2,2'-[oxybis(methylene)]bis[2-(hydroxymethyl)- | >400 | >752 | EU A.16 |

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------|---------|-------------|----------|
| epoxy resin (MW ≤ 700) | LD50 Dermal | Rabbit | 20 g/kg | - |
| | LD50 Oral | Mouse | 15600 mg/kg | - |
| Phenol, isobutylenated, phosphate (3:1) | LD50 Oral | Rat | >5 g/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|------------------------|---------|-------|-----------------------|-------------|
| epoxy resin (MW ≤ 700) | Eyes - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 500 milligrams | - |
| Phenol, isobutylenated, phosphate (3:1) | Skin - Mild irritant | Rabbit | - | 500 mg | - |

Sensitisation

| Product/ingredient name | Route of exposure | Species | Result |
|-------------------------|-------------------|------------------------------|-------------|
| epoxy resin (MW ≤ 700) | skin | Mammal - species unspecified | Sensitising |

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Developmental toxin | Species | Dose | Exposure |
|---------------------------------------|-------------------|-----------|---------------------|---------|-----------------|----------|
| hexaboron dizinc undecaoxide, hydrate | - | Positive | - | Rat | Oral: 100 mg/kg | - |

Conclusion/Summary : Suspected of damaging the unborn child.

Teratogenicity

Not available.

Conclusion/Summary : Suspected of damaging the unborn child.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-----------------------|----------------------------|----------|
| epoxy resin (MW ≤ 700) | Acute EC50 1.4 mg/l | Daphnia | 48 hours |
| | Acute LC50 3.1 mg/l | Fish - pimephales promelas | 96 hours |
| | Chronic NOEC 0.3 mg/l | Fish | 21 days |

Persistence and degradability

Section 12. Ecological information

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| epoxy resin (MW ≤ 700) | - | - | Not readily |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|------|-----------|
| epoxy resin (MW ≤ 700) | 2.64 to 3.78 | 31 | low |
| Phenol, isobutyleneated, phosphate (3:1) | 4.85 | 1850 | high |

Mobility in soil







Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | IATA |
|----------------------------|--|--|--|
| UN number | UN3082 | UN3082 | UN3082 |
| UN proper shipping name | Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700)) | Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700)). Marine pollutant (epoxy resin (MW ≤ 700)) | Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700)) |
| Transport hazard class(es) | 9   | 9   | 9   |
| Packing group | III | III | III |
| Environmental hazards | Yes. | Yes. | Yes. |

Additional information

UN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

ADR/RID : Tunnel restriction code: (-)
Hazard identification number: 90
Special provisions: 375

Section 14. Transport information

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Emergency schedules F-A, S-F

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

TCCSCA List of toxic chemicals

Not applicable.

TCCSCA List of concerned chemicals

Not applicable.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

Procedure used to derive the classification

| Classification | Justification |
|---|--------------------|
| SKIN CORROSION/IRRITATION - Category 2 | Calculation method |
| SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A | Calculation method |
| SKIN SENSITISATION - Category 1 | Calculation method |
| REPRODUCTIVE TOXICITY - Category 1B | Calculation method |
| AQUATIC TOXICITY (ACUTE) - Category 2 | Calculation method |
| AQUATIC TOXICITY (CHRONIC) - Category 2 | Calculation method |

References : Not available.

Organisation that prepared the SDS : Jotun AS, Norway
+47 33 45 70 00

History

Date of printing : 14.08.2023

Date of previous issue : 18.07.2023

Version : 1.02

Section 16. Other information

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

✔ Indicates information that has changed from previously issued version.

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.