SAFETY DATA SHEET



1/13

Tankguard Type II Comp A

Section 1. Chemical product and company identification		
Product name	: 无溶剂酚醛环氧涂料II类 组份A	
Product code	: 23040	
Product type	: Liquid.	
Product description	: Paint.	
Relevant identified uses	of the substance or mixture and uses advised against	
Use in coatings - Industria Use in coatings - Professi		
Supplier's details	: 佐敦涂料(张家港)有限公司 中国江苏扬子江国际化学工业园南海路39号 215634 电话: +86 512 58937988 传真: +86 512 58937986	
	Jotun Coatings (Zhangjiagang) Co. Ltd NO.39 Nanhai Road Jiangsu Yangtze River International Chemical Industry Park, Jiangsu Province 215634 China Tel: +86 512 58937988 Fax: +86 512 58937986	
	中远佐敦船舶涂料(青岛)有限公司 中国山东省青岛市高新区春阳路800号 总机电话: +86-532-68689888 总机传真: +86-532-66726750	
	Jotun COSCO Marine Coatings (Qingdao) Co. Ltd. No. 800, Chunyang Road, High-tech Zone, Qingdao, P. R. China Tel: +86-532-68689888 Fax: +86-532-66726750	
	SDSJotun@jotun.com	
Emergency telephone number (with hours of operation)	: Emergency Services for Chemical Incident of China. Tel: +86 532 83889090	

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Classification of the	: SKIN CORROSION/IRRITATION - Category 2
substance or mixture	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A
	SKIN SENSITISATION - Category 1
	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Date of issue/Date of revision: 17.01.2024Date of previous issue: 15.01.2024Version: 1.02

Section 2. Hazards identification

GHS label elements	
Hazard pictograms	
Signal word	: Warning.
Hazard statements	 H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements	
General	: Not applicable.
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.
Response	 P391 - Collect spillage. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	: No known significant effects or critical hazards.
Health hazards	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

Ingredient name	%	CAS number
phenol, polymer with formaldehyde, glycidyl ether	≤50	28064-14-4
epoxy-formaldehyde resin (MW<700)	≤25	9003-36-5
oxirane, 2,2'-[1,6-hexanediylbis(oxymethylene)]bis-	≤5	16096-31-4
complex mixture of diamid waxes	≤3	-
silane, trimethyoxy[3-(oxiranyl-methoxy)propyl]-	<3	2530-83-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower Eye contact eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. 2 Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. : Wash out mouth with water. Remove dentures if any. If material has been Ingestion swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

most important symptoms/	enecis, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Ducto attain of first statem	. No estimate the television and never set with a suitable training.

Protection of first-aiders
 No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

reisonal precautions, protec	ιv	<u>e equipment and emergency procedures</u>
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and material for con	Ita	inment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures :	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general soccupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Contro	l parameters

```
Occupational exposure limits
```

None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>ires</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Date of issue/Date of revision		: 17.01.2024 Date of previous issue : 15.01.2024 Version : 1.02 5/13

Section 8. Exposure controls/personal protection

	• •
	Always ensure that gloves are free from defects and that they are stored and used correctly.
	The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	Wear suitable gloves tested to ISO 374-1:2016. May be used, gloves(breakthrough time) 4 - 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm)
	Recommended, gloves(breakthrough time) > 8 hours: fluor rubber (> 0.35 mm), Viton® (> 0.7 mm), neoprene (> 0.35 mm), nitrile rubber (> 0.75 mm), butyl rubber (> 0.4 mm), PVC (> 0.5 mm)
	For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state: Liquid.Colour: Green., Grey, White.Odour: Characteristic.Odour threshold: Not applicable.pH: Not applicable.Melting point/freezing point: Not applicable.Boiling point, initial boiling point, and boiling range: Not available.Flash point: Not available.Evaporation rate: Not available.Flammability: Not applicable.Lower and upper explosion limit/flammability limit: 0.43 - 0%Vapour pressure: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation WV<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
Odour:Characteristic.Odour threshold:Not applicable.pH:Not applicable.Melting point/freezing point:Not applicable.Boiling point, initial boiling point, and boiling range:Not available.Flash point:Not available.Evaporation rate:Not available.Flammability:Not available.Lower and upper explosion limit/flammability limit:0.43 - 0%Vapour pressure:Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation Ward 20°C) (epoxy-formation Ward 20°C) (epoxy-formation Ward 20°C)			
Odour threshold:Not applicable.pH:Not applicable.Melting point/freezing point:Not applicable.Boiling point, initial boiling point, and boiling range:Not available.Flash point:Not available.Evaporation rate:Not available.Flammability:Not applicable.Lower and upper explosion limit/flammability limit:0.43 - 0%Vapour pressure:Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation (MW<700)).			
pH:Not applicable.Melting point/freezing point:Not applicable.Boiling point, initial boiling point, and boiling range:Not available.Flash point:Not available.Evaporation rate:Not available.Flammability:Not applicable.Cower and upper explosion limit/flammability limit:Not applicable.Vapour pressure:Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation with explosion).			
Melting point/freezing pointNot applicable.Boiling point, initial boiling point, and boiling rangeNot available.Flash point: Not available.Evaporation rate: Not available.Flammability: Not available.Flammability: Not applicable.Lower and upper explosion limit/flammability limit: 0.43 - 0%Vapour pressure: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
Boiling point, initial boiling point, and boiling range: Not available.Flash point: Not available.Evaporation rate: Not available.Flammability: Not available.Flammability: Not applicable.Lower and upper explosion limit/flammability limit: 0.43 - 0%Vapour pressure: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
point, and boiling rangeFlash point: Not available.Evaporation rate: Not available.Flammability: Not applicable.Lower and upper explosion limit/flammability limit: 0.43 - 0%Vapour pressure: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-forma (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
Evaporation rate: Not available.Flammability: Not applicable.Lower and upper explosion: 0.43 - 0%Imit/flammability limit: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
Flammability : Not applicable. Lower and upper explosion limit/flammability limit : 0.43 - 0% Vapour pressure : Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-forma (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
Lower and upper explosion limit/flammability limit: 0.43 - 0%Vapour pressure: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-forma (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
limit/flammability limitVapour pressure: Highest known value: 0.08 kPa (0.6 mm Hg) (at 20°C) (epoxy-formation (MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
(MW<700)). Weighted average: 0.07 kPa (0.53 mm Hg) (at 20°C)			
Relative vapour density : Not available.	aldeh	hyde res	sin
Density : 1.541 g/cm ³			
Solubility(ies) :			
Media Result			
cold water Not soluble hot water Not soluble			
Date of issue/Date of revision : 17.01.2024 Date of previous issue : 15.01.2024 Ver	rsion	: 1.02	6/13

Section 9. Physical and chemical properties and safety characteristics

Solubility in water	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Particle characteristics	
Median particle size	: Not applicable.
No additional information.	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
phenol, polymer with formaldehyde, glycidyl ether	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-
epoxy-formaldehyde resin (MW<700)	Skin - Mild irritant	Mammal - species unspecified	-	-	-
oxirane, 2,2'- [1,6-hexanediylbis (oxymethylene)]bis-	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
· · · /	Skin - Mild irritant	Mammal - species unspecified	-	-	-
silane, trimethyoxy[3- (oxiranyl-methoxy)propyl]-	Eyes - Irritant	Mammal - species unspecified	-	-	-

Sensitisation

Section 11. Toxicological information

Product/ingredient name	Route of exposure	Species	Result
phenol, polymer with formaldehyde, glycidyl ether	skin	Mammal - species unspecified	Sensitising
epoxy-formaldehyde resin (MW<700)	skin	Mammal - species unspecified	Sensitising
oxirane, 2,2'- [1,6-hexanediylbis (oxymethylene)]bis-	skin	Mammal - species unspecified	Sensitising

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure			
<u>Short term exposure</u>			
Potential immediate effects	: Not available.		
Potential delayed effects Long term exposure	: Not available.		

Date of issue/Date of revision

: 17.01.2024 Date of previous issue

Section 11. Toxicological information

Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
Not available.		
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
phenol, polymer with formaldehyde, glycidyl ether	Acute EC50 3.3 mg/l	Daphnia	48 hours
	Acute LC50 7.5 mg/l	Fish	96 hours
epoxy-formaldehyde resin (MW<700)	Acute EC50 2 mg/l	Daphnia	24 hours
, , , , , , , , , , , , , , , , , , ,	Acute LC50 2 mg/l	Fish	96 hours
oxirane, 2,2'- [1,6-hexanediylbis (oxymethylene)]bis-	Acute EC50 47 mg/l	Daphnia	48 hours
	Acute LC50 30 mg/l	Fish - Cyprinidae (Leuciscus idus)	96 hours

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
phenol, polymer with formaldehyde, glycidyl ether	-	-	Not readily
epoxy-formaldehyde resin (MW<700)	-	-	Not readily
silane, trimethyoxy[3- (oxiranyl-methoxy)propyl]-	-	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
epoxy-formaldehyde resin (MW<700) oxirane, 2,2'- [1,6-hexanediylbis (oxymethylene)]bis-	2.7 0.822	-	low low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Date of issue/Date of revision

Section 12. Ecological information

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (phenol, polymer with formaldehyde, glycidyl ether)	Environmentally hazardous substance, liquid, n.o.s. (phenol, polymer with formaldehyde, glycidyl ether)	Environmentally hazardous substance, liquid, n.o.s. (phenol, polymer with formaldehyde, glycidyl ether). Marine pollutant (phenol, polymer with formaldehyde, glycidyl ether)	Environmentally hazardous substance, liquid, n.o.s. (phenol, polymer with formaldehyde, glycidyl ether)
Transport hazard class(es)	9	9	9	9
Packing group	III	111	111	111
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional informat	tion			
China	: The enviror sizes of ≤5		stance mark is not requi	red when transported in
UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
IMDG	 This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F 			
ΙΑΤΑ	or ≤5 kg, pr		angerous good when trai neet the general provisio	
ADR / RID		riction code: (-) ntification number: 90		
Marking	• The enviror	nmental hazardous / mar	ine pollutant mark is only	applicable for

Section 14. Transport information

Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Extinguishing media		
Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	1	None known.
Incompatible materials	:	No specific data.
Transport in bulk according	:	Not available.

to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product:

Law of the People's Republic of China on the Prevention and Control of Occupational Diseases

Regulations on the Control over Safety of Dangerous Chemicals Measures for Environmental Management of New Chemical Substances Law of the People's Republic of China on the Prevention and Control of Environment Pollution Caused by Solid Wastes Safety regulations for the use of chemicals in the workplace General Rule for Classification and Hazard Communication of Chemicals Classification and code of dangerous goods

List of Goods banned for Importing

None of the components are listed.

Drug Precursors Requiring an Import/Export License

None of the components are listed.

Inventory of Hazardous Chemicals

None of the components are listed.

List of Explosive Precursors

None of the components are listed.

List of Goods banned for Exporting

None of the components are listed.

List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

Catalogue and classification of drug precursor chemicals

None of the components are listed.

Inventory of highly toxic articles

None of the components are listed.

Catalogue of Hazardous Chemicals of Priority Management

None of the components are listed.

Catalogue of Occupational Disease Hazard Factors - Dust

Ingredient name	Status
titanium dioxide	Listed
barium sulfate	Listed

Catalogue of Occupational Disease Hazard Factors - Chemical Factors

Date of issue/Date of revision	: 17.01.2024	Date of previous issue	: 15.01.2024	Version : 1.02	11/13
--------------------------------	--------------	------------------------	--------------	----------------	-------

Section 15. Regulatory information

Ingredient name

barium sulfate

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

<u>History</u>	
Date of printing	: 17.01.2024
Date of issue/Date of revision	: 17.01.2024
Date of previous issue	: 15.01.2024
Version	: 1.02
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	Calculation method

References

: Not available. Indicates information that has changed from previously issued version.

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the guality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

Status

Listed

Section 16. Other information

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.