# SAFETY DATA SHEET



# Jotafloor EP SL Comp B (40)

# Section 1. Identification

GHS product identifier	: Jotafloo
Other means of identification	: Not avail
Product code	: 25980
Product description	: Paint.
Product type	: Liquid.

Jotafloor EP SL Comp B (40)
Not available.
25980

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses Use in coatings - Consumer use: Apply this product only as specified on the label. Use in coatings - Professional use

Manufacturing country	: Jotun Thailand Limited 700/353 Amata Nakorn Industrial Estate (BIP 2) Moo 6, Tumbol Donhualoh, Amphur Muang Chonburi Chonburi 20000 Thailand
	Phone: + 66 2 022 9888

Fax: + 66 2 022 9888 , + 66 38 214 375

SDSJotun@jotun.com

Emergency telephone number	÷	Jotun Thailand Limited
		Phone: + 66 2 022 9888 ext. 2100, 2400, 2402

## Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 5 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SKIN SENSITISATION - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
GHS label elements	
Signal word	: Danger.
Hazard statements	<ul> <li>H302 - Harmful if swallowed.</li> <li>H313 - May be harmful in contact with skin.</li> <li>H314 - Causes severe skin burns and eye damage.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
General	: P102 - Keep out of reach of children.

Date of iss	ue : 28.05.2020	1/11
Date of iss	ue : 28.05.2020	

### Section 2. Hazards identification

Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.</li> <li>P273 - Avoid release to the environment.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P264 - Wash hands thoroughly after handling.</li> </ul>
Response	<ul> <li>P304 + P340 + P310 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician.</li> <li>P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician.</li> <li>P302 + P352 + P312 - IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical attention.</li> <li>P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.</li> </ul>
Storage	: P405 - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: None known.

### Section 3. Composition/information on ingredients

-		-	
Substance/mixture	: Mixture		
Other means of identification	: Not available.		
CAS number/other identifiers			
CAS number	: Not applicable.		
EC number	: Mixture.		
Product code	: 25980		
Ingredient name		%	CAS number
benzyl alcohol 3-aminomethyl-3,5,5-trimethyl		≥25 - ≤50 ≥25 - ≤50	100-51-6 2855-13-2
salicylic acid	оубонскупанние	<3	69-72-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact

(

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

# Section 4. First aid measures

Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effect	<u>s</u>	
Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	1	Harmful if swallowed.
Over-exposure signs/sympto	<u>oms</u>	
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	:	Adverse symptoms may include the following: stomach pains
Indication of immediate medio	cal a	ttention and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Date of issue	: 28.05.2020	3/11

### Section 4. First aid measures

### Section 5. Firefighting measures

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire. None known.	
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burs This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	st.
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides	
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incid there is a fire. No action shall be taken involving any personal risk or without suitable training.	dent if
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	ł e	Eating, drinking and smoking should be prohibited in areas where this material is nandled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional nformation on hygiene measures.
Conditions for safe storage, including any incompatibilities	f r t r	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

Control parameters		
Occupational exposure limits		
None.		
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

# Section 8. Exposure controls/personal protection

	<ul> <li>There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.</li> <li>The breakthrough time must be greater than the end use time of the product.</li> <li>The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.</li> <li>Gloves should be replaced regularly and if there is any sign of damage to the glove material.</li> <li>Always ensure that gloves are free from defects and that they are stored and used correctly.</li> <li>The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.</li> <li>Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.</li> <li>Wear suitable gloves tested to EN374.</li> <li>Recommended, gloves(breakthrough time) &gt; 8 hours: 4H, butyl rubber, fluor rubber, Viton®</li> <li>May be used, gloves(breakthrough time) 4 - 8 hours: nitrile rubber, PVC</li> </ul>
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

# Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Characteristic.
Odour threshold	: Not available.
рН	: Not applicable.
Melting point	: Not applicable.
Boiling point	: Lowest known value: 205.3°C (401.5°F) (benzyl alcohol). Weighted average: 228.04°C (442.5°F)
Flash point	: Closed cup: 100°C (212°F)
Burning time	: Not applicable.
Burning rate	: Not applicable.
Evaporation rate	: 0.007 (benzyl alcohol) compared with butyl acetate
Flammability (solid, gas)	: Not applicable.
Lower and upper explosive (flammable) limits	: 1.2 - 13%
Vapour pressure	<ul> <li>Highest known value: 0.007 kPa (0.05 mm Hg) (at 20°C) (benzyl alcohol).</li> <li>Weighted average: 0.004 kPa (0.03 mm Hg) (at 20°C)</li> </ul>
Vapour density	: Highest known value: 3.7 (Air = 1) (benzyl alcohol).
Relative density	: 1 g/cm <sup>3</sup>
Solubility	: Insoluble in the following materials: cold water and hot water.

Date of issue	: 28.05.2020	6/11

## Section 9. Physical and chemical properties

Partition coefficient: n-octanol/ water	: Not available.	
Auto-ignition temperature	: Lowest known value: 380°C (716°F) (3-aminomethyl- 3,5,5-trimethylcyclohexylamine).	
Decomposition temperature	: Not available.	
SADT	: Not available.	
Viscosity	: Kinematic (40°C): >0.205 cm²/s (>20.5 mm²/s)	
Aerosol product		

Section 10. Stabili	Section 10. Stability and reactivity				
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
Chemical stability	: The product is stable.				
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
Conditions to avoid	: No specific data.				
Incompatible materials	<ul> <li>Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.</li> </ul>				
Hazardous decomposition products	<ul> <li>Under normal conditions of storage and use, hazardous decomposition products should not be produced.</li> </ul>				

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol 3-aminomethyl- 3,5,5-trimethylcyclohexylamine	LD50 Oral LD50 Oral		1230 mg/kg 1030 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
salicylic acid	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Eyes - Mild irritant	Mammal - species unspecified	-	-	-

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	skin	Mammal - species unspecified	Sensitising

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

# Ś

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
salicylic acid	-	-	Positive	Rat	Oral: 150 mg/kg	-
Teratogenicity				•	•	•
Not available.						
Specific target organ toxicit	<u>y (single exp</u>	<u>osure)</u>				
Not available.						
Specific target organ toxicit	<u>y (repeated e</u>	<u>xposure)</u>				
Not available.						
Aspiration hazard						
Not available.						
Potential acute health effect	<u>s</u>					
Eye contact	: Cause	s serious eye	damage.			
Inhalation	: No kno	No known significant effects or critical hazards.				
Skin contact		Causes severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.				
Ingestion	: Harmfu	Harmful if swallowed.				
Symptoms related to the phy	reical chomic	al and toxical	ogical charactoristi	<u></u>		
Inhalation		cific data.	<u>ogical characteristi</u>	<u>cs</u>		
Ingestion	: Advers		may include the fol	lowing:		
Skin contact	: Advers pain or rednes	e symptoms r irritation	may include the fol	lowing:		
Eye contact		e symptoms r g	may include the fol	lowing:		
Potential chronic health eff	<u>ects</u>					
General		ensitized, a s low levels.	evere allergic reac	tion may occur v	vhen subsequen	tly exposed
Carcinogenicity	: No kno	wn significant	t effects or critical l	nazards.		
Mutagenicity	: No kno	wn significant	t effects or critical l	nazards.		
Teratogenicity	: No kno	No known significant effects or critical hazards.				
Developmental effects	: No kno	No known significant effects or critical hazards.				
Fertility effects			t effects or critical l			

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Dermal	1217.64 mg/kg 2669.9 mg/kg 24.42 mg/l

# Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	Acute EC50 17.4 to 21.5 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
salicylic acid	Acute IC50 37 mg/l Acute LC50 32 μg/l Fresh water	Algae Daphnia - Daphnia magna -	72 hours 48 hours
		Neonate	
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Daphnia longispina - Neonate	21 days

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol 3-aminomethyl- 3,5,5-trimethylcyclohexylamine	-		Readily Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	<100	low
3-aminomethyl-	0.99	-	low
3,5,5-trimethylcyclohexylamine			
salicylic acid	2.21 to 2.26	-	low

#### Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt
		material and runoff and contact with soil, waterways, drains and sewers.

	UN	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066
UN proper shipping name	Paint related material	Paint related material	Paint related material

## Section 14. Transport information

Transport hazard class(es)	8	8	8		
Packing group	Ш	Ш	Ш		
Environmental hazards	No.	No.	No.		
Special precautions for user	<b>Transport within user's</b> <b>premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<b>Transport within user's</b> <b>premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<b>Transport within user's</b> <b>premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
Additional information	-	<b>Emergency schedules</b> F-A, S-B	-		

Transport in bulk according to : Not available. Annex II of Marpol and the IBC Code

ADR / RID

: Tunnel restriction code: (E) Hazard identification number: 80

### Section 15. Regulatory information

Hazardous Substance Act B.E. 2535 (1992)

<u>Type</u> Ingredient name

<u>Type</u>

<u>Authority</u>

**Conditions** 

No known specific national and/or regional regulations applicable to this product (including its ingredients).

### Section 16. Other information

<u>History</u>			
Date of printing	:	28.05.2020	
Date of issue/Date of revision	:	28.05.2020	
Date of previous issue	:	16.04.2020	
Version	:	1.14	
Key to abbreviations	:	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goo by Rail UN = United Nations LogPow = logarithm of the octanol/water partition coefficient	S
References	1	Not available.	
Date of issue		: 28.05.2020 1	0/11

### Section 16. Other information

Indicates information that has changed from previously issued version.

#### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.