



Jotafloor EP SL Comp B (40)

Section 1. Identification

Product name : Jotafloor EP SL Comp B (40)

Product code : 25980
Product description : Paint.
Product type : Liquid.

Other means of identification

: Not available.

Supplier's details : Jotun South Africa (PTY) Ltd

P.O.Box 187, Blackheath 7581,

Cape Town 8000

Tel: +27 21 941 8800 Fax: +27 21 941 8700

SDSJotun@jotun.com

Emergency telephone

number

: 24 hour toll free number Environserve Hazmat: 0800 147 112

Section 2. Hazards identification

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 5
SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN SENSITISATION - Category 1

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements

Hazard pictograms :





Signal word : Danger.

Hazard statements : H302 - Harmful if swallowed.

H313 - May be harmful in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General: P102 - Keep out of reach of children.

Prevention : P280 - Wear protective gloves. Wear eye or face protection. Wear protective

clothina.

P273 - Avoid release to the environment.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash hands thoroughly after handling.

Date of issue/Date of revision : 16.04.2020 Date of previous issue : No previous validation Version : 1 1/11

Section 2. Hazards identification

Response

: P304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON

CENTER or physician. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician.

P302 + P352 + P312 - IF ON SKIN: Wash with plenty of soap and water. Call a

POISON CENTER or physician if you feel unwell.

P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage

: P405 - Store locked up.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

CAS number/other identifiers

CAS number : Not applicable.

EC number : Mixture. **Product code** : 25980

Ingredient name	%	CAS number
benzyl alcohol	≥25 - ≤50	100-51-6
3-aminomethyl-3,5,5-trimethylcyclohexylamine	≥25 - ≤50	2855-13-2
salicylic acid	<3	69-72-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Date of issue/Date of revision : 16.04.2020 Version:1 2/11 Date of previous issue : No previous validation

Section 4. First aid measures

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

Ingestion: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Date of issue/Date of revision : 16.04.2020 Date of previous issue : No previous validation Version : 1

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

media

: None known.

nitrogen oxides

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 16.04.2020 Version : 1 Date of previous issue : No previous validation

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

Date of issue/Date of revision : 16.04.2020 Version :1 Date of previous issue : No previous validation

Section 8. Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to EN374.

Recommended, gloves(breakthrough time) > 8 hours: 4H, butyl rubber, fluor rubber,

Viton®

May be used, gloves(breakthrough time) 4 - 8 hours: nitrile rubber, PVC

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: If workers are exposed to concentrations above the exposure limit, they must use a **Respiratory protection**

respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use

of roller or brush, consider use of charcoalfilter.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. Colour : Various

Odour : Characteristic. Odour threshold : Not applicable. Hq : Not applicable. **Melting point** : Not applicable.

Boiling point : Lowest known value: 205.3°C (401.5°F) (benzyl alcohol). Weighted average: 228.

04°C (442.5°F)

: Closed cup: 100°C (212°F) Flash point

: 0.007 (benzyl alcohol) compared with butyl acetate **Evaporation rate**

Flammability (solid, gas) : Not applicable. : 1.2 - 13% Lower and upper explosive

(flammable) limits

Vapour pressure : Highest known value: 0.007 kPa (0.05 mm Hg) (at 20°C) (benzyl alcohol).

Weighted average: 0.004 kPa (0.03 mm Hg) (at 20°C)

Highest known value: 3.7 (Air = 1) (benzyl alcohol). Vapour density

Density : 1 g/cm³

: Insoluble in the following materials: cold water and hot water. Solubility

Partition coefficient: n-

octanol/water

Not available.

Auto-ignition temperature : Lowest known value: 380°C (716°F) (3-aminomethyl-3,5,

5-trimethylcyclohexylamine).

Decomposition temperature : Not available.

Viscosity Kinematic (40°C): >0.205 cm²/s (>20.5 mm²/s)

Date of issue/Date of revision Version : 1 6/11 : 16.04.2020 Date of previous issue : No previous validation

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol 3-aminomethyl-3,5, 5-trimethylcyclohexylamine	LD50 Oral LD50 Oral	Rat Rat	1230 mg/kg 1030 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
salicylic acid	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Eyes - Mild irritant	Mammal - species unspecified	-	-	-

Sensitisation

3	Route of exposure	Species	Result
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	skin	Mammal - species unspecified	Sensitising

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
salicylic acid	-	-	Positive		Oral: 150 mg/kg	-

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Date of issue/Date of revision: 16.04.2020Date of previous issue: No previous validationVersion: 1

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

: Causes severe burns. May be harmful in contact with skin. May cause an allergic Skin contact

skin reaction.

: Harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Fertility effects**

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision : 16.04.2020 Version:1 8/11 Date of previous issue : No previous validation

Jotafloor EP SL Comp B (40)

Section 11. Toxicological information

Route	ATE value
Oral	1217.6 mg/kg
Dermal	2669.9 mg/kg
Inhalation (vapours)	24.42 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Acute EC50 17.4 to 21.5 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 37 mg/l	Algae	72 hours
salicylic acid	Acute LC50 32 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Daphnia longispina - Neonate	21 days

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol 3-aminomethyl-3,5, 5-trimethylcyclohexylamine	-		Readily Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	<100	low
3-aminomethyl-3,5,	0.99	-	low
5-trimethylcyclohexylamine			
salicylic acid	2.21 to 2.26	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 16.04.2020 Date of previous issue : No previous validation Version : 1 9/11

Section 14. Transport information

	ADR/RID	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	Paint related material	Paint related material	Paint related material
Transport hazard class(es)	8	8	8
Packing group	III	III	III
Environmental hazards	No.	No.	No.
Additional information	-	Emergency schedules F-A, S-B	-

Additional information

ADR/RID : Hazard identification number 80

Tunnel code (E)

IMDG Emergency schedules F-A, S-B

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of Marpol and

the IBC Code

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Date of issue/Date of revision : 16.04.2020 Date of previous issue Version :1 10/11 : No previous validation

Section 16. Other information

History

Date of printing : 16.04.2020 Date of issue/Date of : 16.04.2020

revision

Date of previous issue : No previous validation

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue/Date of revision : 16.04.2020 Date of previous issue : No previous validation Version : 1 11/11