

SeaQuantum Pro U

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	: SeaQuantum Pro U
UFI	: U61K-N22M-P006-UNY1
Product code	: 28900
Product description	: Paint.
Product type	: Liquid.
Other means of identification	: Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Professional use

1.3 Details of the supplier of the safety data sheet

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Norway

Tel: + 47 33 45 70 00
Fax: +47 33 45 72 42
E-mail: SDSJotun@jotun.no

National contact

Jotun Ibérica S.A.
Poligon Industrial
Santa Rita
Calle Estàtica, no 3
08755 - Castellbisbal Barcelona

Tel: +34 93 771 18 00
Fax: +34 93 771 18 01
SDSJotun@jotun.com

1.4 Emergency telephone number

Jotun Ibérica S.A. Tel. +34 93 77 11 800 (8.00-17.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Acute Tox. 4, H302
Acute Tox. 4, H332
Skin Irrit. 2, H315
Eye Dam. 1, H318
Skin Sens. 1, H317
Repr. 2, H361d
STOT SE 3, H335
STOT RE 2, H373 (nervous system)

SeaQuantum Pro U

SECTION 2: Hazards identification

Aquatic Acute 1, H400

Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Danger.

Hazard statements

: H226 - Flammable liquid and vapour.
 H302 + H332 - Harmful if swallowed or if inhaled.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H318 - Causes serious eye damage.
 H335 - May cause respiratory irritation.
 H361d - Suspected of damaging the unborn child.
 H373 - May cause damage to organs through prolonged or repeated exposure. (nervous system)
 H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

General

: Not applicable.

Prevention

: P201 - Obtain special instructions before use.
 P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 - Avoid release to the environment.
 P260 - Do not breathe vapour.
 P270 - Do not eat, drink or smoke when using this product.

Response

: P391 - Collect spillage.
 P308 + P313 - IF exposed or concerned: Get medical advice or attention.
 P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
 P362 + P364 - Take off contaminated clothing and wash it before reuse.
 P302 + P352 - IF ON SKIN: Wash with plenty of water.
 P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
 P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

: dicopper oxide
 xylene
 colophony
 zineb
 copper pyriithione

Supplemental label elements

: Not applicable.

Additional information

: Antifouling. Active substances: dicopper oxide (CAS 1317-39-1) 33.0 % w/w, zineb (CAS 12122-67-7) 4.8 % w/w, copper pyriithione (CAS 14915-37-8) 2.7 % w/w. Read Technical Data Sheet and Safety Data Sheet before use. Do not reuse empty containers. For professional use only.

In compliance

: IMO Antifouling System Convention compliant AFS/CONF/26 + IMO MEPC.331(76).

SeaQuantum Pro U

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
dicopper oxide	REACH #: 01-2119513794-36 EC: 215-270-7 CAS: 1317-39-1 Index: 029-002-00-X	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 3.34 mg/l M [Acute] = 100 M [Chronic] = 10	[1] [2]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 20 mg/l	[1] [2]
colophony	REACH #: 01-2119480418-32 EC: 232-475-7 CAS: 8050-09-7 Index: 650-015-00-7	≤10	Skin Sens. 1, H317	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	<10	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
zineb	EC: 235-180-1 CAS: 12122-67-7	≤5	Flam. Sol. 1, H228 Skin Sens. 1, H317	M [Acute] = 10 M [Chronic] = 10	[1]

SeaQuantum Pro U

SECTION 3: Composition/information on ingredients

copper pyrithione	Index: 006-078-00-2 EC: 238-984-0 CAS: 14915-37-8	<3	Repr. 2, H361d STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 2, H361d STOT SE 3, H335 STOT RE 1, H372 (nervous system) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 200 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.07 mg/l M [Acute] = 100 M [Chronic] = 100	[1] [2]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤3	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤3	Flam. Liq. 3, H226 STOT SE 3, H336 See Section 16 for the full text of the H statements declared above.	-	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

SeaQuantum Pro U

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains colophony, zineb. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SeaQuantum Pro U

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

SeaQuantum Pro U

SECTION 7: Handling and storage

Put on appropriate personal protective equipment (see Section 8).
 Never use pressure to empty. Container is not a pressure vessel.
 Always keep in containers made from the same material as the original one.
 Comply with the health and safety at work laws.
 Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds**Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
P5c E1	5000 tonne 100 tonne	50000 tonne 200 tonne

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters**Occupational exposure limits**

Product/ingredient name	Exposure limit values
dicopper oxide	National institute of occupational safety and health (Spain, 4/2021). TWA: 0.01 mg/m ³ , (as Cu) 8 hours. Form: Respirable fraction
xylene	National institute of occupational safety and health (Spain, 4/2021). Absorbed through skin. STEL: 442 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 221 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
colophony	National institute of occupational safety and health (Spain, 4/2021). Skin sensitiser.
ethylbenzene	National institute of occupational safety and health (Spain, 4/2021). Absorbed through skin. TWA: 100 ppm 8 hours.

SeaQuantum Pro U

SECTION 8: Exposure controls/personal protection

copper pyrrhione	TWA: 441 mg/m ³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m ³ 15 minutes. National institute of occupational safety and health (Spain, 4/2021).
1-methoxy-2-propanol	TWA: 0.01 mg/m ³ , (as Cu) 8 hours. Form: Respirable fraction National institute of occupational safety and health (Spain, 4/2021). Absorbed through skin. STEL: 568 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
dicopper oxide	DNEL	Long term Oral	0.041 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.082 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	137 mg/kg bw/day	Workers	Systemic
xylene	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Local
	DNEL	Short term Inhalation	260 mg/m ³	General population	Local
	DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Local
colophony	DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	176 mg/m ³	Workers	Systemic

SeaQuantum Pro U

SECTION 8: Exposure controls/personal protection

ethylbenzene	DNEL	Long term Dermal	15 mg/kg bw/day	General population [Consumers]	Systemic	
	DNEL	Long term Inhalation	52 mg/m ³	General population [Consumers]	Systemic	
	DNEL	Long term Oral	15 mg/kg bw/day	General population [Consumers]	Systemic	
	DNEL	Long term Oral	1.0655 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	1.0655 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	2.131 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	10 mg/m ³	Workers	Local	
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	15 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Inhalation	293 mg/m ³	Workers	Local	
	zinc oxide	DMEL	Long term Inhalation	442 mg/m ³	Workers	Local
		DMEL	Short term Inhalation	884 mg/m ³	Workers	Systemic
		DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
DNEL		Long term Inhalation	5 mg/m ³	Workers	Systemic	
DNEL		Long term Dermal	83 mg/kg bw/day	General population [Consumers]	Systemic	
DNEL		Long term Inhalation	2.5 mg/m ³	General population [Consumers]	Systemic	
DNEL		Long term Oral	0.83 mg/kg bw/day	General population [Consumers]	Systemic	
DNEL		Long term Inhalation	0.5 mg/m ³	Workers	Local	
DNEL		Long term Oral	0.83 mg/kg bw/day	General population	Systemic	
DNEL		Long term Inhalation	2.5 mg/m ³	General population	Systemic	
1-methoxy-2-propanol	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Oral	33 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	43.9 mg/m ³	General population	Systemic	
	DNEL	Long term Dermal	78 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	183 mg/kg	Workers	Systemic	

SeaQuantum Pro U

SECTION 8: Exposure controls/personal protection

	DNEL	Long term Inhalation	bw/day 369 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	553.5 mg/ m ³	Workers	Local
	DNEL	Short term Inhalation	553.5 mg/ m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
dicopper oxide	Fresh water	7.8 µg/l	-
	Marine	5.2 µg/l	-
	Sewage Treatment Plant	230 µg/l	-
	Fresh water sediment	87 mg/kg dwt	-
	Marine water sediment	676 mg/kg dwt	-
	Soil	65 mg/kg dwt	-
xylene	Fresh water	0.327 mg/l	-
	Marine	0.327 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Fresh water sediment	12.46 mg/kg dwt	-
	Marine water sediment	12.46 mg/kg dwt	-
	Soil	2.31 mg/kg dwt	-
colophony	Fresh water	0.0054 mg/l	-
	Marine	0.00054 mg/l	-
	Sewage Treatment Plant	1000 mg/l	-
	Fresh water sediment	0.02 mg/kg dwt	-
	Marine water sediment	0.002 mg/kg dwt	-
	Soil	0.0015 mg/kg dwt	-
ethylbenzene	Fresh water	0.1 mg/l	-
	Marine	0.01 mg/l	-
	Sewage Treatment Plant	9.6 mg/l	-
	Fresh water sediment	13.7 mg/kg dwt	-
	Soil	2.68 mg/kg dwt	-
	Secondary Poisoning	20 mg/kg	-
zinc oxide	Fresh water	20.6 µg/l	-
	Marine	6.1 µg/l	-
	Sewage Treatment Plant	52 µg/l	-
	Fresh water sediment	117.8 mg/kg dwt	-
	Marine water sediment	56.5 mg/kg dwt	-
	Soil	35.6 mg/kg dwt	-
1-methoxy-2-propanol	Fresh water	10 mg/l	-
	Marine	1 mg/l	-
	Sewage Treatment Plant	100 mg/l	-
	Fresh water sediment	52.3 mg/kg dwt	-
	Marine water sediment	5.2 mg/kg dwt	-
	Soil	5.49 mg/kg dwt	-

8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

SeaQuantum Pro U

SECTION 8: Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves

Wear suitable gloves tested to ISO 374-1:2016.

Not recommended, gloves(breakthrough time) < 1 hour: neoprene (> 0.35 mm), butyl rubber (> 0.4 mm), PVC (> 0.5 mm)

Recommended, gloves(breakthrough time) > 8 hours: fluor rubber (> 0.35 mm), nitrile rubber (> 0.4 mm), 4H/Silver Shield® (> 0.07 mm), Teflon (> 0.35 mm), polyvinyl alcohol (PVA) (> 0.3 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

Environmental exposure controls : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Red

Odour : Characteristic.

SeaQuantum Pro U

SECTION 9: Physical and chemical properties

Odour threshold	: Not applicable.
Melting point/freezing point	: Not applicable.
Initial boiling point and boiling range	: Lowest known value: 120.17°C (248.3°F) (1-methoxy-2-propanol). Weighted average: 135.09°C (275.2°F)
Flammability	: Not applicable.
Lower and upper explosion limit	: 0.8 - 13.74%
Flash point	: Closed cup: 27°C
Auto-ignition temperature	: Lowest known value: 270°C (518°F) (1-methoxy-2-propanol).
Decomposition temperature	: Not available.
pH	: Not applicable.
Viscosity	: Kinematic (40°C): >20.5 mm ² /s
Solubility in water	: cold water Not soluble hot water Not soluble
Partition coefficient: n-octanol/ water	: Not available.
Vapour pressure	: Highest known value: 1.2 kPa (9.3 mm Hg) (at 20°C) (ethylbenzene). Weighted average: 0.98 kPa (7.35 mm Hg) (at 20°C)
Evaporation rate	: Highest known value: 0.84 (ethylbenzene) Weighted average: 0.79 compared with butyl acetate
Density	: 1.68 g/cm ³
Vapour density	: Highest known value: 3.7 (Air = 1) (xylene). Weighted average: 3.66 (Air = 1)
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

SeaQuantum Pro U

SECTION 11: Toxicological information

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains colophony, zineb. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
dicopper oxide	LC50 Inhalation Dusts and mists	Rat	3.34 mg/l	4 hours
xylene	LD50 Oral	Rat	1340 mg/kg	-
	LC50 Inhalation Vapour	Rat	20 mg/l	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
ethylbenzene	TDL ₀ Dermal	Rabbit	4300 mg/kg	-
	LC50 Inhalation Vapour	Rat - Male	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
zineb	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Oral	Rat	1850 mg/kg	-
copper pyrithione	LC50 Inhalation Dusts and mists	Rat	70 mg/m ³	4 hours
	LD50 Dermal	Rabbit	300 mg/kg	-
1-methoxy-2-propanol	LD50 Oral	Rat	200 mg/kg	-
	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SeaQuantum Pro U	1260.3	4372.0	N/A	94.7	2.1
dicopper oxide	500	N/A	N/A	N/A	3.34
xylene	4300	1100	N/A	20	N/A
ethylbenzene	3500	N/A	N/A	17.8	N/A
copper pyrithione	200	300	N/A	N/A	0.07
1-methoxy-2-propanol	6600	13000	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
dicopper oxide	Eyes - Cornea opacity	Rabbit	-	72 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	-	48 hours	-
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
copper pyrithione	Eyes - Severe irritant	Mammal - species unspecified	-	-	-
	Skin - Irritant	Mammal - species unspecified	-	-	-
zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
1-methoxy-2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-

SeaQuantum Pro U

SECTION 11: Toxicological information

	Skin - Mild irritant	Rabbit	-	500 mg	-
--	----------------------	--------	---	--------	---

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
colophony	skin	Mammal - species unspecified	Sensitising
zineb	skin	Mammal - species unspecified	Sensitising

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
zineb	-	-	Positive	Mammal - species unspecified	Route of exposure unreported	-
copper pyrithione	-	-	Positive	Mammal - species unspecified	Route of exposure unreported	-

Developmental effects : Suspected of damaging the unborn child.**Fertility effects** : No known significant effects or critical hazards.**Teratogenicity**

Suspected of damaging the unborn child.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
zineb	Category 3	-	Respiratory tract irritation
copper pyrithione	Category 3	-	Respiratory tract irritation
1-methoxy-2-propanol	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
copper pyrithione	Category 1	-	nervous system

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

Not available.

11.2.2 Other information

Not available.

SeaQuantum Pro U

SECTION 12: Ecological information**12.1 Toxicity**

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
dicopper oxide	Acute LC50 0.075 mg/l Fresh water Chronic NOEC 0.001 mg/l	Fish - Danio rerio Algae	96 hours -
xylene	Chronic NOEC 0.0052 mg/l Acute LC50 8500 µg/l Marine water	Algae Crustaceans - Palaemonetes pugio	- 48 hours
ethylbenzene	Acute LC50 13400 µg/l Fresh water Acute EC50 7700 µg/l Marine water Acute EC50 2.93 mg/l	Fish - Pimephales promelas Algae - Skeletonema costatum Daphnia	96 hours 96 hours 48 hours
zineb	Acute LC50 4.2 mg/l Acute EC50 0.38 mg/l Fresh water	Fish Algae - Pseudokirchneriella subcapitata Daphnia - Daphnia magna	96 hours 96 hours 48 hours
	Acute LC50 970 to 1800 µg/l Fresh water Acute LC50 0.225 mg/l Acute LC50 20.8 ppm Fresh water Chronic NOEC 0.05 mg/l Fresh water Chronic NOEC 0.05 mg/l Fresh water	Fish Fish - Oncorhynchus mykiss Algae - Chlorella vulgaris Algae - Scenedesmus quadricauda	96 hours 96 hours 96 hours 96 hours
copper pyrrithione	Acute EC50 0.022 mg/l Acute IC50 0.035 mg/l Acute LC50 0.0043 mg/l	Daphnia Algae Fish	48 hours 120 hours 96 hours
zinc oxide	Chronic NOEC 0.00046 mg/l Acute LC50 1.1 ppm Fresh water Chronic NOEC 0.02 mg/l Fresh water	Algae - Skeletonema costatum Fish - Oncorhynchus mykiss Algae - Pseudokirchneriella subcapitata - Exponential growth phase	120 hours 96 hours 72 hours

Conclusion/Summary : This material is very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
dicopper oxide	-	-	Not readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily
zinc oxide	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 to 25.9	low
colophony	1.9 to 7.7	-	high
ethylbenzene	3.6	-	low
zineb	1.3	-	low
zinc oxide	-	28960	high
1-methoxy-2-propanol	<1	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

SeaQuantum Pro U

SECTION 12: Ecological information**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.








Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SeaQuantum Pro U

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	Paint	Paint	Paint. Marine pollutant (dicopper oxide)	Paint
14.3 Transport hazard class(es)	3  	3  	3  	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

ADR/RID

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Hazard identification number 30

Tunnel code (D/E)

ADN

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IMDG

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Emergency schedules F-E, S-E

IATA

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

SeaQuantum Pro U

SECTION 15: Regulatory information

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Annex	Ingredient name	Status
Annex I - Part 1	zineb	Listed

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : Not applicable.

SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

SeaQuantum Pro U

SECTION 16: Other information**Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H332	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361d	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373 (nervous system)	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2

SeaQuantum Pro U

SECTION 16: Other information

Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Sol. 1	FLAMMABLE SOLIDS - Category 1
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 23.03.2023
Date of issue/ Date of revision : 23.03.2023
Date of previous issue : No previous validation
Version : 1

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.