

Ultra Shine D8 (C055)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Ultra Shine D8 (C055)
Product code	: 29960
Product type	: Powder coating.
Other means of identification	: Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use

1.3 Details of the supplier of the safety data sheet

JOTUN CZECH a.s. NA ROVNEM 866 400 04 TRMICE CZECH REPUBLIC

Phone : + 420 477 828 969 Fax.: + 420 477 828 962 sdspowder@jotun.com Jotun A/S P.O.Box 2021 3202 Sandefjord Norway

Tel: + 47 33 45 70 00 Fax: +47 33 45 72 42

SDSJotun@jotun.no

1.4 Emergency telephone number

Contact NHS Direct; phone 0845 4647 or 111. Open 24/7.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] STOT RE 2, H373

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word Hazard statements	Warning.H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
General	: Not applicable.
Prevention	: P260 - Do not breathe dust.
Response	: P314 - Get medical advice/attention if you feel unwell.
Storage	: Not applicable.

Date of issue/Date of revision

SECTION 2: Hazards identification

Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Cyclohexane, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethyl-, homopolymer, caprolactam-blocked -
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	;	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	1	None known.
	• • •	

SECTION 3: Composition/information on ingredients

3.2 Mixtures : M	ixture			
Product/ingredient name	Identifiers	Weight %	Regulation (EC) No. 1272/2008 [CLP]	Туре
benzene-1,2,4-tricarboxylic acid	EC: 208-432-3 CAS: 528-44-9	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335	[1]
Cyclohexane, 5-isocyanato-1- (isocyanatomethyl)-1,3,3-trimethyl-, homopolymer, caprolactam- blocked	CAS: 127184-53-6	≤3	STOT RE 1, H372 (inhalation)	[1]
-	-	≤3	STOT RE 1, H372	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures		
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.	
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. 	
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.	
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. 	
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

4.2 Most important symptoms and effects, both acute and delayed

<u>Over-exposure signs</u>	s/symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any i	mmediate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	Recommended: alcohol-resistant foam, CO_2 blanket, water spray or mist.	
Unsuitable extinguishing media	Do not use water jet. Do not use inert gas under high pressure (e.g. CO2).	
5.2 Special hazards arising f	n the substance or mixture	
Hazards from the substance or mixture	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.	
Hazardous combustion products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	
	Fine dust clouds may form explosive mixtures with air.	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Cool closed containers exposed to fire with water. Do not release runoff from fire drains or watercourses.	to
Special protective equipment for fire-fighters	Appropriate breathing apparatus may be required.	

Date of issue/Date of revision

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.		
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.		
6.3 Methods and material for containment and cleaning up	:	Contain and collect spillage with an electrically protected vacuum cleaner or by wet- brushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.		
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.		

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe handling

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

During stoving/curing caprolactam will be released. Efficient oven extraction must be provided to safely discharge caprolactam from the workplace.

Welding, grinding and other hot work on the already-coated substrate may cause free isocyanates to be formed and released.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)

Recommendations

Date of issue/Date of revision

: 10.06.2021

: Not available.

SECTION 7: Handling and storage

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Dust Limit : 10 mg/m³ (TWA of total inhalable dust) and 4 mg/m³ (TWA of respirable)

No exposure limit value known.

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value	Population	Effects
Cyclohexane, 5-isocyanato-1- (isocyanatomethyl)-1,3,3-trimethyl-, homopolymer, caprolactam-blocked	Long term Inhalation	0.04 mg/m ³	General population	Local
	Long term Inhalation	0.15 mg/m³	Workers	Local
	Short term Inhalation	0.32 mg/m ³	General population	Local
	Short term Inhalation	1.2 mg/m ³	Workers	Local

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls	: Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Date of issue/Date of revision	: 10.06.2021 Date of previous issue : 10.06.2021 Version : 1.01 5/11

SECTION 8: Exposure controls/personal protection

Gloves	 There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. If dust is generated and ventilation is inadequate, use respirator that will protect against dust/mist. (FFP2 / N95).
Environmental exposure controls	: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties

Physical state: Solid. Powder.Colour: VariousOdour threshold: Odourless.Odour threshold: Not applicable.pH: Not applicable.Melting point (dust): 85 - 115 °CInitial boiling point and boiling range: Not applicable.Flash point: Not applicable.Evaporation rate: Not applicable.Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Papour density: 1.2 to 1.9 g/cm³Solubility(les): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water: Not applicable.Auto-ignition temperature: > 400°CDecomposition temperature: > 250°CDate of issue/Date of revision: 10.06.2021Date of previous issue: 10.06.2021Version ::1.01	<u>Appearance</u>		
Odour: Odourless.Odour threshold: Not applicable.pH: Not applicable.Melting point (dust): 85 - 115 °CInitial boiling point and boiling range: Not applicable.Flash point: Not applicable.Evaporation rate: Not applicable.Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: 400°CDecomposition temperature: 250°C	Physical state	1	Solid. Powder.
Odour threshold:Not applicable.pH:Not applicable.Melting point (dust):85 - 115 °CInitial boiling point and boiling range:Not applicable.Flash point:Not applicable.Evaporation rate:Not applicable.Flammability (solid, gas):Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust):30 g/m³ (EN 14034-3)Minimum ignition energy (mJ):10 - 30 (EN 13821)Vapour pressure:Not applicable.Vapour density:1.2 to 1.9 g/cm³Solubility(ies)::Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/:Not applicable.Vater:Auto-ignition temperature::>400°CDecomposition temperature::>250°C	Colour	1	Various
pH: Not applicable.Melting point (dust): 85 - 115 °CInitial boiling point and boiling range: Not applicable.Flash point: Not applicable.Evaporation rate: Not applicable.Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: > 400°CDecomposition temperature: > 250°C	Odour	1	Odourless.
Melting point (dust):85 - 115 °CInitial boiling point and boiling range:Not applicable.Flash point:Not applicable.Evaporation rate:Not applicable.Flammability (solid, gas):Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust):30 g/m³ (EN 14034-3)Minimum ignition energy (mJ):10 - 30 (EN 13821)Vapour pressure:Not applicable.Vapour density:Not applicable.Density:1.2 to 1.9 g/cm³Solubility(ies):Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water:> 400°CDecomposition temperature:> 400°C	Odour threshold	1	Not applicable.
Initial boiling point and boiling rangeNot applicable.Flash point: Not applicable.Evaporation rate: Not applicable.Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: Auto-ignition temperature: > 400°CDecomposition temperature: 250°C	рН	1	Not applicable.
boiling rangeFlash point: Not applicable.Evaporation rate: Not applicable.Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: Auto-ignition temperature: > 400°CDecomposition temperature: 250°C	Melting point (dust)	1	85 - 115 °C
Evaporation rate: Not applicable.Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water: Not applicable.Auto-ignition temperature: > 400°C 250°C		1	Not applicable.
Flammability (solid, gas): Fine dust clouds may form explosive mixtures with air.Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: Not applicable.Auto-ignition temperature: > 400°CDecomposition temperature: 250°C	Flash point	:	Not applicable.
Lower explosion limit (dust): 30 g/m³ (EN 14034-3)Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: > 400°CDecomposition temperature: > 250°C	Evaporation rate	1	Not applicable.
Minimum ignition energy (mJ): 10 - 30 (EN 13821)Vapour pressure: Not applicable.Vapour density: Not applicable.Density: 1.2 to 1.9 g/cm³Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not applicable.water: Not applicable.Auto-ignition temperature: > 400°CDecomposition temperature: 250°C	Flammability (solid, gas)	1	Fine dust clouds may form explosive mixtures with air.
Vapour pressure : Not applicable. Vapour density : Not applicable. Density : 1.2 to 1.9 g/cm³ Solubility(ies) : Insoluble in the following materials: cold water and hot water. Partition coefficient: n-octanol/ : Not applicable. water	Lower explosion limit (dust)	1	30 g/m³ (EN 14034-3)
Vapour density : Not applicable. Density : 1.2 to 1.9 g/cm³ Solubility(ies) : Insoluble in the following materials: cold water and hot water. Partition coefficient: n-octanol/ : Not applicable. water	Minimum ignition energy (mJ)	1	10 - 30 (EN 13821)
Density : 1.2 to 1.9 g/cm³ Solubility(ies) : Insoluble in the following materials: cold water and hot water. Partition coefficient: n-octanol/ : Not applicable. water Auto-ignition temperature : > 400°C Decomposition temperature : 250°C	Vapour pressure	1	Not applicable.
Solubility(ies) : Insoluble in the following materials: cold water and hot water. Partition coefficient: n-octanol/ : Not applicable. water . Auto-ignition temperature : > 400°C Decomposition temperature : 250°C	Vapour density	1	Not applicable.
Partition coefficient: n-octanol/ : Not applicable. water Auto-ignition temperature : > 400°C Decomposition temperature : 250°C	Density	1	1.2 to 1.9 g/cm ³
water Auto-ignition temperature : > 400°C Decomposition temperature : 250°C	Solubility(ies)	1	Insoluble in the following materials: cold water and hot water.
Decomposition temperature : 250°C		1	Not applicable.
	Auto-ignition temperature	1	> 400°C
Date of issue/Date of revision : 10.06.2021 Date of previous issue : 10.06.2021 Version : 1.01	Decomposition temperature	1	250°C
	Date of issue/Date of revision	: 1	10.06.2021 Date of previous issue : 10.06.2021 Version : 1.01

6/11

SECTION 9: Physical and chemical properties

Viscosity

: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity **10.1 Reactivity** : Fine dust clouds may form explosive mixtures with air. **10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7). **10.3 Possibility of** : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation. **10.5 Incompatible materials** : Not applicable. **10.6 Hazardous** : Decomposition products may include the following materials: carbon monoxide, decomposition products carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Acute toxicity estimates

None.

Irritation/Corrosion

Product/ingredient name	Exposure	Species	Score	Exposure	Observation
benzene-1,2,4-tricarboxylic acid	Skin - Mild irritant Eyes - Mild irritant	Mammal - species unspecified Mammal - species unspecified	-	-	-

Sensitisation

Based on available data, the classification criteria are not met.

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Developmental effects

: No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards. Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
benzene-1,2,4-tricarboxylic acid	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Cyclohexane, 5-isocyanato-1-(isocyanatomethyl) -1,3,3-trimethyl-, homopolymer, caprolactam-blocked	Category 1	inhalation	-
-	Category 1	-	-

Aspiration hazard

Based on available data, the classification criteria are not met.

Other information

: None identified.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

No known significant effects or critical hazards.

12.2 Persistence and degradability

Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	: No known significant effects or critical hazards.
----------------------------	---

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment meth <u>Product</u>	ods
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

SECTION 13: Dispo	SECTION 13: Disposal considerations				
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. 				
European waste catalog	ue (EWC)				
The European Waste Cata	alogue classification of this product, when disposed of as waste, is:				
Waste code	Waste designation				
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances				
Packaging					
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.				
Disposal considerations : Using information provided in this safety data sheet, advice should the relevant waste authority on the classification of empty containers Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance we national legal provisions.					
Result	European waste catalogue (EWC)				
CEPE Paint Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances				
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of				

SECTION 14: Transport information

	•			
	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

spilt material and runoff and contact with soil, waterways, drains and sewers.

14.7 Transport in bulk according to IMO instruments

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and enviro	onmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 190	<u>7/2006 (REACH)</u>
Annex XIV - List of substan	nces subject to authorisation
Annex XIV	
None of the components a	re listed.
Substances of very high	<u>concern</u>
None of the components a	e listed.
Annex XVII - Restrictions	: Not applicable.
on the manufacture, placing on the market	
and use of certain	
dangerous substances,	
mixtures and articles	
Other EU regulations	
VOC	: Not available.
VOC for Ready-for-Use Mixture	: Not applicable.
Europe inventory	: Not determined.
Ozone depleting substanc	<u>es (1005/2009/EU)</u>
Not listed.	
Prior Informed Consent (P	<u>IC) (649/2012/EU)</u>
Not listed.	
Seveso Directive	
This product is not controlled	d under the Seveso Directive.
National regulations	
Industrial use	: The information contained in this safety data sheet does not constitute the user's
	own assessment of workplace risks, as required by other health and safety
	legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
International regulations	
	ion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
	Demistent Ornenia Dellutente
	Persistent Organic Pollutants
Not listed.	
Rotterdam Convention on P	Prior Informed Consent (PIC)
Not listed.	
UNECE Aarhus Protocol on	POPs and Heavy Metals
Not listed.	
15.2 Chemical safety	: Not applicable.
assessment	

SECTION 16: Other information

Indicates	information	that has	changed from	previously	y issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification			
STOT RE 2, H373	Calculation method			
Full text of abbreviated H statements				

H315 H319	Causes skin irritation. Causes serious eye irritation.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H373	May cause damage to organs through prolonged or repeated
	exposure.

Full text of classifications [CLP/GHS]

Eye Irrit. 2 Skin Irrit. 2 STOT RE 1		SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2		SPECIFIC TARGET ORGAN TOXICITY - REPEATED
STOT SE 3		EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	: 10.06.2021	
Date of issue/ Date of revision	: 10.06.2021	
Date of previous issue	: 10.06.2021	
Version	: 1.01	

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.