

SAFETY DATA SHEET



Jotun Protects Property

Jotacote Universal S120 Standard Comp B

Section 1. Identification

GHS product identifier : Jotacote Universal S120 Standard Comp B

Product code : 30223

Product description : Hardener.

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use

Use in coatings - Professional use

Supplier's details : Jotun Paints Inc.
842 W. Sam Houston Parkway North
City Center Three, Suite 300
Houston, TX 77024 USA
Phone number: +1 (713) 860-8241
SDSJotun@jotun.com

Emergency telephone number (with hours of operation) : 1-800-424-9300
(Staffed 24/7)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
SKIN CORROSION - Category 1C
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1
AQUATIC HAZARD (ACUTE) - Category 1
AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger.

Hazard statements : H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H400 - Very toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Section 2. Hazards identification

- Prevention** : P280 - Wear protective gloves, protective clothing and eye or face protection.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapor.
P270 - Do not eat, drink or smoke when using this product.
- Response** : P391 - Collect spillage.
P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor.
P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor.
P363 - Wash contaminated clothing before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

- CAS number** : Not applicable.
- Product code** : 30223

Ingredient name	%	CAS number
Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	≥75 - ≤90	1173092-74-4
Formaldehyde, oligomeric reaction products with phenol	≤10	9003-35-4
2,6-ditert-butyl-p-cresol	≤10	128-37-0
3-aminopropyldiethylamine	<5	104-78-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Section 4. First aid measures

- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	None
Formaldehyde, oligomeric reaction products with phenol	None
2,6-ditert-butyl-p-cresol	None
3-aminopropyldiethylamine	None

Biological exposure indices

No exposure indices known.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
The breakthrough time must be greater than the end use time of the product.
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Always ensure that gloves are free from defects and that they are stored and used correctly.
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
- Body protection** : Use chemical-resistant protective suit / disposable overall.
- Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Clear.
- Odor** : Characteristic.
- Odor threshold** : Not applicable.
- pH** : Not applicable.
- Melting point** : Not applicable.
- Boiling point** : Lowest known value: 170°C (338°F) (3-aminopropyl-diethylamine).
- Flash point** : Closed cup: 100°C (212°F)
Open cup: 100°C (212°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Lower and upper explosive (flammable) limits** : Not applicable.
- Vapor pressure** : Highest known value: 0.2 kPa (1.5 mm Hg) (at 20°C) (3-aminopropyl-diethylamine).
- Vapor density** : Highest known value: 4.48 (Air = 1) (3-aminopropyl-diethylamine).
- Relative density** : 1.005 g/cm³ 8.39 pounds/gallon
- Solubility(ies)** :

Media	Result
cold water	Not soluble
hot water	Not soluble

Section 9. Physical and chemical properties

Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm ² /s (>20.5 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-aminopropyldiethylamine	LD50 Oral	Rat	550 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,6-ditert-butyl-p-cresol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Mild irritant	Human	-	48 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	48 hours 500 milligrams	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	skin	Mammal - species unspecified	Sensitizing

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
2,6-ditert-butyl-p-cresol	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	592.03 mg/kg
Dermal	22448.98 mg/kg

Section 11. Toxicological information

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2,6-ditert-butyl-p-cresol	5.1	330 to 1800	high

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.











Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN2735	UN2735	UN2735	UN2735	UN2735	UN2735
UN proper shipping name	Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated)	Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated)	Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated)	Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated)	Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated)	Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated)

Section 14. Transport information

Transport hazard class(es)	8  	8  	8 	8  	8  	8 
Packing group	III	III	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

- DOT Classification** : This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.
- TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.
- Mexico Classification** : -
- ADR/RID** : Tunnel restriction code: (E)
Hazard identification number: 80
- IMDG** : Emergency schedules (EmS): F-A, S-B
Marine pollutant: Yes.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- Transport in bulk according to IMO instruments** : Not available.
- IMDG Code Segregation group** : 18 - Alkalis

Section 15. Regulatory information

- U.S. Federal regulations** :
- Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed
- Clean Air Act Section 602 Class I Substances** : Not listed
- Clean Air Act Section 602 Class II Substances** : Not listed
- DEA List I Chemicals (Precursor Chemicals)** : Not listed
- DEA List II Chemicals (Essential Chemicals)** : Not listed
- SARA 302/304**

Section 15. Regulatory information

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : ACUTE TOXICITY (oral) - Category 4
SKIN CORROSION - Category 1C
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1

Composition/information on ingredients

Name	%	Classification
Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	≥75 - ≤90	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1
Formaldehyde, oligomeric reaction products with phenol	≤10	EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
3-aminopropyldiethylamine	<5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1

State regulations

Massachusetts : The following components are listed: BUTYLATED HYDROXYTOLUENE; 3-(DIETHYLAMINO)-PROPYLAMINE

New York : None of the components are listed.

New Jersey : The following components are listed: 2,6-DI-tert-BUTYL-p-CRESOL; 3-(DIETHYLAMINO)PROPYLAMINE

Pennsylvania : The following components are listed: PHENOL, 2,6-BIS(1,1-DIMETHYLETHYL)-4-METHYL-; 1,3-PROPANEDIAMINE, N,N-DIETHYL-

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

Australia : Not determined.

Canada : Not determined.

China : Not determined.

Europe : Not determined.

Section 15. Regulatory information

Japan	: Not determined.
Malaysia	: Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	3
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
SKIN CORROSION - Category 1C	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

History

Date of printing	: 02.05.2024
Date of issue/Date of revision	: 02.05.2024
Date of previous issue	: 11.05.2023
Version	: 1.03

Key to abbreviations

: ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 UN = United Nations

References

: Not available.

Indicates information that has changed from previously issued version.

Section 16. Other information

[Notice to reader](#)

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

✔ Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.