



### Fenomastic My Home Smooth Silk

### Section 1. Identification

**Product name** : Fenomastic My Home Smooth Silk

30402 **Product code** 

: Waterborne paint. **Product description** 

**Product type** : Liquid.

Other means of : Not available.

identification

Supplier's details : Jotun Saudia Co Ltd.

> P.O. Box 34698 Jeddah 21478 Kingdom of Saudi Arabia Tel: +966 2 6350535 Fax: +966 2 6362483 SDSJotun@jotun.com

**Emergency telephone** 

number

: Jotun AS, Norway +47 33 45 70 00

### Section 2. Hazards identification

: SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 Classification of the LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 substance or mixture

**GHS label elements** 

Signal word : No signal word.

**Hazard statements** : H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

General : P102 - Keep out of reach of children. **Prevention** : P273 - Avoid release to the environment.

Response : Not applicable. **Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not : None known.

result in classification

### Section 3. Composition/information on ingredients

Substance/mixture Other means of

identification

: Not available.

### **CAS** number/other identifiers

**CAS** number : Not applicable.

**EC** number : Mixture. **Product code** 30402

Date of issue/Date of revision : 20.05.2022 : 20.05.2022 Version: 2.01 1/10 Date of previous issue

Fenomastic My Home Smooth Silk

### Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Alcohols, C16-18 and C18-unsatd., ethoxylated	≤0.28	68920-66-1
ammonia	≤0.26	1336-21-6
Amines, rosin	<0.1	61790-47-4
C(M)IT/MIT (3:1)	<0.003	55965-84-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person

may need to be kept under medical surveillance for 48 hours.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse.

Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been

swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Date of issue/Date of revision : 20.05.2022 Date of previous issue : 20.05.2022 Version : 2.01 2/10

### Section 4. First aid measures

See toxicological information (Section 11)

### Section 5. Firefighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** media

: None known.

metal oxide/oxides

### Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

### **Hazardous thermal** decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

### Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### **Special protective** equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 20.05.2022 : 20.05.2022 Version : 2.01 3/10 Date of previous issue

### Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
ammonia	ACGIH TLV (United States, 1/2021).  TWA: 25 ppm 8 hours.  TWA: 17 mg/m³ 8 hours.  STEL: 35 ppm 15 minutes.  STEL: 24 mg/m³ 15 minutes.

### Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

### **Skin protection**

Hand protection

Date of issue/Date of revision : 20.05.2022 Date of previous issue : 20.05.2022 Version : 2.01 4/10

### Section 8. Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to EN374.

Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber, PVC, neoprene

May be used, gloves(breakthrough time) 4 - 8 hours: 4H

**Body protection** : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: If workers are exposed to concentrations above the exposure limit, they must use a **Respiratory protection** respirator according to EN 140. By spraying: particulate filter (FFP2 / N95). In

confined spaces, use compressed-air or fresh-air respiratory equipment.

### Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour : White.

Odour : Characteristic. : Not applicable. **Odour threshold** 

: 8 to 10 pН : 0 **Melting point** 

**Boiling point** : Lowest known value: 100°C (212°F) (water). Weighted average: 102.29°C (216.1°F)

: Not available. Flash point

: Highest known value: 0.36 (water) Weighted average: 0.35compared with butyl **Evaporation rate** 

acetate

Flammability (solid, gas) Lower and upper explosive

(flammable) limits

: 2.6 - 12.6%

: Not applicable.

: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: Vapour pressure

3.12 kPa (23.4 mm Hg) (at 20°C)

Vapour density : Highest known value: 2.6 (Air = 1) (propylene glycol).

**Density** : 1.21 to 1.369 g/cm<sup>3</sup>

Solubility : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

: Not applicable. **Auto-ignition temperature Decomposition temperature** : Not available.

: Kinematic (40°C): >20.5 mm<sup>2</sup>/s (>20.5 cSt) **Viscosity** 

Date of issue/Date of revision : 20.05.2022 : 20.05.2022 Version : 2.01 5/10 Date of previous issue

### Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous

Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

: No specific data.

Conditions to avoid Incompatible materials

: No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ammonia	LD50 Oral	Rat	350 mg/kg	-
C(M)IT/MIT (3:1)	LD50 Oral	Rat	53 mg/kg	-

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Alcohols, C16-18 and C18-unsatd., ethoxylated	Skin - Mild irritant	Mammal - species unspecified	-	-	-
ammonia	Eyes - Severe irritant	Rabbit	-	250 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 milligrams	-
Amines, rosin	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Eyes - Mild irritant	Mammal - species unspecified	-	-	-

### **Sensitisation**

3	Route of exposure	Species	Result
C(M)IT/MIT (3:1)	skin	Mammal - species unspecified	Sensitising

### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Name	3 3 3	Route of exposure	Target organs
ammonia	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision : 20.05.2022 Date of previous issue : 20.05.2022 Version : 2.01 6/10

### **Section 11. Toxicological information**

Not available

#### **Aspiration hazard**

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

**Acute toxicity estimates** 

Not available.

Date of issue/Date of revision : 20.05.2022 Date of previous issue : 20.05.2022 Version : 2.01 7/10

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Alcohols, C16-18 and	Acute LC50 1.3 mg/l	Fish	96 hours
C18-unsatd., ethoxylated			
ammonia	Acute EC50 0.101 mg/l Fresh water	Daphnia	96 hours
	Acute LC50 0.89 mg/l Fresh water	Fish	96 hours
C(M)IT/MIT (3:1)	Acute EC50 0.048 mg/l	Algae - Pseudokirchneriella	72 hours
	_	subcapitata	
	Acute EC50 0.0052 mg/l	Algae - Skeletonema costatum	48 hours
	Acute EC50 0.1 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.22 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC 0.00064 mg/l	Algae - Skeletonema costatum	48 hours
	Chronic NOEC 0.0012 mg/l	Algae - Pseudokirchneriella	72 hours
		subcapitata	
	Chronic NOEC 0.004 mg/l	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.098 mg/l	Fish - Oncorhynchus mykiss	28 days

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ammonia C(M)IT/MIT (3:1)	-		Readily Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Alcohols, C16-18 and C18-unsatd., ethoxylated	4.2	-	high
ammonia C(M)IT/MIT (3:1)	<1 -	- 3.16	low low

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

### Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 20.05.2022 Date of previous issue : 20.05.2022 Version : 2.01 8/10

### **Section 14. Transport information**

	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

### Section 16. Other information

**History** 

**Date of printing** : 20.05.2022 : 20.05.2022 Date of issue/Date of

revision

Date of previous issue : 20.05.2022

**Version** : 2.01

Date of issue/Date of revision : 20.05.2022 : 20.05.2022 Version : 2.01 Date of previous issue 9/10 Fenomastic My Home Smooth Silk

### Section 16. Other information

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue/Date of revision : 20.05.2022 Date of previous issue : 20.05.2022 Version : 2.01 10/10