

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Produ	ct id	ontifi	or
1.1	FIUUU	LL IU	entin	ei

Product name Product code

Product type Other means of

identification

: Guard Miles+ W5 (C060)

: 33042

: Powder coating.

: Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use

1.3 Details of the supplier of the safety data sheet

Jotun A/S P.O.Box 2021 3202 Sandefjord Norway

Tel: + 47 33 45 70 00 Fax: +47 33 45 72 42 E-mail: SDSJotun@jotun.no

National contact

JOTUN CZECH a.s. NA ROVNEM 866 400 04 TRMICE CZECH REPUBLIC

Phone : + 420 477 828 969 Fax.: + 420 477 828 962 sdsjotun@jotun.com

1.4 Emergency telephone number

224 919 293 – Toxikologické informační středisko (TIS)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 11.04.2023 Date of previous issue	: 11.04.2023	Version : 1.01				
General	: Not applicable.						
Precautionary statements							
Hazard statements	: H412 - Harmful to aquatic life with lo	ong lasting effects.					
Signal word	: No signal word.						
2.2 Label elements							

1/14

SECTION 2: Hazards	ic	lentification
Prevention	:	P273 - Avoid release to the environment.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	EUH208 - Contains benzene-1,2,4-tricarboxylic acid 1,2-anhydride. May produce an allergic reaction. EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	ien	<u>its</u>
Containers to be fitted with child-resistant fastenings	1	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2	≥25 - ≤50	Carc. 2, H351 (inhalation)	-	[1] [2] [*]
EC: 231-784-4 CAS: 7727-43-7	≤10	Not classified.	-	[2]
REACH #: 01-2119977073-34 EC: 247-952-5 CAS: 26741-53-7	≤1	Aquatic Chronic 1, H410	M [Chronic] = 1	[1]
EC: 201-074-9 CAS: 77-99-6	≤1	Repr. 2, H361fd	-	[1]
REACH #: 01-2119489422-34 EC: 209-008-0 CAS: 552-30-7 Index: 607-097-00-4	≤0.3	Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [3]
	EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2 EC: 231-784-4 CAS: 7727-43-7 REACH #: 01-2119977073-34 EC: 247-952-5 CAS: 26741-53-7 EC: 201-074-9 CAS: 77-99-6 REACH #: 01-2119489422-34 EC: 209-008-0 CAS: 552-30-7	EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2 $\geq 25 - \leq 50$ EC: 231-784-4 CAS: 7727-43-7 ≤ 10 REACH #: 01-2119977073-34 EC: 247-952-5 CAS: 26741-53-7 ≤ 1 EC: 201-074-9 CAS: 77-99-6 ≤ 1 REACH #: 01-2119489422-34 EC: 209-008-0 CAS: 552-30-7 ≤ 0.3	EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2 $\geq 25 - \leq 50$ Carc. 2, H351 (inhalation)EC: 231-784-4 CAS: 7727-43-7 ≤ 10 Not classified.REACH #: 01-2119977073-34 EC: 247-952-5 CAS: 26741-53-7 ≤ 1 Aquatic Chronic 1, H410EC: 201-074-9 CAS: 77-99-6 ≤ 1 Repr. 2, H361fdREACH #: 01-2119489422-34 EC: 209-008-0 CAS: 552-30-7 ≤ 0.3 Eye Dam. 1, H318 Resp. Sens. 1, H317 STOT SE 3, H335	Identifiers 7_0 ClassificationLimits, M-factors and ATEsEC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2 $\geq 25 - \leq 50$ Carc. 2, H351 (inhalation)-EC: 231-784-4 CAS: 7727-43-7 ≤ 10 Not classifiedREACH #: 01-2119977073-34 EC: 247-952-5 CAS: 26741-53-7 ≤ 1 Aquatic Chronic 1, H410M [Chronic] = 1EC: 201-074-9 CAS: 77-99-6 ≤ 1 Repr. 2, H361fd-REACH #: 01-2119489422-34 EC: 209-008-0 CAS: 552-30-7 ≤ 0.3 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335-

Guard Miles+ W5 (C060)				
SECTION 3: Composition/information on ingredients				
		the full	ction 16 for text of the H ents declared	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix. This mixture contains \geq 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	1	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Contains benzene-1,2,4-tricarboxylic acid 1,2-anhydride. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special t	treatment needed
---	------------------

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Guard	Miles+	W5	(C060)
-------	--------	----	--------

SECTION 4: First aid measures

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO_2 blanket, water spray or mist.
Unsuitable extinguishing media	:	Do not use water jet. Do not use inert gas under high pressure (e.g. CO2).
5.2 Special hazards arising f	ron	n the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
		Fine dust clouds may form explosive mixtures with air.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and material for containment and cleaning up	:	Contain and collect spillage with an electrically protected vacuum cleaner or by wet- brushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe handling

SECTION 7: Handling and storage

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)

Recommendations: Not available.Industrial sector specific: Not available.solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Dust Limit : 10 mg/m³ (TWA of total inhalable dust) and 4 mg/m³ (TWA of respirable)

Product/ingredient name	Exposure limit values
titanium dioxide	EU OEL (Europe).
barium sulfate	TWA: 5 mg/m ³ 8 hours. Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 5/2021). TWA: 10 mg/m ³ 8 hours. Form: Dust
procedures European St assessment values and r atmosphere: of exposure (Workplace for the meas	hould be made to monitoring standards, such as the following: andard EN 689 (Workplace atmospheres - Guidance for the of exposure by inhalation to chemical agents for comparison with limit neasurement strategy) European Standard EN 14042 (Workplace s - Guide for the application and use of procedures for the assessment to chemical and biological agents) European Standard EN 482 atmospheres - General requirements for the performance of procedures urement of chemical agents) Reference to national guidance or methods for the determination of hazardous substances will also be
DNELs/DMELs	

Date of issue/Date of revision

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2,4,8,10-tetraoxa-3,9-diphosphaspiro [5.5]undecane, 3,9-bis[2,4-bis (1,1-dimethylethyl)phenoxy]-	DNEL	Long term Inhalation	0.68 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	2.75 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	0.39 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.39 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.78 mg/ kg bw/day	Workers	Systemic
propylidynetrimethanol	DNEL	Long term Inhalation	3.3 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	0.34 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.34 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.58 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.94 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.3 mg/m ³	Workers	Systemic
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	DNEL	Long term Oral	2.5 mg/kg bw/day	General population	Systemic
. ,	DNEL	Long term Dermal	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	4.4 mg/m ³	General population	Systemic
	DNEL	Short term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	8.8 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	10 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	17.5 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	35 mg/m³	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

Eye/face protection	: Safety eyewear complying to ISO 16321-1:2022 should be used when a risk
	assessment indicates this is necessary to avoid exposure to liquid splashes, mists,
	gases or dusts. If contact is possible, the following protection should be worn,
	unless the assessment indicates a higher degree of protection: safety glasses with
	side-shields.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

<u>Gloves</u>

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber (> 0.4 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection	: Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. If dust is generated and ventilation is inadequate, use respirator that will protect against dust/mist. (FFP2 / N95).
Environmental exposure controls	: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

7/14

9.1 Information on basic physical and chemical properties

Appearance				
Physical state	: Solid. Po	owder.		
Colour	: Various			
Odour	: Odourles	SS.		
Odour threshold	: Not appli	icable.		
Melting point (dust)	: 85 - 115	°C		
Initial boiling point and boiling range	: Not appli	icable.		
Lower explosion limit (dust)	: 30 g/m³ ((EN 14034-3)		
Minimum ignition energy (mJ)	: 10 - 30 (EN 13821)		
Flash point	:			
Auto-ignition temperature	: > 400°C			
Date of issue/Date of revision	: 11.04.2023	Date of previous issue	: 11.04.2023	Version : 1.01

SECTION 9: Physical and chemical properties

Decomposition temperature	1	230°C	
рН	1	Not applicable.	
Viscosity	:	Not applicable.	
Solubility in water	1	cold water hot water	Not soluble Not soluble
Partition coefficient: n-octanol/ water	:	Not applicable.	
Vapour pressure	:	Not applicable.	
Evaporation rate	:	Not applicable.	
Density	:	1.2 to 1.9 g/cm ³	
Vapour density	:	Not applicable.	
Explosive properties	1	Not available.	
Oxidising properties	1	Not available.	
Particle characteristics			
Median particle size	÷	Not available.	

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	Fine dust clouds may form explosive mixtures with air.		
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).		
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	:	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame).		
		Take precautionary measures against electrostatic discharges.		
		To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.		
		Prevent dust accumulation.		
10.5 Incompatible materials	:	Not applicable.		
10.6 Hazardous decomposition products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.		

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

Contains benzene-1,2,4-tricarboxylic acid 1,2-anhydride. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propylidynetrimethanol	LD50 Oral	Rat	14000 mg/kg	-

Acute toxicity estimates

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
propylidynetrimethanol	14000	N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours	-
2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane, 3,9-bis[2,4-bis (1,1-dimethylethyl)phenoxy]-	Skin - Severe irritant	Rabbit	-	0.5 Grams	-
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	Eyes - Irritant	Mammal - species unspecified	-	-	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	skin	Mammal - species unspecified	Sensitising

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

- **Developmental effects**
- No known significant effects or critical hazards.No known significant effects or critical hazards.

Fertility effects Teratogenicity

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
benzene-1,2,4-tricarboxylic acid 1,2-anhydride	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
2,4,8,10-tetraoxa- 3,9-diphosphaspiro[5.5] undecane, 3,9-bis[2,4-bis (1,1-dimethylethyl)phenoxy]-	Acute EC10 15.4 mg/l	Algae	72 hours
	Acute EC50 97 mg/l	Algae	72 hours
	Acute LC50 70.7 mg/l	Fish	96 hours
	Chronic NOEC 0.1 mg/l	Daphnia	21 days

Conclusion/Summary

: This material is harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol benzene-1,2,4-tricarboxylic acid 1,2-anhydride	-0.47 0.06	<1 -	low low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation		
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances		
Packaging			
Methods of disposal	packaging sho	n of waste should be avoided or minimised wherever possible. Waste uld be recycled. Incineration or landfill should only be considered g is not feasible.	
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. 		
Type of packaging		European waste catalogue (EWC)	
CEPE Guidelines	15 01 10*	packaging containing residues of or contaminated by hazardous substances	
Special precautions	taken when ha Empty contain	and its container must be disposed of in a safe way. Care should be indling emptied containers that have not been cleaned or rinsed out. ers or liners may retain some product residues. Avoid dispersal of nd runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
Date of issue/Date of re	vision : 11.04.2	023 Date of previous issu	e : 11.04.2023	Version : 1.01

Guard Miles+ W5 (C060)				
SECTION 14: Transport information				
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for	1	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in
		the event of an accident or spillage.

14.7 Maritime transport in	: Not available.
bulk according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	ngredient name	Status	Reference number	Date of revision
	benzene-1,2,4-tricarboxylic acid 1,2-anhydride	Recommended	ED/71/2019	14.04.2021
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles <u>Other EU regulations</u>	s : Not applicable.			
Industrial emissions (integrated pollution prevention and control) Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) Water	: Not listed			
Ozone depleting substant Not listed.	<u>nces (1005/2009/EU)</u>			
Prior Informed Consent Not listed.	(<u>PIC) (649/2012/EU)</u>			
Persistent Organic Pollu Not listed.	<u>tants</u>			
Seveso Directive This product is not control	led under the Seveso Directive.			

National regulations

SECTION 15: Regulatory information

Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
International regulations	
Chemical Weapon Convent	tion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol Not listed.	
Stockholm Convention on	Persistent Organic Pollutants
Not listed.	
Rotterdam Convention on Not listed.	Prior Informed Consent (PIC)
UNECE Aarhus Protocol or	<u>ı POPs and Heavy Metals</u>
Not listed.	

15.2 Chemical safety : Not applicable. **assessment**

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	: 11.04.2023
Date of issue/ Date of revision	: 11.04.2023
Date of previous issue	e : 11.04.2023
Version	: 1.01

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.