

Hardtop Peelable

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|--------------------------------------|-----------------------|
| Product name | : Hardtop Peelable |
| UFI | : R500-C3Q8-Q008-X093 |
| Product code | : 33582 |
| Product description | : Paint. |
| Product type | : Liquid. |
| Other means of identification | : Not available. |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use
Use in coatings - Professional use

1.3 Details of the supplier of the safety data sheet

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Norway

Tel: + 47 33 45 70 00
Fax: +47 33 45 72 42
E-mail: SDSJotun@jotun.no

1.4 Emergency telephone number

Norwegian National Poison Centre: +47 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning.

Hazard statements : H317 - May cause an allergic skin reaction.

Precautionary statements

General : Not applicable.

Hardtop Peelable**SECTION 2: Hazards identification**

| | |
|---|---|
| Prevention | : P280 - Wear protective gloves. P261 - Avoid breathing vapour. |
| Response | : P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. |
| Storage | : Not applicable. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : 2-methyl-2H-isothiazol-3-one (MIT) 2-octyl-2h-isothiazol-3-one (OIT) |
| Supplemental label elements | : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. |
| Special packaging requirements | |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known. |

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|------------------------------------|---|--------|--|--|---------|
| ethanediol | REACH #: 01-2119456816-28 EC: 203-473-3 CAS: 107-21-1 Index: 603-027-00-1 | ≤3 | Acute Tox. 4, H302 STOT RE 2, H373 (kidneys) (oral) | ATE [Oral] = 500 mg/kg | [1] [2] |
| 2-methyl-2H-isothiazol-3-one (MIT) | EC: 220-239-6 CAS: 2682-20-4 | <0.01 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1 | [1] |
| 2-octyl-2h-isothiazol-3-one | EC: 247-761-7 | <0.001 | Acute Tox. 3, H301 | ATE [Oral] = 100 | [1] |

*Hardtop Peelable***SECTION 3: Composition/information on ingredients**

| | | | | | |
|-------|--|--|---|--|--|
| (OIT) | CAS: 26530-20-1 Index: 613-112-00-5 | | Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above. | mg/kg ATE [Dermal] = 690 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 | |
|-------|--|--|---|--|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayedOver-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Hardtop Peelable

SECTION 4: First aid measures

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

*Hardtop Peelable***SECTION 7: Handling and storage**

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| ethanediol | <p>FOR-2011-12-06-1358 (Norway, 6/2021). Absorbed through skin. Notes: indicative limit value</p> <p>TWA: 52 mg/m³ 8 hours. Form: dust TWA: 20 ppm 8 hours.</p> <p>FOR-2011-12-06-1358 (Norway, 6/2021). Absorbed through skin.</p> <p>STEL: 104 mg/m³ 15 minutes. STEL: 40 ppm 15 minutes.</p> |

- Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Hardtop Peelable**SECTION 8: Exposure controls/personal protection**

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|------------------------------------|------|-----------------------|-------------------------|--------------------|----------|
| ethanediol | DNEL | Long term Inhalation | 7 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 35 mg/m ³ | Workers | Local |
| | DNEL | Long term Dermal | 53 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 106 mg/kg bw/day | Workers | Systemic |
| 2-methyl-2H-isothiazol-3-one (MIT) | DNEL | Long term Inhalation | 0.021 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 0.021 mg/m ³ | Workers | Local |
| | DNEL | Long term Oral | 0.027 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 0.043 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 0.043 mg/m ³ | Workers | Local |
| | DNEL | Short term Oral | 0.053 mg/kg bw/day | General population | Systemic |

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection**Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves

Hardtop Peelable**SECTION 8: Exposure controls/personal protection**

Wear suitable gloves tested to ISO 374-1:2016.

May be used, gloves(breakthrough time) 4 - 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm)

Recommended, gloves(breakthrough time) > 8 hours: butyl rubber (> 0.4 mm), Viton® (> 0.7 mm), 4H/Silver Shield® (> 0.07 mm), Teflon (> 0.35 mm), nitrile rubber (> 0.4 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties**Appearance**

- Physical state** : Liquid.
- Colour** : Pink
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- Melting point/freezing point** : 0
- Initial boiling point and boiling range** : Lowest known value: 100°C (212°F) (water). Weighted average: 103.64°C (218.6°F)
- Flammability** : Not applicable.
- Lower and upper explosion limit** : 3.2 - 15.3%
- Flash point** : Not applicable.
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : 9.6
- Viscosity** : Kinematic (40°C): >20.5 mm²/s
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Vapour pressure** : Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 3.08 kPa (23.1 mm Hg) (at 20°C)
- Evaporation rate** : Highest known value: 0.36 (water) Weighted average: 0.35 compared with butyl acetate
- Density** : 1.076 to 1.084 g/cm³
- Vapour density** : Highest known value: 2.1 (Air = 1) (ethanediol).
- Explosive properties** : Not available.
- Oxidising properties** : Not available.

Hardtop Peelable**SECTION 9: Physical and chemical properties****Particle characteristics****Median particle size** : Not applicable.**9.2 Other information**

No additional information.

SECTION 10: Stability and reactivity**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|---------|------------|----------|
| ethanediol 2-octyl-2h-isothiazol-3-one (OIT) | LD50 Oral | Rat | 4700 mg/kg | - |
| | LD50 Dermal | Rabbit | 690 mg/kg | - |
| | LD50 Dermal | Rabbit | 690 mg/kg | - |
| | LD50 Oral | Rat | 550 mg/kg | - |

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|------------------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| Hardtop Peelable | 25000 | N/A | N/A | N/A | N/A |
| ethanediol | 500 | N/A | N/A | N/A | N/A |
| 2-methyl-2H-isothiazol-3-one (MIT) | 100 | 300 | N/A | 0.5 | N/A |
| 2-octyl-2h-isothiazol-3-one (OIT) | 100 | 690 | N/A | N/A | 0.05 |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| ethanediol | Eyes - Mild irritant | Rabbit | - | 1 hours 100 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 6 hours 1440 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 555 milligrams | - |

Sensitisation

Hardtop Peelable**SECTION 11: Toxicological information**

| Product/ingredient name | Route of exposure | Species | Result |
|------------------------------------|-------------------|------------------------------|-------------|
| 2-methyl-2H-isothiazol-3-one (MIT) | skin | Mammal - species unspecified | Sensitising |
| 2-octyl-2h-isothiazol-3-one (OIT) | skin | Mammal - species unspecified | Sensitising |

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity**Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.**Teratogenicity**

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| ethanediol | Category 2 | oral | kidneys |

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

| Product/ingredient name | Result | Species | Exposure |
|------------------------------------|--------------------------------------|-----------------------------------|----------|
| ethanediol | Acute LC50 41000000 µg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| 2-methyl-2H-isothiazol-3-one (MIT) | Acute EC50 0.445 mg/l | Algae | 24 hours |
| 2-octyl-2h-isothiazol-3-one (OIT) | Acute EC50 2.94 mg/l | Daphnia | 48 hours |
| | Acute LC50 6 mg/l | Fish | 96 hours |
| | Acute EC50 0.084 mg/l | Algae - Scenedesmus subspicatus | 72 hours |
| | Acute EC50 0.32 mg/l | Daphnia | 48 hours |
| | Acute LC50 0.047 mg/l | Fish | 96 hours |

Conclusion/Summary : No known significant effects or critical hazards.**12.2 Persistence and degradability****Conclusion/Summary** : Not available.**12.3 Bioaccumulative potential**

Hardtop Peelable**SECTION 12: Ecological information**

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-----------------------------------|--------------------|-----|-----------|
| ethanediol | -1.36 | - | low |
| 2-octyl-2h-isothiazol-3-one (OIT) | 2.45 | - | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | Waste paint and varnish containing organic solvents or other dangerous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Hardtop Peelable

SECTION 13: Disposal considerations

| Type of packaging | European waste catalogue (EWC) |
|-------------------|---|
| CEPE Guidelines | 15 01 10* packaging containing residues of or contaminated by hazardous substances |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Hardtop Peelable

SECTION 15: Regulatory information

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Norway

Product registration number : Under declaration

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available

Hardtop Peelable

SECTION 16: Other information

PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|--------------------|--------------------|
| Skin Sens. 1, H317 | Calculation method |

Full text of abbreviated H statements

| | |
|------|--|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Full text of classifications [CLP/GHS]

| | |
|-------------------|---|
| Acute Tox. 2 | ACUTE TOXICITY - Category 2 |
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Skin Corr. 1 | SKIN CORROSION/IRRITATION - Category 1 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |

Date of printing : 24.03.2023

Date of issue/ Date of revision : 24.03.2023

Date of previous issue : 23.03.2023

Version : 1.05

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Hardtop Peelable

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor spray painting by professionals with efficient ventilation such as spray booth or local exhaust ventilation

This safe use information is linked to SWED no. : Professional spray painting, near-industrial setting
Jotun_CEPE_PW_01_ABCA

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|--|---------------------------------------|--|---|--|
| | | | Type | ach (air changes per hour) | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Professional application of coatings and inks by spraying | PROC11 | More than 4 hours | Local exhaust ventilation | Refer to relevant technical standards | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Film formation - force drying, stoving and other technologies | PROC04 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10 | None | None | None |
| Cleaning | PROC05 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Waste management | PROC08a | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |

See chapter 8 of this Safety Data Sheet for specifications.



The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

Hardtop Peelable

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor painting by professionals with brush, roller, putty knife etc. with enhanced ventilation or LEV

This safe use information is linked to SWED no. : Professional low-energy painting, near-industrial setting
Jotun_CEPE_PW_02_ACBA

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|--|---------------------------------------|--|---|--|
| | | | Type | ach (air changes per hour) | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Local exhaust ventilation | Refer to relevant technical standards | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Local exhaust ventilation | Refer to relevant technical standards | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Professional application of coatings and inks by brush or roller | PROC10 | More than 4 hours | Local exhaust ventilation | Refer to relevant technical standards | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Film formation - air drying | PROC04 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Cleaning | PROC05 | More than 4 hours | Local exhaust ventilation | Refer to relevant technical standards | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Waste management | PROC08a | More than 4 hours | Local exhaust ventilation | Refer to relevant technical standards | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |

See chapter 8 of this Safety Data Sheet for specifications.



The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

Hardtop Peelable

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor spray painting by professionals for specialist applications, with good general room ventilation plus respiratory protection

This safe use information is linked to SWED no. : Professional spray painting, indoor (Level II)
Jotun_CEPE_PW_03b_AABA

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|-------------------------------|----------------------------|--|---|--|
| | | | Type | ach (air changes per hour) | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Professional application of coatings and inks by spraying | PROC11 | More than 4 hours | Good general room ventilation | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Film formation - force drying, stoving and other technologies | PROC04 | More than 4 hours | Good general room ventilation | 3 - 5 | None | None | None |
| Cleaning | PROC05 | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Waste management | PROC08a | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |

See chapter 8 of this Safety Data Sheet for specifications.



The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

Hardtop Peelable

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor painting by professionals with brush or roller, with good general room ventilation (open doors/windows)

This safe use information is linked to SWED no. : Professional painting, indoor brush/roller
Jotun_CEPE_PW_04_AAAA

Product category(ies) : Coatings and paints, thinners, paint removers


Operational conditions

Place of use : Indoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|-------------------------------|----------------------------|-------------|---|--|
| | | | Type | ach (air changes per hour) | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Professional application of coatings and inks by brush or roller | PROC10 | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Film formation - force drying, stoving and other technologies | PROC04 | More than 4 hours | Good general room ventilation | 3 - 5 | None | None | None |
| Cleaning | PROC05 | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Waste management | PROC08a | More than 4 hours | Good general room ventilation | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |

See chapter 8 of this Safety Data Sheet for specifications.



The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

Hardtop Peelable

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Outdoor spray painting by professionals for specialist applications, with respiratory protection

This safe use information is linked to SWED no. : Professional spray painting, outdoor (Level II)
Jotun_CEPE_PW_05b_AEBA

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Outdoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|-------------|----------------------------|--|---|--|
| | | | Type | ach (air changes per hour) | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Outdoors | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Outdoors | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Professional application of coatings and inks by spraying | PROC11 | More than 4 hours | Outdoors | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Film formation - force drying, stoving and other technologies | PROC04 | More than 4 hours | Outdoors | 3 - 5 | None | None | Wear suitable gloves tested to ISO 374-1:2016. |
| Cleaning | PROC05 | More than 4 hours | Outdoors | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Waste management | PROC08a | More than 4 hours | Outdoors | 3 - 5 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |

See chapter 8 of this Safety Data Sheet for specifications.



The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

Hardtop Peelable

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Outdoor painting by professionals with brush or roller

This safe use information is linked to SWED no. : Professional painting, outdoor brush/roller
Jotun_CEPE_PW_06_AEAA

Product category(ies) : Coatings and paints, thinners, paint removers


Operational conditions

Place of use : Outdoor use

Risk management measures (RMM)

| Contributing activity | Process category (ies) | Maximum duration | Ventilation | | Respiratory | Eye | Hands |
|---|------------------------|-------------------|-------------|----------------------------|-------------|---|--|
| | | | Type | ach (air changes per hour) | | | |
| Preparation of material for application | PROC05 | More than 4 hours | Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Loading of application equipment and handling of coated parts before curing | PROC08a | More than 4 hours | Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Professional application of coatings and inks by brush or roller | PROC10 | More than 4 hours | Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Film formation - force drying, stoving and other technologies | PROC04 | More than 4 hours | Outdoors | 3 - 5 | None | None | None |
| Cleaning | PROC05 | More than 4 hours | Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |
| Waste management | PROC08a | More than 4 hours | Outdoors | 3 - 5 | None | Use eye protection according to EN 166. | Wear suitable gloves tested to ISO 374-1:2016. |

See chapter 8 of this Safety Data Sheet for specifications.



The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.