

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Jotun Super Durable 2003 (B004)
Product code	: 37269
Product description	: Paint.
Product type	: Solid.
Other means of identification	: Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Uses in Coatings - Industrial use

1.3 Details of the supplier of the safety data sheet

Jotun Saudia Co Ltd. P.O. Box 34698 Jeddah 21478 Kingdom of Saudi Arabia Tel: +966 2 6350535 Fax: +966 2 6362483 SDSJotun@jotun.com

1.4 Emergency telephone number

SHE Dept. Jotun AS, Norway +47 33 45 70 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	: Muta. Cat. 2; R46 Xn; R20/22
	Xi; R36 R43
Human health hazards	: May cause heritable genetic damage. Also harmful by inhalation and if swallowed. Irritating to eyes. May cause sensitisation by skin contact.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date	of issue	•
		•

Jotun Protects Property

SECTION 2: Hazards identification

Hazard pictograms	
Signal word	: Danger.
Hazard statements	: Harmful if swallowed. Causes serious eye damage. May cause an allergic skin reaction. May cause genetic defects.
Precautionary statements	
General	: Not applicable.
Prevention	: Avoid breathing dust.Obtain special instructions before use. Wear protective gloves. Wear eye or face protection.
Response	 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. If skin irritation or rash occurs: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6,6-tetramethylpiperidin-4-yl)amino) triazin-2-yl)-4,7-diazadecane-1,10-diamine zinc di(benzothiazol-2-yl) disulphide
Supplemental label elements	: Not applicable.

2.3 (Other	hazards
-------	-------	---------

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

			<u>Classif</u>	<u>ication</u>		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре	Notes
1,3,5-tris (oxiranylmethyl)-1,3, 5-triazine-2,4,6(1H, 3H,5H)-trione	EC: 219-514-3 CAS: 2451-62-9 Index: 615-021-00-6	<10	Muta. Cat. 2; R46 T; R23/25 Xn; R48/22 Xi; R41 R43 R52/53	Acute Tox. 3, H301 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340 STOT RE 2, H373 Aquatic Chronic 3, H412	[1]	E
chromium (III) oxide	EC: 215-160-9 CAS: 1308-38-9	≤3	Not classified. See Section 16 for the full text of the R- phrases declared above.	Not classified. See Section 16 for the full text of the H statements declared above.	[2]	-

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

Jotun Super Durable 2003 (B004)

SECTION 3: Composition/information on ingredients

Туре

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health ef	f <u>ects</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
Over-exposure signs/sy	mptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
1.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire sympto

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

	0
5.1 Extinguishing media	
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ blanket, water spray or mist.
Unsuitable extinguishing	: Do not use water jet.
media	Do not use inert gas under high pressure (e.g. CO2).
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: No specific fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Date of issue : 01.0	2.2017
----------------------	--------

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

During stoving/curing caprolactam will be released. Efficient oven extraction must be provided to safely discharge caprolactam from the workplace.

Welding, grinding and other hot work on the already-coated substrate may cause free isocyanates to be formed and released.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s) Recommendations

solutions

Date of issue

: Not available.

Industrial sector specific : Not available.

SECTION 8: Exposure controls/personal protection

: 01.02.2017

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values	
chromium (iii) oxide		EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 2 mg/m ³ , () 8 hours. Form:	
Recommended monitoring procedures	atmosphere or l of the ventilation protective equip the following: E the assessment limit values and atmospheres - (of exposure to c (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness in or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as suropean Standard EN 689 (Workplace atmospheres - Guidance for to of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 hospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be	
Derived no effect levels No DNELs available.			

SECTION 8: Exposure controls/personal protection

Predicted no effect concentrations

No PNECs available.

8.2 Exposure controls		
Appropriate engineering controls	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worke exposure to airborne contaminants below any recommended or statutory limits.	er
Individual protection meas		
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working peri Appropriate techniques should be used to remove potentially contaminated cloth Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	hing.
Eye/face protection	Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles a or face shield. If inhalation hazards exist, a full-face respirator may be required instead.	and/
Skin protection		
Hand protection	There is no one glove material or combination of materials that will give unlimiter resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glo material. Always ensure that gloves are free from defects and that they are stored and us correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not applied once exposure has occurred. For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves. The user must check that the final choice of type of glove selected for handling to product is the most appropriate and takes into account the particular conditions use, as included in the user's risk assessment.	ove sed t be of this
Body protection	Personal protective equipment for the body should be selected based on the tas being performed and the risks involved and should be approved by a specialist before handling this product.	sk
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	Эе
Respiratory protection	If workers are exposed to concentrations above the exposure limit, they must us respirator according to EN 140. If dust is generated and ventilation is inadequate use respirator that will protect against dust/mist. (FFP2 / N95).	
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislatior In some cases, fume scrubbers, filters or engineering modifications to the proce equipment will be necessary to reduce emissions to acceptable levels.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Solid.
Colour	1	Various
Odour	:	Odourless.
Odour threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	1	Not applicable.
Initial boiling point and boiling range	:	Not available.
Flash point	1	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	1	Not applicable.
Burning time	:	Not available.
Burning rate	:	Not available.
Upper/lower flammability or explosive limits	:	
Vapour pressure	:	Not available.
Vapour density	:	Not available.
Relative density	:	1.2 to 1.9 g/cm ³
Solubility(ies)	1	Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	>230°C
Viscosity	:	Kinematic (40°C): >0,205 cm²/s (>20,5 mm²/s)
Explosive properties	1	Not available.
Oxidising properties	1	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Not applicable.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

SECTION 11: Toxicological information

Caprolactam is classified as hazardous to human health and the toxicity effects are described by the following hazard statements: Harmful if swallowed or if inhaled (H302 + H332), Causes skin irritation (H315), Causes serious eye irritation (H319), May cause respiratory irritation (H335).

Contains 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione, N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6, 6-tetramethylpiperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10-diamine, zinc di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-tris(oxiranylmethyl)-1, 3,5-triazine-2,4,6(1H,3H,5H) -trione	LD50 Oral	Rat	138 mg/kg	-

Acute toxicity estimates

Route	ATE value
Oral	1520 mg/kg
Inhalation (vapours)	45,6 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-tris(oxiranylmethyl)-1,3, 5-triazine-2,4,6(1H,3H,5H)- trione	Eyes - Severe irritant	Rabbit	-	100 milligrams	-

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)- trione	Category 2	Not determined	Not determined

Aspiration hazard

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary

: No known significant effects or critical hazards.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3,5-tris(oxiranylmethyl)-1,3, 5-triazine-2,4,6(1H,3H,5H)- trione	-0,8	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

Date of issue : 01.02.2017 8/1			
	Date of Issue	01.02.2017	8/11

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

Jotun Super Durable 2003 (B004)

SECTION 12: Ecological information

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

 Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

 European waste catalogue (EWC)
 : 08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

This preparation is not classified as dangerous according to international transport regulations (ADR/RID, IMDG or ICAO/IATA).

14.1 UN number	: Not regulated.
14.2 UN proper shipping name	: -
14.3 Transport hazard class(es)	: -
14.4 Packing group	: -
14.5 Environmental hazards	: No.
14.6 Special procession	: Transport within user's premises: always transport in closed containers that are
14.6 Special precautions for user	upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
	upright and secure. Ensure that persons transporting the product know what to do in
for user	upright and secure. Ensure that persons transporting the product know what to do in

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

<u>Mutagen</u>

	Ingredient name		Reference number	
1,3,5-Tris(oxiran-2-ylme	thyl)-1,3,5-triazinane-2,4,6-trione; TGIC	Candidate	ED/87/2012	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Restricted to professional users.			
Other EU regulations				
Europe inventory	: Not determined.			
Date of issue	: 01.02.2017		9/	

SECTION 15: Regulatory information

Black List Chemicals	: Not listed			
Priority List Chemicals	: Not determined			
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
1,3,5-tris(oxiranylmethyl)-1, 3,5-triazine-2,4,6(1H,3H, 5H)-trione	-	Muta. 1B, H340	-	-
Chemical Weapons Convention List Schedule I Chemicals	: Not listed			
Chemical Weapons Convention List Schedule II Chemicals	: Not listed			
Chemical Weapons Convention List Schedule III Chemicals	: Not listed			
.2 Chemical safety sessment	: Not applicable.			

SECTION 16: Other information

Indicates information	that has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Muta. 1B, H340	Calculation method

 H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H340 May cause genetic defects. 	Full text of abbreviated H statements	H318 H331 H340 H373	Causes serious eye damage. Toxic if inhaled. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------	------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 16: Other information

Full text of classifications [CLP/GHS]	: Acute Tox. 3, H301ACUTE TOXICITY (oral) - Category 3Acute Tox. 3, H331ACUTE TOXICITY (inhalation) - Category 3Acute Tox. 4, H302ACUTE TOXICITY (oral) - Category 4Aquatic Chronic 3, H412LONG-TERM AQUATIC HAZARD - Category 3Eye Dam. 1, H318SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1Muta. 1B, H340GERM CELL MUTAGENICITY - Category 1BSkin Sens. 1, H317SKIN SENSITIZATION - Category 1STOT RE 2, H373SPECIFIC TARGET ORGAN TOXICITY (REPEATEDEXPOSURE) - Category 2
Full text of abbreviated R phrases	 R46- May cause heritable genetic damage. R23/25- Also toxic by inhalation and if swallowed. R20/22- Also harmful by inhalation and if swallowed. R48/22- Also harmful: danger of serious damage to health by prolonged exposure if swallowed. R41- Risk of serious damage to eyes. R36- Irritating to eyes. R43- May cause sensitisation by skin contact. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Full text of classifications [DSD/DPD]	: Muta. Cat. 2 - Mutagen category 2 T - Toxic Xn - Harmful Xi - Irritant
Date of printing	: 01.02.2017
Date of issue/ Date of revision	: 01.02.2017
Date of previous issue	: No previous validation
Version	: 1
Notice to reader	

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.