

## Aqualine Spray

## Section 1. Identification

|                                      |  |
|--------------------------------------|--|
| <b>Product name</b>                  | : Aqualine Spray   |
| <b>Product code</b>                  | : 39522  |
| <b>Product description</b>           | : Paint.   |
| <b>Product type</b>                  | : Aerosol.   |
| <b>Other means of identification</b> | : Not available.   |
| <b>Supplier's details</b>            | : Jotun UAE Ltd. L.L.C.<br>P.O.Box 3671, Dubai, U.A.E.<br>Tel: 009714 3395000<br>Fax:009714 3380666<br><br>Jotun Abu Dhabi L.L.C.<br>P.O.box-3714<br>Abu Dhabi U.A.E.<br>Tel: 00971 2 5510300<br>Fax:00971 2 5510232<br><br>SDSJotun@jotun.com |
| <b>Emergency telephone number</b>    | : SHE Dept. Jotun AS, Norway<br>+47 33 45 70 00  |

## Section 2. Hazards identification

|   |  |
|---|--|
| <b>Classification of the substance or mixture</b> | : AEROSOLS - Category 1<br>SKIN CORROSION/IRRITATION - Category 3<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A<br>SKIN SENSITISATION - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3<br>SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
|---|--|

### GHS label elements

#### Hazard pictograms



#### Signal word

: Danger.

#### Hazard statements

: H222, H229 - Extremely flammable aerosol. Pressurised container: may burst if heated.  
H316 - Causes mild skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H410 - Very toxic to aquatic life with long lasting effects.

### Precautionary statements

#### General

: P102 - Keep out of reach of children.

## Section 2. Hazards identification

- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing dust or mist.  
P264 - Wash hands thoroughly after handling.  
P251 - Do not pierce or burn, even after use.
- Response** : P391 - Collect spillage.  
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Other means of identification** : Not available.

### CAS number/other identifiers

**CAS number** : Not applicable.  
**EC number** : Mixture.  
**Product code** : 39522

| Ingredient name                 | %         | CAS number |
|---------------------------------|-----------|------------|
| copper thiocyanate              | ≥10 - ≤25 | 1111-67-7  |
| zinc oxide                      | ≥10 - ≤25 | 1314-13-2  |
| hydrocarbons, C9, aromatics     | ≤10       | 64742-95-6 |
| acetone; propan-2-one           | ≤10       | 67-64-1    |
| colophony                       | ≤10       | 8050-09-7  |
| ethyl acetate                   | ≤10       | 141-78-6   |
| xylene                          | ≤5        | 1330-20-7  |
| 2-methoxy-1-methylethyl acetate | ≤5        | 108-65-6   |
| butan-1-ol                      | ≤2.1      | 71-36-3    |
| ethylbenzene                    | ≤3        | 100-41-4   |
| 1-methoxy-2-propanol            | ≤3        | 107-98-2   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause drowsiness or dizziness.
- Skin contact** : Causes mild skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

## Section 4. First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## Section 6. Accidental release measures

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name       | Exposure limits  |
|-----------------------|--|
| acetone; propan-2-one | <b>ACGIH TLV (United States, 1/2021).</b><br>STEL: 500 ppm 15 minutes.<br>TWA: 250 ppm 8 hours.            |
| colophony             | <b>ACGIH TLV (United States, 1/2021). Skin sensitiser. Inhalation sensitiser.</b>                          |
| ethyl acetate         | <b>ACGIH TLV (United States, 1/2021).</b><br>TWA: 1440 mg/m <sup>3</sup> 8 hours.<br>TWA: 400 ppm 8 hours. |

## Section 8. Exposure controls/personal protection

|                      |   |
|----------------------|---|
| xylene               | <b>ACGIH TLV (United States, 1/2021).</b><br>STEL: 651 mg/m <sup>3</sup> 15 minutes.<br>STEL: 150 ppm 15 minutes.<br>TWA: 434 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours. |
| butan-1-ol           | <b>ACGIH TLV (United States, 1/2021).</b><br>TWA: 20 ppm 8 hours.   |
| ethylbenzene         | <b>ACGIH TLV (United States, 1/2021).</b><br><b>Notes: K</b><br>TWA: 20 ppm 8 hours. Form:  |
| 1-methoxy-2-propanol | <b>ACGIH TLV (United States, 1/2021).</b><br>STEL: 369 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 184 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.  |

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. Wear suitable gloves tested to EN374. Not recommended, gloves(breakthrough time) < 1 hour: Saranex, PE  
May be used, gloves(breakthrough time) 4 - 8 hours: butyl rubber, Viton®, PVC, nitrile rubber, neoprene, polyvinyl alcohol (PVA)  
Recommended, gloves(breakthrough time) > 8 hours: Trellehen HPS, Tychem 10000, Teflon, Barricade, CPF 3, Responder, 4H

## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Aerosol.]
- Colour** : Grey, Black
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- pH** : Not applicable.
- Melting point** : Not applicable.
- Boiling point** : Lowest known value: 56.05°C (132.9°F) (acetone). Weighted average: 116.44°C (241.6°F)
- Flash point** : Closed cup: -7°C (19.4°F)
- Evaporation rate** : Highest known value: 6.06 (acetone) Weighted average: 3.36compared with butyl acetate
- Flammability (solid, gas)** : Not applicable.
- Lower and upper explosive (flammable) limits** : 0.8 - 13.74%
- Vapour pressure** : Highest known value: 24 kPa (180 mm Hg) (at 20°C) (acetone). Weighted average: 10.48 kPa (78.61 mm Hg) (at 20°C)
- Vapour density** : Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 3.01 (Air = 1)
- Density** : 1.267 g/cm<sup>3</sup>
- Solubility** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Lowest known value: 270°C (518°F) (1-methoxy-2-propanol).
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C): Not applicable.
- Aerosol product**
- Type of aerosol** : Spray
- Heat of combustion** : 15.89 kJ/g

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : No specific data.

## Section 10. Stability and reactivity

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name         | Result                 | Species    | Dose        | Exposure |
|---------------------------------|------------------------|------------|-------------|----------|
| ethyl acetate<br>xylene         | LD50 Oral              | Rat        | 5620 mg/kg  | -        |
|                                 | LC50 Inhalation Vapour | Rat        | 20 mg/l     | 4 hours  |
|                                 | LD50 Oral              | Rat        | 4300 mg/kg  | -        |
| 2-methoxy-1-methylethyl acetate | TDLo Dermal            | Rabbit     | 4300 mg/kg  | -        |
|                                 | LD50 Dermal            | Rabbit     | >5 g/kg     | -        |
|                                 | LD50 Oral              | Rat        | 8532 mg/kg  | -        |
| butan-1-ol<br>ethylbenzene      | LD50 Oral              | Rat        | 790 mg/kg   | -        |
|                                 | LC50 Inhalation Vapour | Rat - Male | 17.8 mg/l   | 4 hours  |
|                                 | LD50 Dermal            | Rabbit     | >5000 mg/kg | -        |
| 1-methoxy-2-propanol            | LD50 Oral              | Rat        | 3500 mg/kg  | -        |
|                                 | LD50 Dermal            | Rabbit     | 13 g/kg     | -        |
|                                 | LD50 Oral              | Rat        | 6600 mg/kg  | -        |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species                      | Score | Exposure                 | Observation |
|-------------------------|--------------------------|------------------------------|-------|--------------------------|-------------|
| zinc oxide              | Eyes - Mild irritant     | Rabbit                       | -     | 24 hours 500 mg          | -           |
|                         | Skin - Mild irritant     | Rabbit                       | -     | 24 hours 500 mg          | -           |
| acetone; propan-2-one   | Eyes - Mild irritant     | Human                        | -     | 186300 parts per million | -           |
|                         | Eyes - Mild irritant     | Rabbit                       | -     | 10 microliters           | -           |
|                         | Eyes - Moderate irritant | Rabbit                       | -     | 24 hours 20 milligrams   | -           |
|                         | Eyes - Severe irritant   | Rabbit                       | -     | 20 milligrams            | -           |
|                         | Skin - Mild irritant     | Rabbit                       | -     | 24 hours 500 milligrams  | -           |
|                         | Skin - Mild irritant     | Rabbit                       | -     | 395 milligrams           | -           |
| ethyl acetate           | Eyes - Mild irritant     | Mammal - species unspecified | -     | -                        | -           |
|                         | Eyes - Mild irritant     | Mammal - species unspecified | -     | -                        | -           |
| xylene                  | Eyes - Mild irritant     | Rabbit                       | -     | 87 milligrams            | -           |
|                         | Skin - Mild irritant     | Rat                          | -     | 8 hours 60 microliters   | -           |
| 1-methoxy-2-propanol    | Eyes - Mild irritant     | Rabbit                       | -     | 24 hours 500 mg          | -           |
|                         | Skin - Mild irritant     | Rabbit                       | -     | 500 mg                   | -           |

#### Sensitisation

| Product/ingredient name | Route of exposure | Species                      | Result      |
|-------------------------|-------------------|------------------------------|-------------|
| colophony               | skin              | Mammal - species unspecified | Sensitising |

#### Mutagenicity

Not available.

#### Carcinogenicity



## Section 11. Toxicological information

Not available.

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

| Name                            | Category   | Route of exposure | Target organs                |
|---------------------------------|------------|-------------------|------------------------------|
| hydrocarbons, C9, aromatics     | Category 3 | -                 | Respiratory tract irritation |
| acetone; propan-2-one           | Category 3 | -                 | Narcotic effects             |
| ethyl acetate                   | Category 3 | -                 | Narcotic effects             |
| xylene                          | Category 3 | -                 | Respiratory tract irritation |
| 2-methoxy-1-methylethyl acetate | Category 3 | -                 | Narcotic effects             |
| butan-1-ol                      | Category 3 | -                 | Respiratory tract irritation |
| 1-methoxy-2-propanol            | Category 3 | -                 | Narcotic effects             |
|                                 | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Name         | Category   | Route of exposure | Target organs  |
|--------------|------------|-------------------|----------------|
| ethylbenzene | Category 2 | -                 | hearing organs |

### Aspiration hazard

| Name                        | Result                         |
|-----------------------------|--------------------------------|
| hydrocarbons, C9, aromatics | ASPIRATION HAZARD - Category 1 |
| xylene                      | ASPIRATION HAZARD - Category 1 |
| ethylbenzene                | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause drowsiness or dizziness.
- Skin contact** : Causes mild skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

## Section 11. Toxicological information

- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Oral                 | 31055.9 mg/kg  |
| Dermal               | 27149.14 mg/kg |
| Inhalation (vapours) | 359.12 mg/l    |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name          | Result                             | Species  | Exposure |
|----------------------------------|------------------------------------|--|----------|
| copper thiocyanate<br>zinc oxide | Acute LC50 0.07 mg/l               | Fish - Lepomis macrochirus   | 96 hours |
|                                  | Acute LC50 1.1 ppm Fresh water     | Fish - Oncorhynchus mykiss   | 96 hours |
|                                  | Chronic NOEC 0.02 mg/l Fresh water | Algae - Pseudokirchneriella subcapitata - Exponential growth phase | 72 hours |
| hydrocarbons, C9, aromatics      | Acute EC50 <10 mg/l                | Daphnia  | 48 hours |
|                                  | Acute IC50 <10 mg/l                | Algae  | 72 hours |
| xylene                           | Acute LC50 <10 mg/l                | Fish   | 96 hours |
|                                  | Acute LC50 8500 µg/l Marine water  | Crustaceans - Palaemonetes pugio                                   | 48 hours |
| ethylbenzene                     | Acute LC50 13400 µg/l Fresh water  | Fish - Pimephales promelas   | 96 hours |
|                                  | Acute EC50 7700 µg/l Marine water  | Algae - Skeletonema costatum                                       | 96 hours |
|                                  | Acute EC50 2.93 mg/l               | Daphnia  | 48 hours |
|                                  | Acute LC50 4.2 mg/l                | Fish   | 96 hours |

### Persistence and degradability

## Section 12. Ecological information

| Product/ingredient name     | Aquatic half-life | Photolysis | Biodegradability |
|-----------------------------|-------------------|------------|------------------|
| copper thiocyanate          | -                 | -          | Not readily      |
| zinc oxide                  | -                 | -          | Not readily      |
| hydrocarbons, C9, aromatics | -                 | -          | Not readily      |
| xylene                      | -                 | -          | Readily          |
| ethylbenzene                | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name         | LogP <sub>ow</sub> | BCF         | Potential |
|---------------------------------|--------------------|-------------|-----------|
| zinc oxide                      | -                  | 28960       | high      |
| hydrocarbons, C9, aromatics     | -                  | 10 to 2500  | high      |
| acetone; propan-2-one           | -0.23              | -           | low       |
| colophony                       | 1.9 to 7.7         | -           | high      |
| ethyl acetate                   | 0.68               | 30          | low       |
| xylene                          | 3.12               | 8.1 to 25.9 | low       |
| 2-methoxy-1-methylethyl acetate | 1.2                | -           | low       |
| butan-1-ol                      | 1                  | -           | low       |
| ethylbenzene                    | 3.6                | -           | low       |
| 1-methoxy-2-propanol            | <1                 | -           | low       |

### Mobility in soil






Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

|                                   | ADR/RID  | IMDG   | IATA   |
|-----------------------------------|--|--|--|
| <b>UN number</b>                  | UN1950   | UN1950   | UN1950   |
| <b>UN proper shipping name</b>    | AEROSOLS, flammable  | AEROSOLS, flammable.<br>Marine pollutant (copper thiocyanate)  | AEROSOLS, flammable  |
| <b>Transport hazard class(es)</b> | 2.1<br>  | 2.1<br>  | 2.1<br> |
| <b>Packing group</b>              | -  | -  | -  |

## Section 14. Transport information

|                               |      |  |  |
|-------------------------------|------|--|--|
| <b>Environmental hazards</b>  | Yes. | Yes.   | Yes. The environmentally hazardous substance mark is not required.                                       |
| <b>Additional information</b> | -    | The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Emergency schedules</b> F-D, S-U | The environmentally hazardous substance mark may appear if required by other transportation regulations. |

### Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Hazard identification number** 23  
**Tunnel code** (D)
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Emergency schedules** F-D, S-U
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

**Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

## Section 16. Other information

### History

- Date of printing** : 27.12.2021
- Date of issue/Date of revision** : 27.12.2021
- Date of previous issue** : 17.12.2021
- Version** : 1.01

## Section 16. Other information

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

**References** : Not available.

✔ Indicates information that has changed from previously issued version.

### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.