

JOTUN Silikat Murfiller

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|--------------------------------------|---------------------------|
| Product name | : JOTUN Silikat Murfiller |
| Product code | : 41442 |
| Product description | : Waterborne paint. |
| Product type | : Liquid. |
| Other means of identification | : Not available. |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Consumer use: Apply this product only as specified on the label.

1.3 Details of the supplier of the safety data sheet

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Norway

Tel: + 47 33 45 70 00
Fax: +47 33 45 72 42
E-mail: SDSJotun@jotun.no

1.4 Emergency telephone number

Norwegian National Poison Centre: +47 22 59 13 00

NOBB number : 54419464

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger.

Hazard statements : H318 - Causes serious eye damage.

Precautionary statements

General : P102 - Keep out of reach of children.

Prevention : P280 - Wear eye or face protection.

JOTUN Silikat Murfiller

SECTION 2: Hazards identification

| | |
|---|---|
| Response | : P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. |
| Storage | : Not applicable. |
| Disposal | : Not applicable. |
| Hazardous ingredients | : silicic acid, potassium salt |
| Supplemental label elements | : Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. |
| Special packaging requirements | |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known. |

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|------------------------------|---|----|--|---|---------|
| silica, crystalline - quartz | EC: 238-878-4 CAS: 14808-60-7 | <5 | STOT RE 2, H373 (lungs) (inhalation) | STOT RE 2, H373: C ≥ 5% | [1] [2] |
| silicic acid, potassium salt | REACH #: 01-2119456888-17 EC: 215-199-1 CAS: 1312-76-1 | ≤5 | Skin Irrit. 2, H315 Eye Dam. 1, H318 See Section 16 for the full text of the H statements declared above. | - | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

JOTUN Silikat Murfiller

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

JOTUN Silikat Murfiller

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

See Technical Data Sheet / packaging for further information.

JOTUN Silikat Murfiller

SECTION 7: Handling and storage**7.3 Specific end use(s)****Recommendations** : Not available.**Industrial sector specific solutions** : Not available.**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters**Occupational exposure limits**

| Product/ingredient name | Exposure limit values |
|------------------------------|---|
| silica, crystalline - quartz | FOR-2011-12-06-1358 (Norway, 6/2021). Carcinogen. Notes: binding limit value TWA: 0.05 mg/m ³ 8 hours. Form: Respirable dust |

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|------------------------------|------|----------------------|------------------------|--------------------|----------|
| silicic acid, potassium salt | DNEL | Long term Oral | 0.74 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.74 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 1.38 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 1.49 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 5.61 mg/m ³ | Workers | Systemic |

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

JOTUN Silikat Murfiller

SECTION 8: Exposure controls/personal protection

Eye/face protection : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber (> 0.4 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm), fluor rubber (> 0.35 mm), Viton® (> 0.7 mm), PE

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

Environmental exposure controls : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : White.
Odour : Characteristic.
Odour threshold : Not applicable.
Melting point/freezing point : 0
Initial boiling point and boiling range : Not available.
Flammability : Not applicable.

JOTUN Silikat Murfiller

SECTION 9: Physical and chemical properties

| | |
|--|---|
| Lower and upper explosion limit | : Not applicable. |
| Flash point | : Closed cup: Not applicable. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| pH | : 11 |
| Viscosity | : Kinematic (40°C): >20.5 mm ² /s |
| Solubility in water | : cold water Easily soluble hot water Easily soluble |
| Partition coefficient: n-octanol/ water | : Not available. |
| Vapour pressure | : Not available. |
| Evaporation rate | : Not available. |
| Density | : 1.67 g/cm ³ |
| Vapour density | : Not available. |
| Explosive properties | : Not available. |
| Oxidising properties | : Not available. |
| Particle characteristics | |
| Median particle size | : Not applicable. |

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

| | |
|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : Stable under recommended storage and handling conditions (see Section 7). |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| 10.6 Hazardous decomposition products | : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. |

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Acute toxicity estimates

N/A

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|------------------------------|----------------------|------------------------------|-------|----------|-------------|
| silicic acid, potassium salt | Eyes - Irritant | Mammal - species unspecified | - | - | - |
| | Skin - Mild irritant | Mammal - species unspecified | - | - | - |

Sensitisation

JOTUN Silikat Murfiller

SECTION 11: Toxicological information

Based on available data, the classification criteria are not met.

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|------------------------------|------------|-------------------|---------------|
| silica, crystalline - quartz | Category 2 | inhalation | lungs |

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

Conclusion/Summary : No known significant effects or critical hazards.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

JOTUN Silikat Murfiller

SECTION 12: Ecological information

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | Waste paint and varnish containing organic solvents or other dangerous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--|
| CEPE Guidelines | 15 01 10* packaging containing residues of or contaminated by hazardous substances |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| | | | | |

JOTUN Silikat Murfiller

SECTION 14: Transport information

| | | | | |
|-----------------------------------|-----|-----|-----|-----|
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

JOTUN Silikat Murfiller

SECTION 15: Regulatory information

| Product/ingredient name | List name | Name on list | Classification | Notes |
|------------------------------|-------------------------------------|--|----------------|-------|
| silica, crystalline - quartz | Norway Occupational Exposure Limits | krystallinsk silika (SiO ₂), α-kvarts respirabelt støv | Carc. K | - |

Norway

Product registration number : 625321

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : Not applicable.

SECTION 16: Other information

✓ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|------------------|--------------------|
| Eye Dam. 1, H318 | Calculation method |

Full text of abbreviated H statements

| | |
|------|--|
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Full text of classifications [CLP/GHS]

| | |
|---------------|---|
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |

Date of printing : 24.03.2023

Date of issue/ Date of revision : 24.03.2023

JOTUN Silikat Murfiller

SECTION 16: Other information

Date of previous issue : 23.03.2023

Version : 1.01

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.