



## Jotun Thinner No. 31S

Section 1. Identification		
Product name	: Jotun Thinner No. 31S	
Product code	: 4258	
Product description	: Thinner.	
Product type	: Liquid.	
Other means of identification	: Not available.	
Supplier's details	: Jotun UAE Ltd. L.L.C. P.O.Box 3671, Dubai, U.A.E. Tel: 009714 3395000 Fax:009714 3380666	
	Jotun Abu Dhabi L.L.C. P.O.box-3714 Abu Dhabi U.A.E. Tel: 00971 2 5510300 Fax:00971 2 5510232	
	SDSJotun@jotun.com	
Emergency telephone number	: SHE Dept. Jotun AS, Norway +47 33 45 70 00	

### Section 2. Hazards identification

Classification of the substance or mixture	<ul> <li>FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3</li> <li>LONG TERM (CHRONIC) AQUATIC HAZARD, Category 2</li> </ul>
<u>GHS label elements</u> Hazard pictograms	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Signal word	: Warning.
Hazard statements	<ul> <li>H226 - Flammable liquid and vapour.</li> <li>H335 - May cause respiratory irritation.</li> <li>H336 - May cause drowsiness or dizziness.</li> <li>H411 - Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
General	: P102 - Keep out of reach of children.
Prevention	<ul> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P273 - Avoid release to the environment.</li> <li>P261 - Avoid breathing vapour.</li> </ul>
Date of issue/Date of revision	: 05.01.2021 Date of previous issue : No previous validation Version : 1 1/10

### Section 2. Hazards identification

Response	<ul> <li>P391 - Collect spillage.</li> <li>P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.</li> </ul>
Storage	: P405 - Store locked up. P403 - Store in a well-ventilated place. P235 - Keep cool.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Other means of identification	: Not available.

#### **CAS number/other identifiers**

CAS number	: Not available.		
EC number	: Not available.		
Product code	: 4258		
Ingredient name		%	CAS number
hvdrocarbons, C9, aron	natics	100	64742-95-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Section 4. First aid measures

Most important symptoms/effects, acute and delayed			
Potential acute health effects			
Eye contact	:	No known significant effects or critical hazards.	
Inhalation	:	May cause drowsiness or dizziness. May cause respiratory irritation.	
Skin contact	1	No known significant effects or critical hazards.	
Ingestion	1	No known significant effects or critical hazards.	
Over-exposure signs/symptoms			
Eye contact	1	No specific data.	
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness	
Skin contact	:	No specific data.	
Ingestion	1	No specific data.	
Indication of immediate me Notes to physician		<u>I attention and special treatment needed, if necessary</u> Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
Specific treatments	:	No specific treatment.	
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person	

providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date of revision

# Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	<ul> <li>No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.</li> </ul>	
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	
Methods and material for cor	ntainment and cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	

# Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials
Date of issue/Date of revision		: 05.01.2021 Date of previous issue : No previous validation Version : 1 4/10

### Section 7. Handling and storage

before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

None.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>Ires</u>

Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. Wear suitable gloves tested to EN374. Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

Date of issue/Date of revision

### Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Clear.
Odour	:	Characteristic.
Odour threshold	:	Not applicable.
рН	:	Not applicable.
Melting point	:	Not applicable.
Boiling point	:	Lowest known value: 135 to 210°C (275 to 410°F)(hydrocarbons, C9, aromatics).
Flash point	:	Closed cup: 40°C (104°F)
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not applicable.
Lower and upper explosive (flammable) limits	:	1.4 - 7.6%
Vapour pressure	:	Not available.
Vapour density	:	Not available.
Density	:	0.86 g/cm <sup>3</sup>
Solubility	:	Insoluble in the following materials: cold water and hot water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	1	Lowest known value: 280 to 470°C (536 to 878°F) (hydrocarbons, C9, aromatics).
Decomposition temperature	1	Not available.
Viscosity	:	Kinematic (40°C): >0.205 cm²/s (>20.5 mm²/s)

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Not available.

#### Irritation/Corrosion

Not available.

#### **Sensitisation**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### Reproductive toxicity

### Section 11. Toxicological information

Not available.

**Teratogenicity** 

Not available.

#### Specific target organ toxicity (single exposure)

Name	 Route of exposure	Target organs
hydrocarbons, C9, aromatics	Not applicable. Not applicable.	Narcotic effects Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Name	Result
hydrocarbons, C9, aromatics	ASPIRATION HAZARD - Category 1

# Information on likely routes : Not available. of exposure

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.

Date of issue/Date of revision

### Section 11. Toxicological information

Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

Not available.

### Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
hydrocarbons, C9, aromatics	Acute EC50 <10 mg/l	Daphnia	48 hours
	Acute IC50 <10 mg/l	Algae	72 hours
	Acute LC50 <10 mg/l	Fish	96 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C9, aromatics	-	-	Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
hydrocarbons, C9, aromatics	-	10 to 2500	high

Section 13. Disposal considerations		
Other adverse effects	: No known significant effects or critical hazards.	
Soil/water partition coefficient (Koc)	: Not available.	
<u>Mobility in soil</u>		

: The generation of waste should be avoided or minimised wherever possible. **Disposal methods** Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	ADR/RID	IMDG	IATA	
UN number	UN1268	UN1268	UN1268	
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S. (hydrocarbons, C9, aromatics)	PETROLEUM DISTILLATES, N.O.S. (hydrocarbons, C9, aromatics). Marine pollutant (hydrocarbons, C9, aromatics)	PETROLEUM DISTILLATES, N.O.S. (hydrocarbons, C9, aromatics)	
Transport hazard class(es)		3	3	
Packing group	111	111	III	
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.	
Additional information	-	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency schedules</u> F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.	

Additional information		
ADR/RID	:	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Hazard identification number 30 Tunnel code (D/E)
IMDG	:	The marine pollutant mark is not required when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg. <b>Emergency schedules</b> F-E, S-E
ΙΑΤΑ	:	The environmentally hazardous substance mark may appear if required by other transportation regulations.
Special precautions for user		<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according	:	Not available.

# the IBC Code

# Section 15. Regulatory information

Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).
International regulations		

### International regulations

to Annex II of Marpol and

Chemical Weapon Convention List Schedules I, II & III Chemicals	
N1.4 P.4.1	

Not listed.

### Montreal Protocol (Annexes A, B, C, E)

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

9/10

### Section 15. Regulatory information

Not listed.

### Section 16. Other information

<u>History</u>	
Date of printing	: 05.01.2021
Date of issue/Date of revision	: 05.01.2021
Date of previous issue	: No previous validation
Version	: 1
Version       : 1         Key to abbreviations       : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution Fr 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution UN = United Nations	
References	: Not available.

Indicates information that has changed from previously issued version.

#### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.