SAFETY DATA SHEE



Safeguard FRC S/PE Comp B

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Safeguard FRC S/PE Comp B

Index number : 612-108-00-0 **EC** number : 213-048-4 **CAS** number : 919-30-2 **Product code** 44662 **Product description** : Hardener. **Product type** : Liquid.

Other means of identification

: 1-Propanamine, 3-(triethoxysilyl)-; aminopropyltriethoxysilane; 3-(Triethoxysilyl) propylamine; gamma-Aminopropyltriethoxysilane; 1-Propanamine, 3-triethoxysilyl-; y-Aminopropyltriethoxysilane; Aminoalkylalkoxysilane [alkyl (C1-3), alkoxy (C1-2)]; 1-Propylamine, 3-(triethoxysilyl)-; 3-(Triethoxysilyl)-1-propanamine; UC-A 1100;

NUCA 1100

Chemical formula : C9-H23-N-O3-Si

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use Use in coatings - Professional use

1.3 Details of the supplier of the safety data sheet

Jotun A/S P.O.Box 2021 3202 Sandefjord Norway

Tel: +47 33 45 70 00 Fax: +47 33 45 72 42

E-mail: SDSJotun@jotun.no

National contact

Jotun Paints Europe (Ltd). Unit K7, Marina Commercial Park Centre Park Road Cork

Ireland

Tel: +353 214 965955 Fax: +353 214 965992

SDSJotun@jotun.com

1.4 Emergency telephone number

Poisons Information Centre of Ireland: +353 1 809 3000 (8am-10pm, 7 days a week)

Date of issue/Date of revision : 04.07.2023 : 27.03.2023 Version: 2 1/13 Date of previous issue

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mono-constituent substance

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms





Signal word : Danger.

Hazard statements : H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

Precautionary statements

Response

General : Not applicable.

Prevention : \$\overline{\pi}280\$ - Wear protective gloves: 1 - 4 hours (breakthrough time): butyl rubber (> 0.4)

mm)< 1 hour (breakthrough time): PVC (> 0.5 mm). Wear protective clothing. Wear

eve or face protection.

P261 - Avoid breathing vapour.

P270 - Do not eat, drink or smoke when using this product.

: P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor.

P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER

or doctor.

P363 - Wash contaminated clothing before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazardous ingredients

Supplemental label

elements

: 3-aminopropyltriethoxysilane

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 2/13

SECTION 2: Hazards identification

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tankila wasanina afalana

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

PBT	Р	В	Т	vPvB	vP	vB
No	N/A	No	No	No	N/A	No

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.1 Substances : Mono-constituent substance

Product/ingredient name	Identifiers	%	I Classification	Specific Conc. Limits, M-factors and ATEs	Туре
3-aminopropyltriethoxysilane	EC: 213-048-4 CAS: 919-30-2 Index: 612-108-00-0	100	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1780 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Type

[1] Constituent

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 3/13

SECTION 4: First aid measures

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Recommended: alcohol-resistant foam, CO2, powders, water spray.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the

substance or mixture **Hazardous combustion**

products

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 4/13

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 5/13

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
3-aminopropyltriethoxysilane	DNEL	Short term Dermal	8.3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	59 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	8.3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	59 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Inhalation	17.4 mg/m³	General population [Consumers]	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	17.4 mg/m³		Systemic
	DNEL	Long term Oral	1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.5 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	14 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
3-aminopropyltriethoxysilane	Marine Sewage Treatment Plant Fresh water sediment Marine water sediment	0.33 mg/l 0.033 mg/l 13 mg/l 1.2 mg/kg dwt 0.12 mg/kg dwt 0.05 mg/kg dwt	- - - -

8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 6/13

SECTION 8: Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves

Wear suitable gloves tested to ISO 374-1:2016.

For prolonged or repeated handling, use the following type of gloves:

May be used, gloves(breakthrough time) 4 - 8 hours: butyl rubber (> 0.4 mm) Not recommended, gloves(breakthrough time) < 1 hour: PVC (> 0.5 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

Environmental exposure controls

: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Colourless.
Odour : Characteristic.
Odour threshold : Not applicable.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 7/13

SECTION 9: Physical and chemical properties

Melting point/freezing point : 0

Initial boiling point and

boiling range

: >68°C (>154.4°F)

Flammability : Not applicable. : 0.8 - 4.5% Lower and upper explosion

limit

Flash point Closed cup: 103°C [DIN 51758]

Auto-ignition temperature : Not applicable. : Not available. **Decomposition temperature**

pН

Dynamic (room temperature): 2 mPa·s [DIN 53015] **Viscosity**

Kinematic (room temperature): 2 mm²/s

Kinematic (40°C): >20.5 mm²/s

Solubility in water : cold water Easily soluble

hot water Easily soluble

water

Partition coefficient: n-octanol/: The product is more soluble in octanol; log(octanol/water) = 1.7

Vapour pressure : <0.01 kPa (<0.08 mm Hg) (at 20°C) **Evaporation rate** : Not available.

: 0.95 g/cm³ @ 20 °C **Density**

: Not available. Vapour density Not available. **Explosive properties** : Not available. Oxidising properties

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

Molecular weight : 221.42 g/mole

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur.

hazardous reactions

10.4 Conditions to avoid When exposed to high temperatures may produce hazardous decomposition products.

: Keep away from the following materials to prevent strong exothermic reactions: 10.5 Incompatible materials

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous : Decomposition products may include the following materials: carbon monoxide,

decomposition products carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-aminopropyltriethoxysilane	LD50 Oral	Rat	1780 mg/kg	-

Acute toxicity estimates

8/13 Date of issue/Date of revision : 04.07.2023 : 27.03.2023 Version Date of previous issue

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)	
3 -aminopropyltriethoxysilane	1780	N/A	N/A	N/A	N/A	

Irritation/Corrosion

Based on available data, the classification criteria are not met.

Sensitisation

Based on available data, the classification criteria are not met.

Mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary: This product shows a low bioaccumulation potential.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminopropyltriethoxysilane	1.7	3.4	low

12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 9/13

Safeguard FRC S/PE Comp B	
SECTION 12: Ecological information	

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	Р	В	Т	vPvB	νP	vB
3-aminopropyltriethoxysilane	No	N/A	No	No	No	N/A	No

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

Disposal considerations

Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging		European waste catalogue (EWC)
CEPE Guidelines	15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 10/13

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN2735	UN2735	UN2735	UN2735
14.2 UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. (3-aminopropyltriethoxysilane)	Polyamines, liquid, corrosive, n.o.s. (3-aminopropyltriethoxysilane)	Polyamines, liquid, corrosive, n.o.s. (3-aminopropyltriethoxysilane)	Polyamines, liquid, corrosive, n.o.s. (3-aminopropyltriethoxysilane)
14.3 Transport hazard class(es)	8	8	8	8
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

ADR/RID : Hazard identification number 80

Tunnel code (E)

IMDG : **Emergency schedules** F-A, S-B

Segregation Group: 18 - Alkalis

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO

instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Other EU regulations

VOC

: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use

Mixture

: Not available.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version :2 11/13

SECTION 15: Regulatory information

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's

own assessment of workplace risks, as required by other health and safety

legislation. The provisions of the national health and safety at work regulations apply

to the use of this product at work.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: Complete.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 12/13

SECTION 16: Other information

Classification	Justification
K cute Tox. 4, H302	Expert judgment
Skin Corr. 1B, H314	Expert judgment
Eye Dam. 1, H318	SKIN CORROSION/IRRITATION
Skin Sens. 1B, H317	Expert judgment

Full text of abbreviated H statements

⊮ 302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Full text of classifications [CLP/GHS]

Acute Tox. 4 ACUTE TOXICITY - Category 4

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B

Skin Sens. 1B SKIN SENSITISATION - Category 1B

Date of printing : 04.07.2023 Date of issue/ Date of : 04.07.2023

revision

Date of previous issue : 27.03.2023

Version : 2

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Date of issue/Date of revision : 04.07.2023 Date of previous issue : 27.03.2023 Version : 2 13/13