# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : Jotafloor SF Pro Primer(TR) Comp B

Product code : 45765
Product description : Hardener.
Product type : Liquid.
Other means of : Not available.

identification

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Professional use

### 1.3 Details of the supplier of the safety data sheet

Jotun Boya Sanayi ve Ticaret A.Ş.

Balabandere Caddesi, Hilpark Suites Sitesi No: 10, İstinye 34460 Sarıyer, İstanbul

Tel. +90 212 279 7878 SDSJotun@jotun.com

Başvurulacak Kişi: Deren Ercan deren.metiner@jotun.com

Original preparation date : 24.07.2023

### 1.4 Emergency telephone number

### **National Poison Information Center**

- +90 224 442 82 93 Uludağ Üniversitesi Zehir Danısma Merkezi (www.uludag.edu.tr/uludag/zehir.html)
- a. ACİL DURUM TELEFONU: Zehirlenme durumlarında gerektiğinde ulusal zehir merkezinin (UZEM) 114 nolu telefonunu arayınız.
- b. ACİL İLK YARDIM MERKEZİ:112

c. İTFAİYE:110

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

## Classification according to regulation SEA: RG.-10/12/2020-31330

Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317

The product is classified as hazardous according to Regulation SEA: RG.-10/12/2020-31330.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## 2.2 Label elements

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 1/14

## **SECTION 2: Hazards identification**

**Hazard pictograms** 





Signal word : Danger.

Hazard statements : H302 + H332 - Harmful if swallowed or if inhaled.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

**Precautionary statements** 

General : Not applicable.

**Prevention**: P280 - Wear protective gloves, protective clothing and eye or face protection.

P261 - Avoid breathing vapour.

P270 - Do not eat, drink or smoke when using this product.

Response : P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER

or doctor.

P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

**Hazardous ingredients**: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

benzyl alcohol

Supplemental label

elements

: Not applicable.

: Not applicable.

Annex 17 - Restrictions on the manufacture, placing on the market and use of

certain dangerous

substances, mixtures and

articles

**Special packaging requirements** 

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger: Not applicable.

2.3 Other hazards

Product meets the criteria

for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: None known.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 2/14

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	SEA: RG10/12/2020-31330	Type
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥50 - ≤75	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	[1]
benzyl alcohol	EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

### 4.1 Description of first aid measures

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

### Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

# Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 3/14

## SECTION 4: First aid measures

### 4.2 Most important symptoms and effects, both acute and delayed

### Potential acute health effects

**Eve contact** : Causes serious eye damage.

Inhalation : Harmful if inhaled.

**Skin contact** : Causes severe burns. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed.

## Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> pain watering redness

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

## 4.3 Indication of any immediate medical attention and special treatment needed

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician

The exposed person may need to be kept under medical surveillance for 48 hours.

: No specific treatment. **Specific treatments** 

# SECTION 5: Firefighting measures

## 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

**Hazardous thermal** decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides

5.3 Advice for firefighters

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Date of revision : 29.11.2023 : 24.07.2023 Version : 1.01 Original preparation date

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **6.2 Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

# 6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

See Technical Data Sheet / packaging for further information.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 5/14

### Conforms to regulation No. 30105, Turkey KKDIK, Annex 2

Jotafloor SF Pro Primer(TR) Comp B

# SECTION 7: Handling and storage

### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limits

No exposure limit value known.

### **Biological exposure indices**

No exposure indices known.

# Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
<b>3</b> -aminomethyl-	DNEL	Long term Oral	0.526 mg/	General	Systemic
3,5,5-trimethylcyclohexylamine		_	kg bw/day	population [Consumers]	
	DNEL	Short term Inhalation	0.073 mg/ m³	Workers	Local
	DNEL	Long term Inhalation	0.073 mg/ m³	Workers	Local
	DNEL	Long term Oral	0.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.3 mg/kg bw/day	General population	Systemic
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5.4 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	22 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m³	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m <sup>3</sup>	Workers	Systemic

### **PNECs**

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 6/14

# **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Compartment Detail	Value	Method Detail
3-aminomethyl-	Fresh water	0.06 mg/l	-
3,5,5-trimethylcyclohexylamine			
	Marine	0.006 mg/l	-
	Sewage Treatment	3.18 mg/l	-
	Plant		
	Fresh water sediment	5.784 mg/kg dwt	-
	Marine water sediment	0.578 mg/kg dwt	-
	Soil	1.121 mg/kg dwt	-
benzyl alcohol	Fresh water	1 mg/l	-
	Marine	0.1 mg/l	-
	Sewage Treatment	39 mg/l	-
	Plant		
	Fresh water sediment	5.27 mg/kg dwt	-
	Marine water sediment	0.527 mg/kg dwt	-
	Soil	0.456 mg/kg dwt	-

#### 8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

# Skin protection Hand protection

: There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: fluor rubber (> 0.35 mm), Viton® (> 0.7 mm), 4H/Silver Shield® (> 0.07 mm), butyl rubber (> 0.4 mm) May be used, gloves(breakthrough time) 4 - 8 hours: nitrile rubber (> 0.75 mm), PVC (> 0.5 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 7/14

# SECTION 8: Exposure controls/personal protection

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour : Clear.

**Odour** : Characteristic. **Odour threshold** : Not applicable. Melting point/freezing point : Not applicable.

Initial boiling point and

boiling range

: Lowest known value: 205.3°C (401.5°F) (benzyl alcohol). Weighted average:

233.86°C (452.9°F)

Flammability (solid, gas) Upper/lower flammability or

explosive limits

: Not applicable. : 1.2 - 13%

: Closed cup: 100°C (212°F) Flash point

**Auto-ignition temperature** : Not applicable. **Decomposition temperature** : Not available. pН : Not applicable.

**Viscosity** Kinematic (40°C): >20.5 mm<sup>2</sup>/s

Solubility(ies)

Media	Result
cold water	Not soluble
hot water	Not soluble

Partition coefficient: n-octanol/ : Not available.

water

Vapour pressure

Fighest known value: 0.007 kPa (0.05 mm Hg) (at 20°C) (benzyl alcohol).

Weighted average: 0.004 kPa (0.03 mm Hg) (at 20°C) 0.007 (benzyl alcohol) compared with butyl acetate

: 1.122 g/cm<sup>3</sup> **Density** 

: Highest known value: 3.7 (Air = 1) (benzyl alcohol). Vapour density

**Explosive properties** : Not available. Not available. **Oxidising properties** 

**Particle characteristics** 

Median particle size : Not applicable.

### 9.2 Other information

Date of revision : 29.11.2023 : 24.07.2023 Version : 1.01 8/14 Original preparation date

## Conforms to regulation No. 30105, Turkey KKDIK, Annex 2

Jotafloor SF Pro Primer(TR) Comp B

# **SECTION 9: Physical and chemical properties**

No additional information.

# SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of** : Under normal conditions of storage and use, hazardous reactions will not occur.

hazardous reactions

10.4 Conditions to avoid : No specific data.10.5 Incompatible materials : No specific data.

**10.6 Hazardous** : Under normal conditions of storage and use, hazardous decomposition products

**decomposition products** should not be produced.

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	LD50 Oral	Rat	1030 mg/kg	-
benzyl alcohol	LD50 Oral	Rat	1230 mg/kg	-

**Conclusion/Summary**: Not available.

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Jotafloor SF Pro Primer(TR) Comp B	1101.7	N/A	N/A	N/A	3.8
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	N/A	N/A	N/A	N/A
benzyl alcohol	1230	N/A	N/A	N/A	1.5

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Eyes - Mild irritant	Mammal - species unspecified	-	-	-

**Conclusion/Summary**: Not available.

### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl- 3,5,5-trimethylcyclohexylamine		Mammal - species unspecified	Sensitising

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

**Reproductive toxicity** 

**Conclusion/Summary**: Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 9/14

# **SECTION 11: Toxicological information**

## Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

Information on likely routes

: Not available.

of exposure

Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : Harmful if inhaled.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** 

effects

: Not available.

Potential delayed effects

: Not available.

**Long term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

## Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 10/14

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	į	Daphnia - Daphnia magna	48 hours
, , , , , , , , , , , , , , , , , , ,	Acute IC50 37 mg/l	Algae	72 hours

**Conclusion/Summary**: No known significant effects or critical hazards.

### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	-	-	Not readily
benzyl alcohol	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	0.99	-	low
benzyl alcohol	0.87	<100	low

### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## **12.6 Other adverse effects**: No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

The classification of the product may meet the criteria for a hazardous waste.

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 11/14

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3066	UN3066	UN3066	UN3066
14.2 UN proper shipping name	Paint related material	Paint related material	Paint related material	Paint related material
14.3 Transport hazard class(es)	8	8	8	8
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

**Additional information** 

ADR/RID : <u>Hazard identification number</u> 80

**Special provisions** 163

Tunnel code (E)
: Emergency schedules F-A, S-B

14.6 Special precautions for

ıser

**IMDG** 

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Turkey Regulation No. 30105, KKDIK

**Annex 14 - List of substances subject to authorization** 

Annex 14

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex 17 - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Ozone depleting substances

Not listed.

## Regulation on the prevention of major industrial accidents and reduction of their effects

This product is not controlled under the Regulation on the prevention of major industrial accidents and reduction of their effects.

#### **EU regulations**

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 12/14

# SECTION 15: Regulatory information

### **Annex XIV**

None of the components are listed.

### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

This product contains substances for which Chemical Safety Assessments are still 15.2 Chemical safety

assessment required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** 

: ATE = Acute Toxicity Estimate

acronyms EUH statement = SEA-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to regulation SEA: RG.-10/12/2020-31330

Classification	Justification
Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H332	Calculation method
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

Date of revision : 29.11.2023 : 24.07.2023 Original preparation date Version: 1.01 13/14

### Conforms to regulation No. 30105, Turkey KKDIK, Annex 2

Jotafloor SF Pro Primer(TR) Comp B

## **SECTION 16: Other information**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

### Full text of classifications [SEA/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of printing : 29.11.2023 Date of issue/ Date of : 29.11.2023

revision

**Version** 

Date of previous issue : 24.07.2023

: 1.01

Contact information of certified author
Responsible Person: Deren Ercan

Mail Address: deren.metiner@jotun.com Certificate No: LONCA KDU81/2021.26 Certificate Expiration Date: 14.10.2026

### **Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of revision : 29.11.2023 Original preparation date : 24.07.2023 Version : 1.01 14/14