

## Jotatemp 1000 Comp B

## Section 1. Identification

**Product name** : Jotatemp 1000 Comp B

**Product code** : 48343

Other means of

: Not available.

identification

: Hardener.

**Product description Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Use in coatings - Industrial use Use in coatings - Professional use

**Supplier Proline Protective Coatings** : Jotun Australia Pty. Ltd. 59 Calarco Drive, 176 Ossie James Drive,

Derrimut, VIC 3026, Hamilton Airport, Australia Hamilton 3282

New Zealand

Phone: + 61 39314 0722

E-mail: SDSJotun@jotun.com Email: info@prolinepc.nz Contact: +(64) 0508568867

Emergency telephone number (with hours of operation) : Medical Emergencies 24 hours:

Poisons Information Centre (New Zealand) 0800 764

766

e-mail address of person responsible for this SDS : sdsjotun@jotun.com

# Section 2. Hazards identification

**HSNO Classification** 

: FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 99.1%

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

### **GHS label elements**

Signal word : Danger.

**Hazard statements** : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

**Precautionary statements** 

**Prevention** : P280 - Wear protective gloves. Wear eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Version Date of issue/Date of revision: : 1.05 23.10.2023 Jotatemp 1000 Comp B Page: 2/11

# Section 2. Hazards identification

: P362 + P364 - Take off contaminated clothing and wash it before reuse. Response

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

: Not applicable. **Storage** 

**Disposal** P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

**Symbol** 





Other hazards which do not : None known. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of : Not available. identification

| Ingredient name              | % (w/w) | CAS number |
|------------------------------|---------|------------|
| titanium tetrabutanolate     | ≥90     | 5593-70-4  |
| titanium tetraisopropanolate | ≤3      | 546-68-9   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision: Version : 1.05 23.10.2023 Jotatemp 1000 Comp B Page: 3/11

## Section 4. First aid measures

Skin contact

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Inhalation : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

: Causes skin irritation. Skin contact

: Causes serious eye damage. Eye contact

#### Over-exposure signs/symptoms

Inhalation : No specific data.

Ingestion : Adverse symptoms may include the following:

stomach pains

Skin : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Eyes** : Adverse symptoms may include the following:

> pain watering redness

#### Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments

: No specific treatment.

Notes to physician

Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

## Section 5. Firefighting measures

#### **Extinguishing media**

**Suitable** : Use dry chemical, CO2, water spray (fog) or foam.

: Do not use water jet. Not suitable

Specific hazards arising from the chemical

: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

Hazchem code •3Y

Version Date of issue/Date of revision: : 1.05 23.10.2023 Jotatemp 1000 Comp B Page: 4/11

## Section 5. Firefighting measures

Special precautions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Jotatemp 1000 Comp B Page: 5/11

## Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

None.

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection

Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### **Skin protection Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be

Jotatemp 1000 Comp B Page: 6/11

# Section 8. Exposure controls/personal protection

applied once exposure has occurred.

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: butyl rubber (> 0.4 mm)

**Body protection** Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity,

wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use a

respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use

of roller or brush, consider use of charcoalfilter.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

**Physical state** : Liquid. Colourless. Colour **Odour** : Characteristic. : Not available. **Odour threshold** Not applicable.

Melting point/freezing point May start to solidify at the following temperature: 20°C (68°F) This is based on data

for the following ingredient: titanium tetraisopropanolate.

Boiling point, initial boiling

point, and boiling range

Lowest known value: 220°C (428°F) (titanium tetraisopropanolate).

Flash point : Closed cup: 40°C (104°F)

: Not available. **Evaporation rate Flammability** : Not available. Lower and upper explosion Not applicable.

limit/flammability limit

Vapour pressure

: Highest known value: 6 kPa (45.1 mm Hg) (at 20°C) (titanium tetraisopropanolate).

**Relative vapour density** : Not available. : Not available. Relative density

: 0.996 g/cm³ @ 20 °C **Density** 

Insoluble in the following materials: cold water and hot water. Solubility

Solubility in water Not available. Not available. Partition coefficient: n-

octanol/water

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available.

**Viscosity** : Kinematic (40°C (104°F)): >20.5 mm<sup>2</sup>/s (>20.5 cSt)

Flow time (ISO 2431) : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

Jotatemp 1000 Comp B Page: 7/11

## Section 10. Stability and reactivity

**Chemical stability**: The product is stable.

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **Section 11. Toxicological information**

### Information on likely routes of exposure

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

**Eye contact** : Causes serious eye damage.

### Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

**Ingestion**: Adverse symptoms may include the following:

stomach pains

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Acute toxicity**

| Product/ingredient name  | Result    | Species | Dose       | Exposure |
|--------------------------|-----------|---------|------------|----------|
| titanium tetrabutanolate | LD50 Oral | Rat     | 3122 mg/kg | -        |

#### **Irritation/Corrosion**

| Product/ingredient name      | Result                   | Species                            | Score | Exposure                   | Observation |
|------------------------------|--------------------------|------------------------------------|-------|----------------------------|-------------|
| titanium tetrabutanolate     | Eyes - Irritant          | Mammal -<br>species<br>unspecified | -     | -                          | -           |
|                              | Skin - Mild irritant     | Mammal -<br>species<br>unspecified | -     | -                          | -           |
| titanium tetraisopropanolate | Eyes - Mild irritant     | Mammal -<br>species<br>unspecified | -     | -                          | -           |
|                              | Eyes - Moderate irritant | Rabbit                             | -     | 24 hours 20<br>milligrams  | -           |
|                              | Skin - Mild irritant     | Rabbit                             | -     | 24 hours 500<br>milligrams | -           |

### **Sensitisation**

Jotatemp 1000 Comp B Page: 8/11

# **Section 11. Toxicological information**

Not available.

### Potential chronic health effects

General : No known significant effects or critical hazards.Inhalation : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

Skin contactNo known significant effects or critical hazards.Eye contactNo known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.Teratogenicity : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects**: No known significant effects or critical hazards.

Chronic toxicity

Not available.

**Carcinogenicity** 

Not available.

**Mutagenicity** 

Not available.

**Teratogenicity** 

Not available.

**Reproductive toxicity** 

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

| Product/ingredient name  | ( 3  | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | ( - 1 / | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|--------------------------|------|-------------------|--------------------------------|---------|--|
| titanium tetrabutanolate | 3122 | N/A               | N/A                            | N/A     | N/A  |

# **Section 12. Ecological information**

**Ecotoxicity** : No known significant effects or critical hazards.

Aquatic and terrestrial toxicity

Not available.

### Persistence/degradability

Not available.

Jotatemp 1000 Comp B Page: 9/11

# **Section 12. Ecological information**

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers

## **Section 14. Transport information**

|                            | New Zealand   | IMDG  | IATA  |
|----------------------------|---|---|---|
| UN number                  | UN1993  | UN1993  | UN1993  |
| UN proper shipping name    | Flammable liquid, n.o.s.<br>(titanium tetrabutanolate,<br>butan-1-ol) | Flammable liquid, n.o.s.<br>(titanium tetrabutanolate,<br>butan-1-ol) | Flammable liquid, n.o.s.<br>(titanium tetrabutanolate,<br>butan-1-ol) |
| Transport hazard class(es) | 3   | 3   | 3   |
| Packing group              | III   | III   | III   |
| Environmental hazards      | No.   | No.   | No.   |

#### **Additional information**

**New Zealand** : Hazchem code •3Y

**IMDG** : Emergency schedules F-E, S-E ADR/RID Tunnel restriction code: (D/E) Hazard identification number: 30

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Jotatemp 1000 Comp B Page: 10/11

## Section 14. Transport information

Transport in bulk according : Not available.

to IMO instruments

## Section 15. Regulatory information

HSNO Group Standard : HSR002663 Surface Coatings and Colourants (Flammable, Corrosive) Group

Standard 2020

**HSNO Classification** : FLAMMABLE LIQUIDS - Category 3

SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1

#### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

### Section 16. Other information

**History** 

Date of printing : 23.10.2023

Date of issue/Date of : 23.10.2023

revision

Date of previous issue : 20.07.2023

Version : 1.05

**Key to abbreviations** : ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

SGG = Segregation Group UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

#### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their

Jotatemp 1000 Comp B Page: 11/11

# **Section 16. Other information**

needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.