

# HELAIAN DATA KESELAMATAN SAFETY DATA SHEET



JOTUN Multicolor Solvent-Free YC

## Bahagian 1: Pengenalan bahan kimia dan pembekal

**Pengecam produk** : JOTUN Multicolor Solvent-Free YC

**Cara pengenalpastian yang lain** : Tidak tersedia.

**Kod Produk** : 52462

**Pemerihalan produk** : Bahan pewarna. Cat asas air.

**Jenis Produk** : Cecair.

**Kegunaan relevan yang dikenal pasti bagi zat atau campuran serta kegunaan yang tidak dinasihatkan**

Tidak berkenaan.

**Pengilang** : Jotun Paints (Malaysia) Sdn Bhd, Lot 7 Persiaran Perusahaan, Section 23  
40300 SHAH ALAM, Selangor Darul Ehsan  
Malaysia  
Tel: +603 51235500  
Fax: +603 51235599

Jotun Paints (M) Sdn Bhd, Lot 9143, PN 38500, Kawasan perindustrian Nilai, 71800  
Nilai, Negeri Sembilan  
Malaysia  
Tel: +606 798 7500  
Fax: +606 798 7555  
SDSJotun@jotun.com

**Nombor telefon kecemasan (berserta waktu urusan)** : Tel: +603 51235500 Jotun (Malaysia) Sdn. Bhd.  
Tel: +606 7987500 Jotun Paints(M) Sdn Bhd

## Section 1. Identification of the hazardous chemical and of the supplier

**Product identifier** : JOTUN Multicolor Solvent-Free YC

**Other means of identification** : Not available.

**Product code** : 52462

**Product description** : Colouring material. Waterborne paint.

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

Not applicable.

**Manufacturer** : Jotun Paints (Malaysia) Sdn Bhd, Lot 7 Persiaran Perusahaan, Section 23  
40300 SHAH ALAM, Selangor Darul Ehsan  
Malaysia  
Tel: +603 51235500  
Fax: +603 51235599

Jotun Paints (M) Sdn Bhd, Lot 9143, PN 38500, Kawasan perindustrian Nilai, 71800  
Nilai, Negeri Sembilan  
Malaysia  
Tel: +606 798 7500  
Fax: +606 798 7555  
SDSJotun@jotun.com

**Emergency telephone number** : Tel: +603 51235500 Jotun Paints(M) Sdn. Bhd.  
Tel: +606 7987500 Jotun Paints(M) Sdn Bhd

**Tarikh keluaran** : 22.03.2023  
**Date of issue**

## Section 1. Identification of the hazardous chemical and of the supplier

### Bahagian 2: Pengenalan bahaya

**Klasifikasi bahan atau campuran** : BERBAHAYA KEPADA PERSEKITARAN AKUATIK - BAHAYA KRONIK - Kategori 2

**Unsur label GHS**

**Piktogram bahaya** :



**Kata isyarat** : Tiada kata isyarat.

**Pernyataan bahaya** : H411 - Toksik kepada hidupan akuatik dengan kesan kekal berpanjangan.

**Pernyataan berjaga-jaga**

**Pencegahan** : P273 - Elakkan pelepasan bahan ke persekitaran.

**Respons** : P391 - Pungut kumpul tumpahan.

**Penyimpanan** : Tidak berkenaan.

**Pelupusan** : P501 - Lupuskan kandungan dan bekas mengikut semua peraturan tempatan, serantau, nasional dan antarabangsa.

**Bahaya lain yang tidak menyebabkan ia diklasifikasikan** : Tiada yang diketahui.

## Section 2. Hazards identification

**Classification of the substance or mixture** : HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Category 2

**GHS label elements**

**Hazard pictograms** :



**Signal word** : No signal word.

**Hazard statements** : H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention** : P273 - Avoid release to the environment.

**Response** : P391 - Collect spillage.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : None known.

### Bahagian 3: Komposisi dan maklumat mengenai ramuan bahan kimia berbahaya

**Bahan/Penyediaan** : Campuran  
**Cara mengenalpastian yang lain** : Tidak tersedia.

#### Nombor CAS/pengenal pasti lain

**Nombor CAS** : Tidak berkenaan.  
**Nombor EC** : Campuran.  
**Kod Produk** : 52462

Nama Ramuan	%	Nombor CAS
trizinc bis(orthophosphate)	≤5	7779-90-0
bismuth vanadium tetraoxide	≤5	14059-33-7
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	≤5	147170-44-3
3-iodo-2-propynyl butylcarbamate (IPBC)	≤0.3	55406-53-6
bronopol (INN)	≤0.1	52-51-7
2-octyl-2h-isothiazol-3-one (OIT)	≤0.1	26530-20-1
C(M)IT/MIT (3:1)	≤0.1	55965-84-9

Tidak ada ramuan tambahan, setakat yang diketahui pembekal dan dalam pemekatan yang boleh didapati, diklasifikasikan sebagai berbahaya kepada kesihatan atau persekitaran sehingga perlu dilaporkan dalam seksyen ini.

Had pendedahan pekerjaan, jika tersedia, disenaraikan dalam seksyen 8.

### Section 3. Composition and information of the ingredients of the hazardous chemical

**Substance/mixture** : Mixture  
**Other means of identification** : Not available.

#### CAS number/other identifiers

**CAS number** : Not applicable.  
**EC number** : Mixture.  
**Product code** : 52462

Ingredient name	%	CAS number
trizinc bis(orthophosphate)	≤5	7779-90-0
bismuth vanadium oxide (bivo4)	≤5	14059-33-7
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	≤5	147170-44-3
3-iodo-2-propynyl butylcarbamate (IPBC)	≤0.3	55406-53-6
bronopol	≤0.1	52-51-7
2-octyl-2h-isothiazol-3-one (OIT)	≤0.1	26530-20-1
C(M)IT/MIT (3:1)	≤0.1	55965-84-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Bahagian 4: Langkah-langkah pertolongan cemas

### Perihalan langkah pertolongan cemas yang perlu

- Sentuhan mata** : Segera jirus mata dengan air yang banyak, sekali-sekala kedipkan mata. Periksa jika memakai kanta mata dan keluarkan jika ada. Dapatkan bantuan perubatan jika kerengsaan berlaku.
- Penyedutan** : Pindahkan mangsa ke kawasan berudara segar dan biarkan mangsa dalam keadaan rehat supaya mangsa dapat bernafas dengan selesa. Sekiranya tersedut hasil penguraian ketika kebakaran, gejala mungkin tertangguh. Orang yang mengalami dedahan mungkin perlu diletakkan di bawah pengawasan perubatan selama 48 jam.
- Sentuhan kulit** : Curahkan pada kulit tercemar dengan air yang banyak. Tanggalkan pakaian dan kasut yang tercemar. Dapatkan bantuan perubatan jika gejala-gejala berlaku.
- Pengingesan** : Basuh mulut dengan air. Jika bahan telah ditelan dan orang yang mengalami dedahan sedar, berikan sedikit air untuk minum. Jangan paksa muntahan kecuali diarahkan berbuat demikian oleh kakitangan perubatan.

### Simptom/kesan paling penting, akut dan tertunda

#### Kesan Kesihatan Akut Berpotensi

- Sentuhan mata** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Penyedutan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Sentuhan kulit** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Pengingesan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

#### Gejala-gejala/tanda-tanda lampau terdedah

- Sentuhan mata** : Tiada data spesifik.
- Penyedutan** : Tiada data spesifik.
- Sentuhan kulit** : Tiada data spesifik.
- Pengingesan** : Tiada data spesifik.

### Tanda rawatan perubatan segera dan rawatan khas diperlukan, jika perlu

- Nota kepada doktor** : Sekiranya tersedut hasil penguraian ketika kebakaran, gejala mungkin tertangguh. Orang yang mengalami dedahan mungkin perlu diletakkan di bawah pengawasan perubatan selama 48 jam.
- Rawatan spesifik** : Tiada rawatan spesifik.
- Perlindungan untuk pemberi pertolongan cemas** : Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya.

Lihat Maklumat Toksikologi (Seksyen 11)

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.

## Section 4. First aid measures

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.  
**Specific treatments** : No specific treatment.  
**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

## Bahagian 5: Langkah-langkah pemadaman kebakaran

### Media pemadam kebakaran

- Media pemadam yang sesuai** : Guna agen pemadaman sesuai untuk lingkungan api.  
**Media pemadam yang tidak sesuai** : Tiada yang diketahui.

**Bahaya khusus yang timbul daripada bahan kimia ini** : Ketika kebakaran atau jika dipanaskan, peningkatan tekanan akan berlaku dan bekas boleh pecah. Bahan ini toksik pada hidupan akuatik dengan kesan yang berkekalan. Air pemadaman kebakaran yang tercemar dengan bahan ini mesti dibendung dan dielakkan daripada memasuki jalan air, pembetung atau longkang.

- Hasil penguraian terma yang berbahaya** : Produk penguraian mungkin termasuk bahan berikut:  
karbon dioksida  
karbon monoksida  
nitrogen oksida  
oksida fosforus  
oksida logam

**Tindakan perlindungan khas untuk ahli bomba** : Kosongkan kawasan serta-merta dengan mengeluarkan semua orang daripada kawasan sekeliling jika kebakaran berlaku. Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya.

**Alat perlindungan khas untuk ahli bomba** : Ahli bomba perlulah memakai peralatan perlindungan bersesuaian dan peralatan pernafasan serba lengkap dengan penutup muka penuh dalam operasi mod tekanan positif.

## Section 5. Firefighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.  
**Unsuitable extinguishing media** : None known.

## Section 5. Firefighting measures

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
phosphorus oxides  
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Bahagian 6: Langkah-langkah pelepasan tidak sengaja

### Langkah berjaga-jaga peribadi, peralatan pelindung dan prosedur kecemasan

- Untuk kakitangan bukan kecemasan** : Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya. Kosongkan kawasan persekitaran. Halang kakitangan tidak berkaitan dan tidak dilindungi daripada masuk. Jangan sentuh atau jalan melalui bahan tertumpah. Pakai peralatan perlindungan diri yang sesuai.
- Untuk pasukan tindak balas kecemasan** : Jika pakaian khas diperlukan bagi mengendalikan tumpahan, perhatikan apa jua maklumat dalam Seksyen 8 tentang bahan yang sesuai dan tidak sesuai. Lihat juga maklumat dalam bahagian "Untuk kakitangan bukan kecemasan".
- Peringatan alam sekitar** : Elakkan penyebaran bahan tertumpah dan aliran dan bersentuh dengan tanah, jalan air, longkang dan pemetung. Beritahu pihak berkuasa yang berkaitan jika produk menyebabkan pencemaran persekitaran (pemetung, aliran air, tanah atau udara). Bahan mencemar air. Boleh memudaratkan alam sekitar jika terlepas dalam jumlah yang banyak. Pungut kumpul tumpahan.

### Kaedah dan bahan bagi pembendungan dan pembersihan

- Tumpahan kecil** : Hentikan kebocoran jika tidak berisiko. Alih bekas daripada kawasan tumpahan. Cairkan dengan air dan seka bersih jika terlarut air. Sebagai alternatif, atau jika tidak terlarut air, serap dengan bahan kering yang lengai dan isikan dalam bekas pelupusan bahan buangan yang wajar. Buang melalui kontraktor pelupusan sisa yang berlesen.
- Tumpahan besar** : Hentikan kebocoran jika tidak berisiko. Alih bekas daripada kawasan tumpahan. Pendekatan lepas dari arah angin bertiup jauh dari kamu, bukan ke arah kamu. Cegah kemasukan ke dalam pemetung, aliran air, basemen atau ruang terbatas. Siram tumpahan ke dalam loji perawatan efluen atau teruskan seperti berikut. Bendung dan kumpul tumpahan dengan bahan serap tidak mampu bakar seperti pasir, tanah, vermikulit dan tanah diatom, dan letakkan dalam bekas untuk pembuangan mengikut peraturan tempatan (lihat Seksyen 13). Buang melalui kontraktor pelupusan sisa yang berlesen. Bahan penyerap yang tercemar boleh mendatangkan bahaya yang sama seperti produk tertumpah. Nota: Lihat Seksyen 1 untuk maklumat hubungan kecemasan dan Seksyen 13 untuk pelupusan sisa.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

## Section 6. Accidental release measures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- Methods and material for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Bahagian 7: Pengendalian dan penyimpanan

### Langkah berjaga-jaga bagi mengendalikan dengan selamat

- Langkah perlindungan** : Pakai kelengkapan perlindungan peribadi bersesuaian (Lihat Seksyen 9). Jangan inges. Elakkan tersentuh mata, kulit dan pakaian. Elakkan menyedut wap atau kabus. Elakkan pelepasan bahan ke persekitaran. Simpan di dalam bekas asal atau bekas lain yang diluluskan yang diperbuat daripada bahan yang sesuai, tutup ketat apabila tidak digunakan. Bekas kosong mengandungi sisa produk dan boleh menjadi berbahaya. Jangan guna semula bekas.
- Nasihat tentang aturan kebersihan pekerjaan umum** : Makan, minum dan menghisap rokok harus dilarang dalam kawasan di mana bahan ini dikendalikan, disimpan dan diproses. Para pekerja harus membasuh tangan dan muka sebelum makan, minum dan menghisap rokok. Tanggalkan pakaian yang tercemar dan peralatan perlindungan sebelum masuk tempat makan. Lihat juga Seksyen 8 untuk maklumat tambahan tentang langkah kebersihan.
- Syarat-syarat bagi penyimpanan yang selamat, termasuk apa-apa ketakserasian** : Simpan mengikut peraturan tempatan. Simpan di dalam bekas asal yang terlindung dari pancaran terus cahaya matahari dalam kawasan kering, sejuk dan pengudaraan yang baik, jauh daripada bahan tidak sesuai (lihat Seksyen 10) dan makanan dan minuman. Simpan bekas tertutup rapat dan terkedap sehingga sedia untuk diguna. Bekas yang telah dibuka mesti dikedap semula dengan teliti dan disimpan menegak untuk mencegah kebocoran. Jangan simpan dalam bekas tidak berlabel. Gunakan kaedah pengurangan yang sesuai untuk mengelakkan pencemaran alam sekitar. Lihat Bahagian 10 untuk bahan yang tidak serasi sebelum mengendali atau mengguna.

## Section 7. Handling and storage

### Precautions for safe handling

## Section 7. Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Bahagian 8: Kawalan pendedahan dan perlindungan diri

### Parameter kawalan

#### Had Pendedahan Pekerja

Nama Ramuan	Had-Had Pendedahan
3-iodo-2-propynyl butylcarbamate (IPBC)	<b>DFG MAC-values list (Jerman, 10/2021). Kulit pemeka.</b> PEAK: 0.116 mg/m <sup>3</sup> , 4 kali per syif, 15 minit. PEAK: 0.01 ppm, 4 kali per syif, 15 minit. TWA: 0.058 mg/m <sup>3</sup> 8 jam. TWA: 0.005 ppm 8 jam.
bronopol (INN)	<b>DFG MAC-values list (Jerman, 10/2021). Diserap melalui kulit. Kulit pemeka.</b>
2-octyl-2h-isothiazol-3-one (OIT)	<b>DFG MAC-values list (Jerman, 10/2021). Diserap melalui kulit. Kulit pemeka.</b> TWA: 0.05 mg/m <sup>3</sup> 8 jam. Borang: pecahan tersedutkan PEAK: 0.1 mg/m <sup>3</sup> , 4 kali per syif, 15 minit. Borang: pecahan tersedutkan

- Kawalan kejuruteraan yang wajar** : Pengalihudaraan am yang baik hendaklah mencukupi untuk mengawal bahan cemar bawaan udara yang terdedah kepada pekerja.
- Kawalan pendedahan alam sekitar** : Pengeluaran daripada pengudaraan atau peralatan proses kerja hendaklah diperiksa untuk memastikan ianya mematuhi keperluan perundangan perlindungan alam sekitar. Bagi sesetengah kes, penyental wasap, penuras atau pengubahsuaian kejuruteraan terhadap peralatan proses adalah perlu bagi mengurangkan pengeluaran ke tahap yang dibenarkan.

### Langkah-langkah perlindungan individu

- Langkah-langkah kebersihan** : Basuh kedua tangan, lengan dan muka sehingga bersih setelah mengendalikan produk kimia, sebelum makan, merokok dan menggunakan tandas dan pada akhir waktu kerja. Teknik yang sesuai harus digunakan apabila menanggalkan pakaian yang mungkin tercemar. Basuh pakaian tercemar sebelum memakai semula. Pastikan tempat mencuci mata dan pancuran air keselamatan berdekatan dengan lokasi tempat kerja.



## Bahagian 8: Kawalan pendedahan dan perlindungan diri

- Perlindungan mata/muka** : Kacamata keselamatan yang mematuhi kelulusan piawai perlu digunakan apabila penilaian risiko menunjukkan ianya perlu untuk mengelakkan pendedahan kepada percikan cecair, kabu, gas atau debu. Jika sentuhan mungkin terjadi, perlindungan berikut harus dipakai, kecuali taksiran menunjukkan tahap perlindungan lebih tinggi: cermin mata keselamatan dengan pelindung sisi.
- Perlindungan kulit**
- Perlindungan tangan** : Sarung tangan kedap penentang bahan kimia, yang mematuhi piawaian yang diluluskan hendaklah dipakai pada setiap masa apabila mengendalikan produk kimia jika penilaian risiko menunjukkan ini adalah perlu. Dengan mempertimbangkan parameter yang ditetapkan oleh pengilang sarung tangan, pastikan semasa digunakan bahawa sarung tangan masih mengekalkan ciri-ciri perlindungannya. Harus diperhatikan bahawa jangka masa hingga terobos untuk mana-mana bahan sarung tangan mungkin berbeza mengikut pengilang sarung tangan. Bagi kes campuran, yang terdiri daripada beberapa zat, jangka masa perlindungan sarung tangan tidak dapat dianggarkan dengan tepat.
- Tidak ada satu bahan atau kombinasi bahan sarung tangan yang memberikan rintangan tak terbatas terhadap mana-mana satu atau gabungan bahan kimia. Jangka masa terobos mestilah lebih panjang daripada jangka masa kegunaan akhir produk.
- Arahan dan maklumat yang diberikan oleh pengilang sarung tangan tentang penggunaan, penyimpanan, penyenggaraan dan pengantiannya mesti dipatuhi. Sarung tangan harus digantikan selalu dan jika ada tanda kerosakan pada bahan sarung tangan.
- Sentiasa pastikan sarung tangan bebas daripada cacat serta disimpan dan digunakan dengan betul.
- Prestasi atau keberkesanan sarung tangan mungkin dikurangkan oleh kerosakan fizikal/kimia serta penyenggaraan kurang sempurna.
- Krim pelindung boleh menolong melindungi kawasan kulit yang terdedah tetapi tidak harus disapukan setelah pendedahan berlaku.
- Pakai sarung tangan yang sesuai diuji untuk ISO 374-1:2016.
- Disyorkan, sarung tangan(masa terobosan) > 8 jam: Getah nitril (> 0.4 mm), neoprena (> 0.35 mm), getah butil (> 0.4 mm), PVC (> 0.5 mm), getah fluor (> 0.35 mm), alkohol Polivinil (PVA) (> 0.3 mm)
- Perlindungan tubuh** : Peralatan perlindungan peribadi untuk badan perlu dipilih berdasarkan tugas yang dilakukan dan risiko yang terlibat dan perlulah diluluskan oleh pakar sebelum mengendali produk ini.
- Perlindungan kulit yang lain** : Kasut yang wajar dan apa jua langkah tambahan bagi perlindungan kulit harus dipilih berdasarkan tugas yang dilakukan dan risiko yang terbabit, dan harus diluluskan oleh seorang pakar sebelum mengendalikan produk ini.
- Perlindungan respiratori** : Jika pekerja terdedah kepada kepekatan melebihi had pendedahan, mereka mesti memakai alat pernafasan yang sesuai dan diiktiraf. Guna pelindung pernafasan yang mengandungi arang dan penapis habuk apabila menyembur produk ini. (sebagai kombinasi penuras A2-P2) Gunakan alat pernafasan udara termampat atau udara segar di dalam ruang-ruang terbatas. Mempertimbangkan penggunaan panapis yang mengandungi arang apabila guna roller atau berus.

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

## Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
3-iodo-2-propynyl butylcarbamate (IPBC)	<b>DFG MAC-values list (Germany, 10/2021). Skin sensitiser.</b> PEAK: 0.116 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. PEAK: 0.01 ppm, 4 times per shift, 15 minutes. TWA: 0.058 mg/m <sup>3</sup> 8 hours. TWA: 0.005 ppm 8 hours.
bronopol	<b>DFG MAC-values list (Germany, 10/2021). Absorbed through skin. Skin sensitiser.</b> <b>DFG MAC-values list (Germany, 10/2021). Absorbed through skin. Skin sensitiser.</b> TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: inhalable fraction PEAK: 0.1 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. Form: inhalable fraction
2-octyl-2h-isothiazol-3-one (OIT)	

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.  
 The breakthrough time must be greater than the end use time of the product.  
 The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.  
 Gloves should be replaced regularly and if there is any sign of damage to the glove material.  
 Always ensure that gloves are free from defects and that they are stored and used correctly.  
 The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.  
 Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

## Section 8. Exposure controls/personal protection

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves (breakthrough time) > 8 hours: nitrile rubber (> 0.4 mm), neoprene (> 0.35 mm), butyl rubber (> 0.4 mm), PVC (> 0.5 mm), fluor rubber (> 0.35 mm), polyvinyl alcohol (PVA) (> 0.3 mm)

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoal filter.

## Seksyen 9. Sifat fizikal dan kimia

### Rupa

- Keadaan fizikal** : Cecair.
- Warna** : Kuning.
- Bau** : Ciri-ciri. [Sedikit]
- Ambang Bau** : Tidak bekenaan.
- pH** : 7.5-9
- Takat Lebur** : 0
- Takat Didih** : Nilai terendah diketahui: 100°C (212°F) (water).
- Takat kilat** : Tidak tersedia.
- Kadar Penyejatan** : 0.36 (water) berbanding dengan butil asetat
- Kemudahnyalaan (pepejal, gas)** : Tidak bekenaan.
- Had mudah meletup (mudah menyala) bawah dan atas** : Tidak bekenaan.
- Tekanan Wap** : Nilai tertinggi yang diketahui: 3.2 kPa (23.8 mm Hg) (pada 20°C) (water). Purata berat: 2.88 kPa (21.6 mm Hg) (pada 20°C)
- Ketumpatan Wap** : Tidak tersedia.
- Ketumpatan relatif** : 1.96 g/cm<sup>3</sup>
- Kelarutan** : Mudah larut dalam bahan berikut: air sejuk dan air panas.
- Pekali Sekatan Oktanol/Air** : Tidak tersedia.
- Suhu penyalaan automatik** : Nilai terendah diketahui: 444.85°C (832.7°F) (Soybean oil).
- Suhu pereputan** : Tidak tersedia.
- Kelikatan** : Kinematik (40°C): >20.5 mm<sup>2</sup>/s (>20.5 cSt)

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Colour** : Yellow.
- Odour** : Characteristic. [Slight]
- Odour threshold** : Not applicable.
- pH** : 7.5-9

## Section 9. Physical and chemical properties

<b>Melting point</b>	: 0
<b>Boiling point</b>	: Lowest known value: 100°C (212°F) (water).
<b>Flash point</b>	: Not available.
<b>Evaporation rate</b>	: 0.36 (water) compared with butyl acetate
<b>Flammability (solid, gas)</b>	: Not applicable.
<b>Lower and upper explosive (flammable) limits</b>	: Not applicable.
<b>Vapour pressure</b>	: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.88 kPa (21.6 mm Hg) (at 20°C)
<b>Vapour density</b>	: Not available.
<b>Relative density</b>	: 1.96 g/cm <sup>3</sup>
<b>Solubility</b>	: Easily soluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Lowest known value: 444.85°C (832.7°F) (soybean oil).
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Kinematic (40C): >20.5 cSt

## Bahagian 10: Kestabilan dan kereaktifan

<b>Kereaktifan</b>	: Tiada data ujian khusus berkaitan dengan kereaktifan bagi produk ini atau ramuannya.
<b>Kestabilan kimia</b>	: Produk ini stabil.
<b>Kemungkinan tindak balas berbahaya</b>	: Dalam keadaan penyimpanan dan penggunaan yang normal, tindak balas berbahaya tidak akan terjadi.
<b>Keadaan-keadaan yang mesti dielak</b>	: Tiada data spesifik.
<b>Bahan tidak serasi</b>	: Tiada data spesifik.
<b>Produk pereputan berbahaya</b>	: Di bawah keadaan penyimpanan dan penggunaan normal, produk penguraian berbahaya tidak akan terhasil.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: No specific data.
<b>Incompatible materials</b>	: No specific data.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Bahagian 11: Maklumat toksikologi

### Maklumat tentang kesan toksikologi

#### Ketoksikan akut

Nama produk/bahan	Keputusan	Spesis	Dos	Pendedahan
3-iodo-2-propynyl butylcarbamate (IPBC)	LD50 Oral	Tikus	1470 mg/kg	-
2-octyl-2h-isothiazol-3-one (OIT)	LD50 Kulit	Arnab	690 mg/kg	-
C(M)IT/MIT (3:1)	LD50 Kulit	Arnab	690 mg/kg	-
	LD50 Oral	Tikus	550 mg/kg	-
	LD50 Oral	Tikus	53 mg/kg	-

#### Kerengsaan/Kakistan

Nama produk/bahan	Keputusan	Spesis	Skor	Pendedahan	Pencerapan
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	Mata - Merengsa	Mamalia - spesis tak dinyatakan	-	-	-
3-iodo-2-propynyl butylcarbamate (IPBC)	Mata - Merengsa	Mamalia - spesis tak dinyatakan	-	-	-
bronopol (INN)	Mata - Merengsa	Mamalia - spesis tak dinyatakan	-	-	-
	Kulit - Zat merengsa ringan	Mamalia - spesis tak dinyatakan	-	-	-
	Kulit - Zat merengsa ringan	Arnab	-	24 jam 500 milligrams	-
	Kulit - Iritan sederhana	Manusia	-	10 milligrams	-
	Kulit - Iritan sederhana	Arnab	-	80 milligrams	-

#### Pemekaan

Nama produk/bahan	Laluan pendedahan	Spesis	Keputusan
3-iodo-2-propynyl butylcarbamate (IPBC)	kulit	Mamalia - spesis tak dinyatakan	Memeka
2-octyl-2h-isothiazol-3-one (OIT)	kulit	Mamalia - spesis tak dinyatakan	Memeka
C(M)IT/MIT (3:1)	kulit	Mamalia - spesis tak dinyatakan	Memeka

#### Mutagenisiti

Tidak tersedia.

#### Karsinogenisiti

Tidak tersedia.

#### Toksisiti reproduktif

Tidak tersedia.

#### Keteratogenikan

Tidak tersedia.

#### Ketoksikan organ sasaran khusus (pendedahan tunggal)

**Bahagian 11: Maklumat toksikologi**

Nama	Kategori	Laluan pendedahan	Organ Sasaran
bronopol (INN)	Kategori 3	-	Kerengsaan saluran pernafasan

**Ketoksikan organ sasaran khusus (pededahan berulang)**

Nama	Kategori	Laluan pendedahan	Organ Sasaran
bismuth vanadium tetraoxide	Kategori 2	penyedutan	-
3-iodo-2-propynyl butylcarbamate (IPBC)	Kategori 1	-	- trakea

**Bahaya penyedutan**

Tidak tersedia.

**Maklumat tentang laluan pendedahan yang berkemungkinan** : Tidak tersedia.

**Kesan Kesihatan Akut Berpotensi**

- Sentuhan mata** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Penyedutan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Sentuhan kulit** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Pengingesan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

**Gejala yang berkaitan dengan ciri fizikal, kimia dan toksikologi**

- Sentuhan mata** : Tiada data spesifik.
- Penyedutan** : Tiada data spesifik.
- Sentuhan kulit** : Tiada data spesifik.
- Pengingesan** : Tiada data spesifik.

**Kesan tertunda dan serta merta, dan juga kesan kronik akibat pendedahan jangka pendek dan panjang****Pendedahan jangka pendek**

- Kesan serta merta yang berpotensi** : Tidak tersedia.
- Kesan tertunda yang berpotensi** : Tidak tersedia.

**Pendedahan jangka panjang**

- Kesan serta merta yang berpotensi** : Tidak tersedia.
- Kesan tertunda yang berpotensi** : Tidak tersedia.

**Kesan Kesihatan Kronik Berpotensi**

Tidak tersedia.

- Am** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Karsinogenisiti** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Mutagenisiti** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Keteratogenikan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Kesan perkembangan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Kesan kepada kesuburan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

**Ukuran ketoksikan secara angka**

**Bahagian 11: Maklumat toksikologi****Anggaran ketoksikan akut**

Tidak tersedia.

**Section 11. Toxicological information****Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate (IPBC)	LD50 Oral	Rat	1470 mg/kg	-
2-octyl-2h-isothiazol-3-one (OIT)	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-
C(M)IT/MIT (3:1)	LD50 Oral	Rat	53 mg/kg	-

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	Eyes - Irritant	Mammal - species unspecified	-	-	-
3-iodo-2-propynyl butylcarbamate (IPBC)	Eyes - Irritant	Mammal - species unspecified	-	-	-
bronopol	Eyes - Irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Human	-	10 milligrams	-
	Skin - Moderate irritant	Rabbit	-	80 milligrams	-

**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl butylcarbamate (IPBC)	skin	Mammal - species unspecified	Sensitising
2-octyl-2h-isothiazol-3-one (OIT)	skin	Mammal - species unspecified	Sensitising
C(M)IT/MIT (3:1)	skin	Mammal - species unspecified	Sensitising

**Mutagenicity**

Not available.

**Carcinogenicity**

Not available.

**Reproductive toxicity**

Not available.

## Section 11. Toxicological information

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
bronopol	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
bismuth vanadium oxide (bivo4) 3-iodo-2-propynyl butylcarbamate (IPBC)	Category 2 Category 1	inhalation -	- trachea

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.



## Section 11. Toxicological information

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## Bahagian 12: Maklumat ekologi

### Ketoksikan

Nama produk/bahan	Keputusan	Spesis	Pendedahan
trizink bis(ortofosfat)	Akut LC50 0.14 mg/l Kronik NOEC 0.1 mg/l Akut EC50 1.9 mg/l	Ikan - Oncorhynchus mykiss Mikroorganisma Alga	96 jam 4 jam 48 jam
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	Akut LC50 11.1 mg/l Akut EC50 0.022 mg/l	Ikan Alga - Scenedesmus subspicatus	96 jam 72 jam
3-iodo-2-propynyl butylcarbamate (IPBC)	Akut EC50 0.16 mg/l Akut LC50 0.067 mg/l Kronik NOEC 70 ppb Air tawar	Crustacea - Daphnia magna Ikan - Oncorhynchus mykiss Ikan - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	48 jam 96 jam 96 jam
bronopol (INN)	Akut EC50 0.18 ppm Air laut Akut EC50 1.6 ppm Air tawar Akut LC50 11.17 ppm Air tawar Kronik NOEC 1.94 ppm	Alga - Skeletonema costatum Dafnia - Daphnia magna Ikan - Lepomis macrochirus Ikan - Oncorhynchus mykiss	96 jam 48 jam 96 jam 49 hari
2-octyl-2h-isothiazol-3-one (OIT)	Akut EC50 0.084 mg/l	Alga - Scenedesmus subspicatus	72 jam
C(M)IT/MIT (3:1)	Akut EC50 0.32 mg/l Akut LC50 0.047 mg/l Akut EC50 0.048 mg/l	Dafnia Ikan Alga - Pseudokirchneriella subcapitata	48 jam 96 jam 72 jam
	Akut EC50 0.0052 mg/l Akut EC50 0.1 mg/l Akut LC50 0.22 mg/l Akut NOEC 0.00064 mg/l Kronik NOEC 0.0012 mg/l	Alga - Skeletonema costatum Dafnia - Daphnia magna Ikan - Oncorhynchus mykiss Alga - Skeletonema costatum Alga - Pseudokirchneriella subcapitata	48 jam 48 jam 96 jam 48 jam 72 jam
	Kronik NOEC 0.004 mg/l Kronik NOEC 0.098 mg/l	Dafnia - Daphnia magna Ikan - Oncorhynchus mykiss	21 hari 28 hari

### Kegigihan dan degradasi

Nama produk/bahan	Separuh hayat Akuatik	Fotolisis	Sifat biorosot
trizink bis(ortofosfat)	-	-	Tidak mudah
3-iodo-2-propynyl butylcarbamate (IPBC)	-	-	Dengan mudah
C(M)IT/MIT (3:1)	-	-	Tidak mudah

### Potensi bioakumulasi

**Bahagian 12: Maklumat ekologi**

Nama produk/bahan	LogP <sub>ow</sub>	BCF	Berpotensi
trizink bis(ortofosfat)	-	60960	tinggi
bismuth vanadium tetraoxide	-	<14	Rendah
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	1.79	71	Rendah
bronopol (INN)	0.18	-	Rendah
2-octyl-2h-isothiazol-3-one (OIT)	2.45	-	Rendah
C(M)IT/MIT (3:1)	-	3.16	Rendah

**Mobiliti tanah**

**Pekali Sekatan Tanah/Air (Koc)** : Tidak tersedia.

**Kesan-kesan buruk lain** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

**Section 12. Ecological information****Toxicity**

Product/ingredient name	Result	Species	Exposure
trizinc bis(orthophosphate)	Acute LC50 0.14 mg/l Chronic NOEC 0.1 mg/l	Fish - Oncorhynchus mykiss Micro-organism	96 hours 4 hours
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	Acute EC50 1.9 mg/l	Algae	48 hours
3-iodo-2-propynyl butylcarbamate (IPBC)	Acute LC50 11.1 mg/l Acute EC50 0.022 mg/l	Fish Algae - Scenedesmus subspicatus	96 hours 72 hours
bronopol	Acute EC50 0.16 mg/l Acute LC50 0.067 mg/l Chronic NOEC 70 ppb Fresh water	Crustaceans - Daphnia magna Fish - Oncorhynchus mykiss Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	48 hours 96 hours 96 hours
2-octyl-2h-isothiazol-3-one (OIT)	Acute EC50 0.18 ppm Marine water Acute EC50 1.6 ppm Fresh water Acute LC50 11.17 ppm Fresh water Chronic NOEC 1.94 ppm	Algae - Skeletonema costatum Daphnia - Daphnia magna Fish - Lepomis macrochirus Fish - Oncorhynchus mykiss	96 hours 48 hours 96 hours 49 days
C(M)IT/MIT (3:1)	Acute EC50 0.084 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute EC50 0.32 mg/l Acute LC50 0.047 mg/l Acute EC50 0.048 mg/l	Daphnia Fish Algae - Pseudokirchneriella subcapitata	48 hours 96 hours 72 hours
	Acute EC50 0.0052 mg/l Acute EC50 0.1 mg/l Acute LC50 0.22 mg/l Acute NOEC 0.00064 mg/l Chronic NOEC 0.0012 mg/l	Algae - Skeletonema costatum Daphnia - Daphnia magna Fish - Oncorhynchus mykiss Algae - Skeletonema costatum Algae - Pseudokirchneriella subcapitata	48 hours 48 hours 96 hours 48 hours 72 hours
	Chronic NOEC 0.004 mg/l Chronic NOEC 0.098 mg/l	Daphnia - Daphnia magna Fish - Oncorhynchus mykiss	21 days 28 days

## Section 12. Ecological information

### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
trizinc bis(orthophosphate)	-	-	Not readily
3-iodo-2-propynyl butylcarbamate (IPBC)	-	-	Readily
C(M)IT/MIT (3:1)	-	-	Not readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
trizinc bis(orthophosphate)	-	60960	high
bismuth vanadium oxide (bivo4)	-	<14	low
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18 and C18-unsatd. acyl) derivs., inner salts	1.79	71	low
bronopol	0.18	-	low
2-octyl-2h-isothiazol-3-one (OIT)	2.45	-	low
C(M)IT/MIT (3:1)	-	3.16	low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Bahagian 13: Maklumat pelupusan

**Kaedah pelupusan** : Penghasilan sisa perlulah dielakkan atau diminimumkan sekiranya boleh. Pelupusan produk ini, larutan dan sebarang produk sampingan perlulah pada setiap masa mematuhi keperluan perlindungan alam sekitar dan perundangan pelupusan sisa dan sebarang keperluan pihak berkuasa serantau tempatan. Pembuangan lebihan dan hasilan yang tidak boleh dikitar semula melalui kontraktor pelupusan sisa yang berlesen. Bahan buangan tidak harus dibuang secara tidak dirawat ke pembentung kecuali patuh sepenuhnya kepada keperluan semua pihak berkuasa dengan kuasa undang-undang. Bungkusan buangan harus dikitar semula. Penunuan atau kambus tanah hanya harus dipertimbangkan apabila tidak mungkin dikitar semula. Bahan ini dan bekasnya hendaklah dilupuskan dengan cara yang selamat. Hati-hati apabila mengendalikan bekas yang telah dikosongkan tetapi belum dibersihkan atau dibilas. Bekas atau pelapik kosong mungkin mengandungi sisa-sisa produk. Elakkan penyebaran bahan tertumpah dan aliran dan bersentuh dengan tanah, jalan air, longkang dan pemetung.





## Section 13. Disposal information

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff

## Section 13. Disposal information

and contact with soil, waterways, drains and sewers.

## Bahagian 14: Maklumat pengangkutan

	UN	ADR/RID	IMDG	IATA
<b>Nombor UN</b>	UN3082	UN3082	UN3082	UN3082
<b>Nama pengiriman wajar PBB</b>	Environmentally hazardous substance, liquid, n.o.s. (PAINT)	Environmentally hazardous substance, liquid, n.o.s. (PAINT)	Environmentally hazardous substance, liquid, n.o.s. (PAINT). Pencemar marin (trizinc bis (orthophosphate), 2-octyl-2h-isothiazol-3-one (OIT))	Environmentally hazardous substance, liquid, n.o.s. (PAINT)
<b>Kelas bahaya pengangkutan</b>	9 	9 	9 	9 
<b>Kumpulan Pembungkusan</b>	III	III	III	III
<b>Bahaya Alam Sekitar</b>	Ya.	Ya.	Ya.	Ya.
<b>Maklumat Tambahan</b>	Produk ini tidak dikawal selia sebagai barang berbahaya apabila dihantar dalam saiz ≤5 L atau ≤5 kg, dengan syarat pembungkusan memenuhi peruntukan am 4.1.1.1, 4.1.1.2 dan 4.1.1.4 hingga 4.1.1.8.	Produk ini tidak dikawal selia sebagai barang berbahaya apabila dihantar dalam saiz ≤5 L atau ≤5 kg, dengan syarat pembungkusan memenuhi peruntukan am 4.1.1.1, 4.1.1.2 dan 4.1.1.4 hingga 4.1.1.8. <b>Nombor Identifikasi Bahaya 90</b> <b>Kod terowong (-)</b>	Produk ini tidak dikawal selia sebagai barang berbahaya apabila dihantar dalam saiz ≤5 L atau ≤5 kg, dengan syarat pembungkusan memenuhi peruntukan am 4.1.1.1, 4.1.1.2 dan 4.1.1.4 hingga 4.1.1.8. <b>Jadual Kecemasan F-A, S-F</b>	Produk ini tidak dikawal selia sebagai barang berbahaya apabila dihantar dalam saiz ≤5 L atau ≤5 kg, dengan syarat pembungkusan memenuhi peruntukan am 5.0.2.4.1, 5.0.2.6.1.1 dan 5.0.2.8.









**Langkah pencegahan istimewa untuk pengguna** : "Pengangkutan dalam premis pemilik:" sentiasa mengangkut dalam bekas bertutup yang tegak dan selamat. Pastikan orang yang mengangkut produk tahu apa yang perlu dilakukan sekiranya berlaku kemalangan atau tumpahan.

**Angkut secara pukal menurut alatan IMO** : Tidak tersedia.

## Section 14. Transport information

	UN	ADR/RID	IMDG	IATA
<b>UN number</b>	UN3082	UN3082	UN3082	UN3082

## Section 14. Transport information

<b>UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. (PAINT)	Environmentally hazardous substance, liquid, n.o.s. (PAINT)	Environmentally hazardous substance, liquid, n.o.s. (PAINT). Marine pollutant (trizinc bis (orthophosphate), 2-octyl-2h-isothiazol-3-one (OIT))	Environmentally hazardous substance, liquid, n.o.s. (PAINT)
<b>Transport hazard class(es)</b>	9  	9  	9  	9  
<b>Packing group</b>	III	III	III	III
<b>Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.
<b>Additional information</b>	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <b>Hazard identification number</b> 90 <b>Tunnel code</b> (-)	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <b>Emergency schedules</b> F-A, S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Special precautions for user** : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Bahagian 15: Maklumat pengawalseliaan

**Inventori Malaysia (Daftar EHS)** : Tidak ditentukan

### Peraturan Antarabangsa

#### Bahan Kimia Jadual I, II & III Senarai Konvensyen Senjata Kimia

Tidak tersenarai.

#### Protokol Montreal

Tidak tersenarai.

#### Konvensyen Stockholm tentang zat pencemar organik gigih

Tidak tersenarai.

#### Protokol UNECE Aarhus tentang POP dan Logam Berat

Tidak tersenarai.

## Section 15. Regulatory information

## Section 15. Regulatory information

Malaysia Inventory (EHS Register) : Not determined

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### International lists

#### National inventory

Australia : Not determined.  
 Canada : Not determined.  
 China : Not determined.  
 Europe :  
 Japan : **Japan inventory (CSCL):** Not determined.  
           **Japan inventory (ISHL):** Not determined.  
 New Zealand : Not determined.  
 Philippines : Not determined.  
 Republic of Korea : Not determined.  
 Taiwan : Not determined.  
 United States : Not determined.

## Bahagian 16: Maklumat lain

### Sejarah

Tarikh cetakan : 22.03.2023  
 Tarikh keluaran/Tarikh semakan : 22.03.2023  
 Tarikh Keluaran Terdahulu : 21.05.2019  
 Versi : 1  
 Petunjuk untuk Singkatan : ATE = Anggaran Keracunan Teruk  
   BCF = Faktor Biokepekatan  
   GHS = Sistem Global Berharmoni bagi Pengelasan dan Pelabelan Kimia  
   IATA = Persatuan Pengangkutan Udara Antarabangsa  
   IBC = Bekas Pukul Sederhana  
   IMDG = Barang-barang Berbahaya Laut Antarabangsa  
   LogPow = Logaritma pekali sekatan bagi oktanol/air  
   MARPOL = Persidangan Antarabangsa bagi Pencegahan Pencemaran Daripada Kapal-kapal, 1973 seperti yang diubah oleh Protokol 1978. ("Marpol" = pencemaran laut)  
   UN = Pertubuhan Bangsa-bangsa Bersatu

### Prosedur yang digunakan untuk memperoleh pengelasan

Klasifikasi	Justifikasi
BERBAHAYA KEPADA PERSEKITARAN AKUATIK - BAHAYA KRONIK - Kategori 2	Kaedah pengiraan

Rujukan : Tidak tersedia.

## Bahagian 16: Maklumat lain

✔ Menunjukkan maklumat yang telah berubah daripada versi isu terdahulu.

### Notis kepada pembaca

Pada pengetahuan terbaik kami, maklumat yang terkandung di dalam adalah tepat. Bagaimanapun, pembekal yang dinamakan di atas atau sebarang anak syarikatnya tidak bertanggungjawab terhadap ketepatan atau kelengkapan maklumat yang terkandung di dalam.

Penentuan terakhir kesesuaian sebarang bahan adalah tanggungjawab pengguna. Semua bahan mungkin mengandungi bahaya yang tidak diketahui dan harus digunakan dengan berhati-hati. Walaupun bahaya tertentu telah diterangkan di sini, kami tidak memberi jaminan bahawa hanya bahaya ini sahaja yang wujud.

## Section 16. Other information

### History

**Date of printing** : 22.03.2023

**Date of issue/Date of revision** : 22.03.2023

**Date of previous issue** : 21.05.2019

**Version** : 1

**Key to abbreviations** :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- UN = United Nations

### Procedure used to derive the classification

Classification	Justification
HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Category 2	Calculation method

**References** : Not available.

✔ Indicates information that has changed from previously issued version.

### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.