

VISIR Oljegrinning klar VISIR Oljegrinning klar

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	: VISIR Oljegrinning klar
Product code	: 5860
Product type	: Liquid.
Product description	: Paint.
Other means of identification	: Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in coatings - Consumer use: Apply this product only as specified on the label.

1.3 Details of the supplier of the safety data sheet

Jotun Boya Sanayi ve Ticaret A.Ş.
Balabandere Caddesi, Hilpark Suites Sitesi No: 10, İstinye 34460 Sarıyer, İstanbul

Tel. +90 212 279 7878
SDSJotun@jotun.com

Başvurulacak Kişi: Emre Demir
emre.demir@jotun.com.tr

1.4 Emergency telephone number

National Poison Information Center

- +90 224 442 82 93 Uludağ Üniversitesi Zehir Danışma Merkezi (www.uludag.edu.tr/uludag/zehir.html)
a. ACİL DURUM TELEFONU: Zehirlenme durumlarında gerektiğinde ulusal zehir merkezinin (UZEM) 114 nolu telefonunu arayınız.
b. ACİL İLK YARDIM MERKEZİ:112
c. İTFAİYE:110

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to regulation SEA: RG.-10/12/2020-31330

☑ Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
STOT RE 1, H372 (central nervous system (CNS))
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation SEA: RG.-10/12/2020-31330.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 2/15

SECTION 2: Hazards identification

Signal word : Danger.

Hazard statements : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS))
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

General : P102 - Keep out of reach of children.

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
P273 - Avoid release to the environment.
P260 - Do not breathe vapour.
P270 - Do not eat, drink or smoke when using this product.
P264 - Wash hands thoroughly after handling.

Response : P391 - Collect spillage.
P314 - Get medical advice/attention if you feel unwell.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)
2-octyl-2h-isothiazol-3-one (OIT)

Supplemental label elements : Not applicable.

Additional information : Contains film preservative: DCOIT

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Yes, applicable.

Tactile warning of danger : Yes, applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	CAS no.	%	SEA: RG.-11/12/2013-28848	Type
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)	EC: 265-185-4 CAS: 64742-82-1 Index: 649-330-00-2	≥50 - ≤75	STOT RE 1, H372 (central nervous system (CNS)) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	-
dipropylene glycol methyl ether	EC: 252-104-2 CAS: 34590-94-8	≤10	Not classified.	-
neodecanoic acid, zinc salt	CAS: 27253-29-8	≤3	Aquatic Chronic 3, H412	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	CAS: 64359-81-5	<0.25	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	-

SECTION 3: Composition/information on ingredients

2-octyl-2h-isothiazol-3-one (OIT)	CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) See Section 16 for the full text of the H statements declared above.	-
-----------------------------------	--	--------	---	---

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 4/15

SECTION 4: First aid measures

There are no data available on the mixture itself. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT), 2-octyl-2h-isothiazol-3-one (OIT). May produce an allergic reaction.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 6/15

SECTION 7: Handling and storage

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds (in tonnes)

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200	500

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-methoxymethylethoxy)propanol	TR ISGGM OEL (Turkey, 12/2013). Absorbed through skin. TWA: 308 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived no effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)	DNEL	Long term Inhalation	0.41 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	1.9 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	178.57 mg/m ³	General population	Local
	DNEL	Short term Inhalation	640 mg/m ³	General population	Local
	DNEL	Long term Inhalation	837.5 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	1066.67 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	1152 mg/m ³	General population	Systemic
	DNEL	Short term	1286.4 mg/	Workers	Systemic

SECTION 8: Exposure controls/personal protection

dipropylene glycol methyl ether	DNEL	Inhalation	m ³		
		Long term Dermal	65 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	310 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	37.2 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Oral	1.67 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	15 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
neodecanoic acid, zinc salt	DNEL	Long term Inhalation	308 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	1.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2.21 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.21 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	7.67 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	25.93 mg/m ³	Workers	Systemic

Predicted no effect concentrations

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
dipropylene glycol methyl ether	PNEC	Fresh water	19 mg/l	Assessment Factors
	PNEC	Marine	1.9 mg/l	Assessment Factors
	PNEC	Fresh water sediment	70.2 mg/kg dwt	Assessment Factors
	PNEC	Marine water sediment	7.02 mg/kg dwt	Assessment Factors
	PNEC	Soil	2.74 mg/kg	Assessment Factors
	PNEC	Sewage Treatment Plant	4168 mg/l	Assessment Factors

8.2 Exposure controls

Appropriate engineering controls

- : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

SECTION 8: Exposure controls/personal protection

- Hand protection** : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
The breakthrough time must be greater than the end use time of the product.
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Always ensure that gloves are free from defects and that they are stored and used correctly.
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
Wear suitable gloves tested to ISO 374-1:2016.
Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber
- For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- pH** : Not applicable.
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : **L**owest known value: 189.6°C (373.3°F) (dipropylene glycol methyl ether).
Weighted average: 195.6°C (384.1°F)
- Flash point** : Closed cup: 63°C (ISO 3679:2015)
- Evaporation rate** : 0.02 (dipropylene glycol methyl ether) compared with butyl acetate
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : 1.1 - 14%
- Vapour pressure** : **H**ighest known value: 0.05 kPa (0.4 mm Hg) (at 20°C) (hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)).
- Vapour density** : Highest known value: 5.1 (Air = 1) (dipropylene glycol methyl ether).
- Density** : 0.884 g/cm³ (ISO 2811-1:2016)

Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 9/15

SECTION 9: Physical and chemical properties

Solubility(ies)	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Lowest known value: 207°C (404.6°F) (dipropylene glycol methyl ether).
Decomposition temperature	: Not available.
Viscosity	: <input checked="" type="checkbox"/> Kinematic (40°C): >20.5 mm ² /s (>20.5 cSt) (ISO 3219)
Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. Under normal conditions of storage and use, hazardous reactions will not occur.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects** There are no data available on the mixture itself. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT), 2-octyl-2h-isothiazol-3-one (OIT). May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-octyl-2H-isothiazol-3-one (OIT)	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

Conclusion/Summary : Not available.**Acute toxicity estimates**

Route	ATE value
Inhalation (dusts and mists)	133.67 mg/l

Irritation/Corrosion

Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 10/15

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-methoxymethylethoxy) propanol	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Mammal - species unspecified	-	-	-
	Skin - Severe irritant	Mammal - species unspecified	-	-	-

Conclusion/Summary : Not available.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
4,5-dichloro-2-octyl-2H-isothiazol-3-one	skin	Mammal - species unspecified	Sensitising
2-octyl-2H-isothiazol-3-one (OIT)	skin	Mammal - species unspecified	Sensitising

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy	Category 1	-	central nervous system (CNS)

Aspiration hazard

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 11/15

SECTION 11: Toxicological information

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute EC50 0.0057 mg/l	Crustaceans - Daphnia magna	48 hours
	Acute LC50 0.014 mg/l	Fish - Lepomis macrochirus	96 hours
	Acute LC50 0.0027 mg/l	Fish - Onchorhynchus mykiss	96 hours
	Chronic NOEC 0.00056 mg/l	Fish	97 days
	Acute EC50 0.084 mg/l	Algae - Scenedesmus subspicatus	72 hours
2-octyl-2H-isothiazol-3-one (OIT)	Acute EC50 0.32 mg/l	Daphnia	48 hours
	Acute LC50 0.047 mg/l	Fish	96 hours

Conclusion/Summary : Water polluting material. May be harmful to the environment if released in large quantities. This material is toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-methoxymethylethoxy) propanol	-	-	Readily
4,5-dichloro-2-octyl-2H-isothiazol-3-one	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Naphtha (petroleum), hydrodesulfurized heavy	-	10 to 2500	high
(2-methoxymethylethoxy) propanol	0.004	-	low
neodecanoic acid, zinc salt	-	60960	high
2-octyl-2H-isothiazol-3-one (OIT)	2.45	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.









SECTION 13: Disposal considerations

13.1 Waste treatment methods

T. C. Ministry of Environment and Urbanism published on April 2, 2015 R.G. Dispose according to the "Waste Management Regulation" no. 29314.

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT))	Environmentally hazardous substance, liquid, n.o.s. (4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT))	Environmentally hazardous substance, liquid, n.o.s. (4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)). Marine pollutant (4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT))	Environmentally hazardous substance, liquid, n.o.s. (4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT))
14.3 Transport hazard class(es)	9  	9  	9  	9  

Product name : VISIR Oljegrunning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 13/15

SECTION 14: Transport information

14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional information	<p>This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.</p> <p>Hazard identification number 90</p> <p>Special provisions 375</p> <p>Tunnel code (-)</p>	<p>This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.</p>	<p>This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.</p> <p>Emergency schedules F-A, S-F</p>	<p>This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.</p>

Marking : The environmental hazardous / marine pollutant mark is only applicable for packages containing more than 5 litres for liquids and 5 kg for solids.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Directive

This product is controlled under the Regulation on the prevention of major industrial accidents and reduction of their effects.

Danger criteria

Category
E2

EU regulations

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

International regulations

Product name : VISIR Oljegrunning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 14/15

SECTION 15: Regulatory information

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to regulation SEA: RG.-10/12/2020-31330

Classification	Justification
✔ Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372 (central nervous system (CNS)) Aquatic Chronic 2, H411	Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

✔ H301 H302 H304 H311 H314 H315 H317 H318 H319 H330 H372 H400 H410 H411 H412	Toxic if swallowed. Harmful if swallowed. May be fatal if swallowed and enters airways. Toxic in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
--	---

Full text of classifications [CLP/GHS]

✔ Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1 Skin Irrit. 2 Skin Sens. 1 STOT RE 1	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
---	--

Product name : VISIR Oljegrønning klar

SDS No. : 5860

Revision date : 01.02.2023

Initial Preparation Date : 13.04.2018

Version : 3

Page : 15/15

SECTION 16: Other information

Date of printing : 01.02.2023

Date of issue/ Date of revision : 01.02.2023

Date of previous issue : 09.06.2021

Version : 3

Contact information of certified author

Responsible Person: Emre Demir

Mail Address: emre.demir@jotun.com.tr

Certificate No: KDU01.14.06

Certificate Expiration Date: 11.07.2025

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.