

# SAFETY DATA SHEET



## Jotamastic SF Alu Comp A

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

<b>Product name</b>	: Jotamastic SF Alu Comp A
<b>Product code</b>	: 9002
<b>Product description</b>	: Paint.
<b>Product type</b>	: Liquid.
<b>Other means of identification</b>	: Not available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### 1.3 Details of the supplier of the safety data sheet

Jotun Boya Sanayi ve Ticaret A.Ş.  
Balabandere Caddesi, Hilpark Suites Sitesi No: 10, İstinye 34460 Sarıyer, İstanbul

Tel. +90 212 279 7878  
SDSJotun@jotun.com

Başvurulacak Kişi: Deren Ercan  
deren.metiner@jotun.com

**Original preparation date** : 05.06.2023

#### 1.4 Emergency telephone number

##### National Poison Information Center

- +90 224 442 82 93 Uludağ Üniversitesi Zehir Danışma Merkezi ([www.uludag.edu.tr/uludag/zehir.html](http://www.uludag.edu.tr/uludag/zehir.html))  
a. ACİL DURUM TELEFONU: Zehirlenme durumlarında gerektiğinde ulusal zehir merkezinin (UZEM) 114 nolu telefonunu arayınız.  
b. ACİL İLK YARDIM MERKEZİ:112  
c. İTFAİYE:110

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to regulation SEA: RG.-10/12/2020-31330

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation SEA: RG.-10/12/2020-31330.


See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** :

Warning.

**Hazard statements** :

H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements**

**General** :

Not applicable.

**Prevention** :

P280 - Wear protective gloves. Wear eye or face protection.  
 P273 - Avoid release to the environment.  
 P261 - Avoid breathing vapour.

**Response** :

P391 - Collect spillage.  
 P362 + P364 - Take off contaminated clothing and wash it before reuse.  
 P302 + P352 - IF ON SKIN: Wash with plenty of water.  
 P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** :

Not applicable.

**Disposal** :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** :

epoxy resin (MW ≤ 700)  
 epoxy-formaldehyde resin (MW<700)  
 oxirane, mono[(c12-14-alkyloxy)methyl]derivs  
 hydrocarbons, c9-unsatd., polymd.  
 Phenol, methylstyrenated  
 Phenol, styrenated

**Supplemental label elements** :

Contains epoxy constituents. May produce an allergic reaction.

**Annex 17 - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Not applicable.

**2.3 Other hazards**

**Product meets the criteria for PBT or vPvB** :

This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

**Other hazards which do not result in classification** :

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	SEA: RG.-10/12/2020-31330	Type
epoxy resin (MW ≤ 700)	EC: 216-823-5 CAS: 1675-54-3	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	[1]
epoxy-formaldehyde resin (MW<700)	EC: 500-006-8 CAS: 9003-36-5	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
oxirane, mono[(c12-14-alkyloxy)methyl] derivs	EC: 271-846-8 CAS: 68609-97-2	≤10	Skin Irrit. 2, H315 Skin Sens. 1B, H317	[1]
hydrocarbons, c9-unsatd., polymd.	CAS: 71302-83-5	≤5	Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
benzyl alcohol	EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≤5	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	[1]
Phenol, methylstyrenated	EC: 270-966-8 CAS: 68512-30-1	≤3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1] [2]
Phenol, styrenated	EC: 262-975-0 CAS: 61788-44-1	≤3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
complex mixture of diamid waxes	-	≤3	Aquatic Chronic 4, H413	[1]
hydrocarbons, C9, aromatics	EC: 918-668-5 CAS: 128601-23-0	≤3	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance meets the criteria for vPvB

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**SECTION 4: First aid measures**

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed****Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

**Over-exposure signs/symptoms**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

**5.2 Special hazards arising from the substance or mixture**

## SECTION 5: Firefighting measures

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide  
 sulfur oxides  
 halogenated compounds  
 metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

See Technical Data Sheet / packaging for further information.

#### Regulation on the prevention of major industrial accidents and reduction of their effects - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

#### Biological exposure indices

No exposure indices known.

- Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

**SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Type	Exposure	Value	Population	Effects	
2,2-bis[4(2,3-epoksipropoksi)fenil]propan	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic	
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	4.93 mg/m <sup>3</sup>	Workers	Systemic	
	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	DMEL	Short term Dermal	8.3 µg/cm <sup>2</sup>	Workers	Local
DNEL		Long term Oral	6.25 mg/kg bw/day	General population	Systemic	
DNEL		Long term Inhalation	8.7 mg/m <sup>3</sup>	General population	Systemic	
DNEL		Long term Inhalation	29.39 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Dermal	62.5 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	104.15 mg/kg bw/day	Workers	Systemic	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	3.6 mg/m <sup>3</sup>	Workers	Systemic	
	hydrocarbons, C9-unsaturated, polymerized	DNEL	Long term Dermal	3.5 mg/kg bw/day	Workers	Systemic
DNEL		Long term Inhalation	1.41 mg/m <sup>3</sup>	Workers	Systemic	
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	5.4 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	22 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Short term Inhalation	27 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Inhalation	110 mg/m <sup>3</sup>	Workers	Systemic	
	Phenol, methylstyrenated	DNEL	Long term Dermal	16.4 mg/kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	57 mg/m <sup>3</sup>	General population [Consumers]	Systemic

**SECTION 8: Exposure controls/personal protection**

Phenol, styrenated	DNEL	Long term Dermal	8 mg/kg bw/day	General population [Consumers]	Systemic	
	DNEL	Long term Inhalation	28 mg/m <sup>3</sup>	General population [Consumers]	Systemic	
	DNEL	Long term Oral	4 mg/kg bw/day	General population [Consumers]	Systemic	
	DNEL	Long term Oral	0.2 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.348 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	1.41 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	1.67 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	3.5 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.75 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	1.31 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	2.1 mg/kg bw/day	Workers	Systemic	
	hydrocarbons, C9, aromatics	DNEL	Long term Inhalation	7.4 mg/m <sup>3</sup>	Workers	Systemic
		DNEL	Long term Dermal	12.5 mg/kg bw/day	Workers	Systemic
DNEL		Long term Inhalation	151 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Dermal	7.5 mg/kg bw/day	General population [Consumers]	Systemic	
DNEL		Long term Inhalation	32 mg/m <sup>3</sup>	General population [Consumers]	Systemic	
DNEL		Long term Oral	7.5 mg/kg bw/day	General population [Consumers]	Systemic	
DNEL		Long term Inhalation	0.41 mg/m <sup>3</sup>	General population	Systemic	
DNEL		Long term Inhalation	1.9 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Inhalation	178.57 mg/m <sup>3</sup>	General population	Local	
DNEL		Short term Inhalation	640 mg/m <sup>3</sup>	General population	Local	
DNEL	Long term Inhalation	837.5 mg/m <sup>3</sup>	Workers	Local		
DNEL	Short term Inhalation	1066.67 mg/m <sup>3</sup>	Workers	Local		
DNEL	Short term Inhalation	1152 mg/m <sup>3</sup>	General population	Systemic		
DNEL	Short term Inhalation	1286.4 mg/m <sup>3</sup>	Workers	Systemic		

**PNECs**



**SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Compartment Detail	Value	Method Detail
2,2-bis[4(2,3-epoksipropoksi)fenil]-propan	Fresh water	0.006 mg/l	-
	Marine	0.0006 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	0.996 mg/l	-
	Marine water sediment	0.0996 mg/l	-
	Soil	0.196 mg/l	-
hydrocarbons, C9-unsaturated, polymerized	Fresh water	54 µg/l	-
	Marine	5.4 µg/l	-
	Sewage Treatment Plant	2.2 mg/l	-
	Fresh water sediment	1584 mg/kg dwt	-
	Marine water sediment	158 mg/kg dwt	-
	Soil	316.7 mg/kg dwt	-
benzyl alcohol	Secondary Poisoning	200 mg/kg	-
	Fresh water	1 mg/l	-
	Marine	0.1 mg/l	-
	Sewage Treatment Plant	39 mg/l	-
	Fresh water sediment	5.27 mg/kg dwt	-
	Marine water sediment	0.527 mg/kg dwt	-
Phenol, methylstyrenated	Soil	0.456 mg/kg dwt	-
	Fresh water	14 µg/l	-
	Marine	1.4 µg/l	-
	Sewage Treatment Plant	2.4 mg/l	-
	Fresh water sediment	52.9 mg/kg dwt	-
	Marine water sediment	5.3 mg/kg dwt	-
	Soil	10.5 mg/kg dwt	-

**8.2 Exposure controls**

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection**

**Hand protection** : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

## SECTION 8: Exposure controls/personal protection

Wear suitable gloves tested to ISO 374-1:2016.

May be used, gloves(breakthrough time) 4 - 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm)

Not recommended, gloves(breakthrough time) < 1 hour: PVC (> 0.5 mm)

Recommended, gloves(breakthrough time) > 8 hours: fluor rubber (> 0.35 mm), Viton® (> 0.7 mm), 4H/Silver Shield® (> 0.07 mm), neoprene (> 0.35 mm), butyl rubber (> 0.4 mm), nitrile rubber (> 0.75 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Aluminium, ,Aluminium red toned
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : Lowest known value: 135 to 210°C (275 to 410°F)(hydrocarbons, C9, aromatics).  
Weighted average: 272.25°C (522°F)
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)
- Flash point** : Closed cup: 83°C (181.4°F)
- Auto-ignition temperature** : Lowest known value: >375°C (>707°F) (hydrocarbons, c9-unsatd., polymd.).
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s
- Solubility(ies)** :

Media	Result
cold water	Not soluble
hot water	Not soluble

**Partition coefficient: n-octanol/ water** : Not available.

## SECTION 9: Physical and chemical properties

- Vapour pressure** : Highest known value: 0.3 kPa (2.5 mm Hg) (at 20°C) (hydrocarbons, C9, aromatics). Weighted average: 0.03 kPa (0.23 mm Hg) (at 20°C)  
0.007 (benzyl alcohol) compared with butyl acetate
- Density** : 1.643 to 1.67 g/cm<sup>3</sup>
- Vapour density** : Highest known value: 11.7 (Air = 1) (epoxy resin (MW ≤ 700)). Weighted average: 10.26 (Air = 1)
- Explosive properties** : Not available.
- Oxidising properties** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Shelf life at 23 °C** : 18 month(s)

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2-bis[4 (2,3-epoksipropoksi)fenil]- propan	LD50 Dermal	Rabbit	20 g/kg	-
	LD50 Oral	Mouse	15600 mg/kg	-
Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	LD50 Oral	Rat	17100 mg/kg	-
	LD50 Dermal	Rat	2000 mg/kg	-
hydrocarbons, C9-unsaturated, polymerized	LD50 Oral	Rat	2000 mg/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
benzyl alcohol	LD50 Oral	Rabbit	>5010 mg/kg	-
	LD50 Oral	Rat	2500 mg/kg	-
Phenol, styrenated	LD50 Dermal	Rabbit	>5010 mg/kg	-
	LD50 Oral	Rat	2500 mg/kg	-

**Conclusion/Summary** : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Jotamastic SF Alu Comp A	35142.9	N/A	N/A	N/A	42.9
oxirane, mono[(c12-14-alkyloxy)methyl]derivs	17100	N/A	N/A	N/A	N/A
benzyl alcohol	1230	N/A	N/A	N/A	1.5
Phenol, styrenated	2500	N/A	N/A	N/A	N/A

## SECTION 11: Toxicological information

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,2-bis[4(2,3-epoksi)propoksi fenil]-propan	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Skin - Mild irritant	Mammal - species unspecified	-	-	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 µl	-
benzyl alcohol	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
Phenol, methylstyrenated	Skin - Mild irritant	Mammal - species unspecified	-	-	-
Phenol, styrenated	Eyes - Mild irritant	Rabbit	-	0.1 Milliliters	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Rabbit	-	0.5 Milliliters	-

**Conclusion/Summary** : Not available.

### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
2,2-bis[4(2,3-epoksi)propoksi fenil]-propan	skin	Mammal - species unspecified	Sensitising
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	skin	Mammal - species unspecified	Sensitising
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	skin	Mammal - species unspecified	Sensitising
hydrocarbons, C9-unsaturated, polymerized	skin	Mouse	Sensitising
Phenol, methylstyrenated	skin	Mammal - species unspecified	Sensitising
Phenol, styrenated	skin	Mammal - species unspecified	Sensitising

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

**SECTION 11: Toxicological information**

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, C9, aromatics	Category 3 Category 3	-	Respiratory tract irritation Narcotic effects

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

Product/ingredient name	Result
hydrocarbons, C9, aromatics	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

**Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Short term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

**Long term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

**Potential chronic health effects**

Not available.

- Conclusion/Summary** : Not available.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
2,2-bis[4(2,3-epoksi)propoksi fenil]-propan  Formaldehide, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute EC50 1.4 mg/l	Daphnia	48 hours
	Acute LC50 3.1 mg/l	Fish - pimephales promelas	96 hours
	Chronic NOEC 0.3 mg/l	Fish	21 days
	Acute EC50 2 mg/l	Daphnia	24 hours
Phenol, styrenated	Acute LC50 2 mg/l	Fish	96 hours
	Acute EC50 100 mg/l	Algae	72 hours
	Acute EC50 54 mg/l	Daphnia	48 hours
hydrocarbons, C9, aromatics	Acute LC50 25.8 mg/l	Fish	96 hours
	Acute EC50 <10 mg/l	Daphnia	48 hours
	Acute IC50 <10 mg/l	Algae	72 hours
	Acute LC50 <10 mg/l	Fish	96 hours

**Conclusion/Summary** : Water polluting material. May be harmful to the environment if released in large quantities. This material is toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2-bis[4(2,3-epoksi)propoksi fenil]-propan	-	-	Not readily
Formaldehide, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	-	Not readily
benzyl alcohol	-	-	Readily
hydrocarbons, C9, aromatics	-	-	Not readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2,2-bis[4(2,3-epoksi)propoksi fenil]-propan	2.64 to 3.78	31	low
Formaldehide, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	low
Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	low
hydrocarbons, C9-unsaturated, polymerized	3.627	-	low
benzyl alcohol	0.87	<100	low
Phenol, methylstyrenated	3.627	-	low
hydrocarbons, C9, aromatics	-	10 to 2500	high

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

## SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
epoxy resin (MW ≤ 700)	No	N/A	No	No	No	N/A	No
epoxy-formaldehyde resin (MW<700)	No	N/A	N/A	No	N/A	N/A	N/A
oxirane, mono[(c12-14-alkyloxy)methyl] derivs	No	N/A	No	No	No	N/A	No
hydrocarbons, C9-unsaturated, polymerized	No	N/A	N/A	No	N/A	N/A	N/A
benzyl alcohol	No	N/A	No	No	No	N/A	No
Phenol, methylstyrenated	No	N/A	N/A	No	SVHC (Recommended)	Specified	Specified
Phenol, styrenated	No	N/A	N/A	No	N/A	N/A	N/A
complex mixture of diamid waxes	No	N/A	N/A	No	N/A	N/A	N/A
hydrocarbons, C9, aromatics	No	N/A	No	No	No	N/A	No

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### Waste list

Waste code	Waste code definition
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

#### Packaging





**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN3082	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), epoxy-formaldehyde resin (MW<700))	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), epoxy-formaldehyde resin (MW<700))	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), epoxy-formaldehyde resin (MW<700)). Marine pollutant	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), epoxy-formaldehyde resin (MW<700))

## SECTION 14: Transport information

			(epoxy resin (MW ≤ 700), epoxy-formaldehyde resin (MW<700))	
<b>14.3 Transport hazard class(es)</b>	9 	9 	9 	9 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.

### Additional information

#### ADR/RID

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Hazard identification number** 90

**Tunnel code** (-)

#### ADN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

#### IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Emergency schedules** F-A, S-F

#### IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

#### Marking

: The environmental hazardous / marine pollutant mark is only applicable for packages containing more than 5 litres for liquids and 5 kg for solids.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Turkey Regulation No. 30105, KKDİK

#### Annex 14 - List of substances subject to authorization

##### Annex 14

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex 17 - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.



**SECTION 15: Regulatory information****Ozone depleting substances**

Not listed.

**Regulation on the prevention of major industrial accidents and reduction of their effects**

This product is controlled under the Regulation on the prevention of major industrial accidents and reduction of their effects.

**Danger criteria****Category**

E2

**EU regulations****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

**Substances of very high concern**

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
WPvB	oligomerisation and alkylation reaction products of 2-phenylpropene and phenol	Recommended	D(2023) 8585-DC	23.01.2024

**Annex XVII - Restrictions** : Not applicable.

**on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

**Industrial emissions** : Listed

**(integrated pollution prevention and control) - Air**

**Industrial emissions** : Listed

**(integrated pollution prevention and control) - Water**

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**International regulations****Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

## SECTION 15: Regulatory information

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 EUH statement = SEA-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to regulation SEA: RG.-10/12/2020-31330

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### Full text of classifications [SEA/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of printing** : 28.05.2024

**Date of issue/ Date of revision** : 28.05.2024

**Date of previous issue** : 29.11.2023

**Version** : 1.02

### Contact information of certified author

Responsible Person: Deren Ercan  
 Mail Address: deren.metiner@jotun.com  
 Certificate No: LONCA KDU81/2021.26  
 Certificate Expiration Date: 14.10.2026

### Notice to reader

## SECTION 16: Other information

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.