

## JOTAPROFF PVA matt 05

### Product description

#### Type

Waterborne dispersion paint for indoor use.

#### Features and benefits

Wall paint with good opacity, and a subtle gloss appearance. Offers limited splash back, and offers an appearance of a nice finish with a fine texture.

#### Recommended use

Use as a middle and topcoat on substrates made by plaster, concrete, sand filler, boards, glass fibre woven fabric and paper wallpaper.

### Product data

<b>Packaging size</b>	Pre-mixed colours and White 10 liter. A -base: 2,7 and 9 liter. B- and C-base: 9 liter.
<b>Base availability</b>	A, B and C.
<b>Tinting</b>	All other colour formulations to be mixed over <b>Jotun Multicolor</b> . Up to 10 % with <b>Jotun Multicolor</b> colorants.
<b>Colors</b>	Pre-mixed colours: White, 1767 Råhvid and 1759 Lys råhvid.
<b>Gloss level</b>	05 silky matt
<b>Generic type</b>	PVA copolymer dispersion panit
<b>Solids by volume</b>	38 ± 2 volume%
<b>Specific gravity</b>	1.4
<b>VOC for Ready-for-Use Mixture</b>	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC.

### Application data

#### Remarks

Contents of tins with different production numbers should be mixed to avoid possible colour deviations. Stir well.

#### Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

#### Guiding data for airless spray

<b>Nozzle tip</b>	0.46-0.53 mm (0.018-0.021")
<b>Spray angle degrees</b>	65-80°
<b>Pressure at nozzle</b>	Min. 15 MPa (Min. 150 kg/cm <sup>2</sup> )

#### Spreading rate and film thickness

	Spreading rate per coat (m <sup>2</sup> /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)

Recommended: 8 - 10 100 - 125 38 - 48

### Conditions during application

Temperature of substrate and air must be minimum +10 °C.

### Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

#### The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Recoatable, minimum	Ca 2 h
Dry to use	Ca 24 h

## Directions for use

### Surface preparation

The substrate must be clean, sound and dry: Clean with **JOTUN Spesialvask før maling**. Previously painted surfaces must be sanded and cleaned.

### Pretreatment

Bare iron and nail heads to be primed with **QUICK Bengalack Grunning**.

### Primer

Old glossy/semi glossy paint must be primed with **JOTUN Heftgrunning Universal**. Surfaces discoloured by soot, nicotine etc.: Prime with **JOTUN Kvist- og sperregrunning**.

### Topcoat

2 coats **JOTAPROFF PVA matt 05**. 3 coats on absorbant, porous surfaces is recommended to avoid discolouring.

### Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spesialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

### Storage

In storage and in transport keep the container frost free and upright.

### Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



## Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

## Miscellaneous

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.