

Rehabilit Cubiertas

Product description

Type

This product is an elastic waterproof paint made of resin emulsion specially laminated.

Features and benefits

Thick application paint, providing a semi-gloss finish, high strength, flexibility and impermeability. It is completely non-toxic.

Recommended use

It is specially designed for treating roofs and terraces of buildings and walls with leak problems, repairing various cracks. It offers a waterproof protection to the coated surface solving the problem of leaks on rooftops.

Do not apply directly on glossy, non-porous or vitrified surfaces.

Substrate

Cement plaster, Concrete, block work, gypsum board and rendered surfaces.

Product data

Packaging size	4 L and 15 L
Colours	White and red. For other colours please call Jotun office.
Solids by volume	43 ± 2 volume% Theoretical

Application data

The product can be applied by

Roller : Recommended.
Brush : Recommended.
Nylon or steel trowel.

Film thickness per coat

Typical recommended range

1 - 2 kg/m² Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

Dilution

Ready to use.

Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface must be sanded to achieve maximum adhesion if the application is done after recommended recoating time.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Substrate temperature

23 °C

Surface (touch) dry

3 h

Hard dry

24 - 48 h

Dry to over coat, minimum

6 - 7 h

Directions for use

Surface preparation

The substrate must be in good condition, clean, dry and free of dust, oil, grease and grout, and as mold and defects inherent moisture etc. All traces of migration and leaks should be eliminated. The chalky and dusty surfaces, loose grains and loose material should be removed with a stiff brush. If the surface was already painted, it must be sanded thoroughly before applying paint, or try a small area of the area to test the total acceptance and adherence of paint over the old. It is recommended to apply a coat of sealer or consolidating primer Jotashield Penetrating Primer Blanco. The treated surface must have sufficient flatness for distributing paint provide thick and homogeneous appearance. If it is concrete, it must be of good quality and not rough. If it is a lightweight concrete should be coated with a cement mortar quality.

Other surfaces:

The product can be used on other substrates. Contact Jotun for more information.

Do not apply directly on glossy, non-porous or vitrified surfaces. In these cases the pore must be opened or nuanced before proceeding to apply the paint system.

Recommended paint system

Topcoat

Jotashield Penetrating Primer Blanco : 1 x 35 microns (microns) dry film thickness

Rehabilit Cubiertas : 1 x 400 microns (microns) dry film thickness

Mesh (fabric arm , while the layer remains moist Rehabilit Covers)

Rehabilit Cubiertas : 1 x 400 microns (microns) dry film thickness

Depending on the area of use can be specified other systems.

Remarks

Other systems may be specified, depending on area of use.

Contents of packaging with different batch numbers must be mixed together before use.

Please refer to the Decorative Sales Department for technical advice.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Rehabilit Cubiertas 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.