Technical Data Sheet



JOTUN Sparkel grove underlag

Product description

Туре

Light filler.

Features and benefits

Can be levelled in thickness 0-12 mm without cracking. Minimal shrinkage.

Recommended use

Filling of holes and smoothing of rough surfaces.

Used for spot- and full treatment of boards, plaster and concrete. Use only in dry rooms. The filler is not recommended in combination with paper strips.

Product data

Generic type	Filler for manual application based on cellulose derivatives added lightweight fillers combined with crushed dolomite marble.				
Viscosity					
Solids by volume	70 ± 2 volume%				
Specific gravity	0.8				
Particle size	0 - 0.3 mm				
Specific gravity	0.8				

Application data

Remarks

Thinner

Spreading rate per coat	Film thickness per coat (µm)		
(m²/liter)	Wet (calculated)	Dry (calculated)	

Date of issue:	05.12.2023	Product code:	139	Product family code:	9JS	Page: 1/3

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



Drying times

Dust dry	30 min.
Surface (touch) dry	24 h
Dry to use	24 h

Directions for use

Disposal of waste



Environmental labelling




Approvals



CE-marking

A Declaration of Performance (DoP) for the product has been issued.



Date of issue:	05.12.2023	Product code:	139	Product family code:	9JS	Page: 2/3

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet. **First-aid measures**, refer to section 4. **Handling and storage**, refer to section 7. **Transport information**, refer to section 14. **Regulatory information**, refer to section 15.

Contact information

Jotun A/S Box 2021, NO-3202 Sandefjord Tel: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

Date of issue:	05.12.2023	Product code:	139	Product family code:	9JS	Page: 3/3

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.