

## JOTUN Sparkel grove underlag

### Product description

#### Type

Light filler.

#### Features and benefits

Can be levelled in thickness 0-12 mm without cracking. Minimal shrinkage.

#### Recommended use

Filling of holes and smoothing of rough surfaces.

Used for spot- and full treatment of boards, plaster and concrete. Use only in dry rooms. The filler is not recommended in combination with paper strips.

### Product data

<b>Generic type</b>	Filler for manual application based on cellulose derivatives added lightweight fillers combined with crushed dolomite marble.
<b>Viscosity</b>	
<b>Solids by volume</b>	70 ± 2 volume%
<b>Specific gravity</b>	0.8
<b>Particle size</b>	0 - 0.3 mm

### Application data

#### Remarks

#### Thinner

	Spreading rate per coat (m <sup>2</sup> /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)

## Drying times

Dust dry	30 min.
Surface (touch) dry	24 h
Dry to use	24 h

## Directions for use

### Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.


### Disposal of waste



## Environmental labelling




## Approvals



### CE-marking

A Declaration of Performance (DoP) for the product has been issued.



## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

---

## Contact information

Jotun Sverige AB  
Box 151  
421 22 Västra Frölunda  
Tlf.: +46 31 69 63 00

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.