

DEMIDEKK Ultimate fönster

Product description

Type

Opaque wood protection for outdoor use. The product is water borne. Based on the AMA (Alkyd Modified Acrylics) technology.

Features and benefits

Very good colour stability and long maintenance intervals. Contains effective film conserving agents that counteract mould growth on the surface.

Easy to apply. Has good adhesion.

Recommended use

Especially suitable for planed wood, like windows, doors, window dressings, garden furniture, garage door, fences etc. To be applied to new, previously stained or painted woodwork, as well as impregnated. To be used in combination with **VISIR Oljegranning**, as part of a system treatment. Also suitable as a topcoat for previously primed gutters, fascia's made of plastic and metal commonly use on buildings.

Product data

Gloss level	40-50 semi gloss
Generic type	Based on the AMA (Alkyd Modified Acrylics) technology.
Solids by volume	37 ± 2 volume%
Specific gravity	1.26
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/d): 130 g/l. The product contains max 130 g/l VOC.

Application data

Remarks

Guiding data for airless spray

Nozzle tip	0.46 mm (0.018")
Spray angle degrees	65-80°
Pressure at nozzle	15-18 MPa (150-180 kg/cm ²)

The product may be diluted in case of spray application. Thinner: water.

Thinner

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended, sawn wood:	6 - 9	111 - 167	41 - 62
Recommended, planed wood:	9 - 12	83 - 111	31 - 41

Drying times

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature 41 °F 59 °F 73 °F

Dust dry 6 h 4 h 2 h
Recoatible, minimum 12 h 6 h 4 h

Directions for use

Disposal of waste



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Contact information

Jotun Boya Sanayi ve Ticaret Anonim Şirketi
Balabandere Cad. Hilpark Suites Sitesi
No:10 İstinye 34460
Sarıyer, İstanbul / Türkiye
Telefon: +90 212 279 78 78

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.