

JOTAPROFF Primadekk 02

Product description

Type

Waterborne, completely matt dispersion paint with low odour, for indoor use in ceilings in dry rooms.

Features and benefits

It covers very well and provides a perfect stain free end result.

Recommended use

Use as a middle coat and topcoat in ceilings made of concrete, putty and boards.

Product data

Packaging size	3 L (content 2.7 L). 10 L (content 9 L) and 100 L.
Base availability	Hvit (S0500-N)
Tinting	If white base is bought as white colour, it shall NOT be tinted using Jotun Multicolor . All other colour formulations to be mixed over Jotun Multicolor .
Colors	Can be tinted in selected colours using Jotun Multicolor . Pre-mixed colours (10 L): Egghvit (0502-Y) and Bomull (S0502-Y).
Gloss level	02 completely matt
Generic type	PVA copolymer dispersion panit
Solids by volume	33 ± 2 volume%
Specific gravity	1.35
pH value	8.5 to 9.5
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 10 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well before use.

Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

Guiding data for airless spray

Nozzle tip	0.018–0.021"
Spray angle degrees	50–80°
Pressure at nozzle	Min. 15 MPa (Min. 150 kg/cm ²)

Cleaning of painting tools

Water and **JOTUN Penselrens**.

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	7 - 10	100 - 143	33 - 47

Thinner

Shall not be thinned.

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Drying times

Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Paintable	3 h
Dry to use	24 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry: Clean with **JOTUN Spezialvask før maling**. Sand down previously painted, old glossy/semi glossy paint with suitable abrasive paper and remove dust.

Pretreatment

Bare iron and nail heads to be primed with **QUICK Bengalack Metallgrunning**.

Primer

Unpainted absorbent substrates, like wallpaper and unpainted concrete/plastered walls, must be primed before applying middle coat and topcoat.

Chalking, bleeding and porous substrates: Should be brushed and primed with **JOTAPROFF PVA 07**.

Ceilings discoloured by soot, nicotine etc.: Prime with **JOTUN Kvist- og sperregrunning**.

Topcoat

2 x **JOTAPROFF Primadekk 02**.

Cleaning of spillage

JOTUN Spezial wipes is recommended to clean spillage. **JOTUN Spezial wipes** is a convenient washing/cleansing wipe for use before and during paint work.

Maintenance

The product shall not be washed. Washing will cause stains.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Green Building Standards

The declared product meets the following requirements:

- The emission requirements for M1: Classification of Indoor Environment 2008 (LCI 05-10440, 2014)
- Swan (2096 0002)
- Property criteria in BASTA (2016:A1)
- Accepted according to Building Evaluation Assessment Criteria (Byggvarubedømmningens Bedømningskriterier) 4.0 (2016)
- Class B according to Bedømningskriterier (Assessment Criteria) 6.0 for SundaHus (2013)

BREEAM® NOR (2016)

- Hea 9: VOC content for "Interior matt walls and ceilings" (30 g/l) (EU Directive 2004/42/CE) and emission demands (ISO 16000-9/10).
- Mat 01: Product-specific Type III EPD (ISO 14025;21930, EN 15804).
- Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

BREEAM® NOR (2012)

- Hea 9: VOC content for "Interior matt walls and ceilings" (30 g/l) (EU Directive 2004/42/CE) and emission demands (ISO 16000-9/10).
- Mat 1.3: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804).
- Mat 1.5: This product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional certificates and approvals may be available on request.
The EPDs are available at www.epd-norge.no

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.