

JOTAPROFF Primadekk 02

Product description

Type

Waterborne, completely matt dispersion paint with low odour, for indoor use in ceilings in dry rooms.



Features and benefits

JOTAPROFF Primadekk 02 is our very best ceiling paint for professional painters. It has superb opacity, a fully matt expression at all angles, and very good touching up properties. **JOTAPROFF Primadekk 02** be tinted into several of the most popular white tones.

Recommended use

Use as a middle coat and topcoat in ceilings made of concrete, putty and boards.



Product data

Packaging size	3 L (filling level 2.7 L). 10 L (filling level 9 L)
Base availability	White (S0500-N)
Tinting	If white base is bought as white colour, it shall NOT be tinted using Jotun Multicolor . All other colour formulations to be mixed over Jotun Multicolor .
Colors	Can be tinted in selected colours using Jotun Multicolor .
Gloss level	02 completely matt



Generic type	PVA copolymer dispersion panit
Solids by volume	31 ± 2 volume%
Specific gravity	1.38
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 10 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well before use.

Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

Guiding data for airless spray

Nozzle tip	0.018–0.021"
Spray angle degrees	50–80°
Pressure at nozzle	Min. 15 MPa (Min. 150 kg/cm ²)

Cleaning of painting tools

Water and JOTUN Penselrens.

Thinner

Shall not be diluted.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	8 – 10	100 – 125	31 – 39

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Cleaning of spillage

JOTUN Spezial wipes are recommended to clean spillage. JOTUN Spezial wipes are a convenient washing/cleansing wipe for use before and during paint work.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Recoatable, minimum	3 h
Dry to use	24 h

Directions for use

The substrate must be clean, sound and dry.
Clean with **JOTUN Spesialvask før maling**.

Substrate	Treatment
Bare metal:	Primer: Bare iron and nail heads to be primed with QUICK Bengalack Grunning . Topcoat: 2 x JOTAPROFF Primadekk 02 .
Unpainted absorbent substrates, like wallpaper and unpainted concrete/plastered walls:	Primer: 1 x JOTAPROFF PVA 07 . Topcoat: 2 x JOTAPROFF Primadekk 02 .
Chalking, bleeding and porous substrates:	Primer: 1 x JOTAPROFF PVA 07 . Topcoat: 2 x JOTAPROFF Primadekk 02 .
Previously painted old glossy/semi glossy paint:	Surface preparation: Sand down previously painted old glossy/semi glossy paint with suitable abrasive paper and remove dust. Primer: Old glossy/semi glossy paint must be primed with JOTUN Heftgrunning Universal . Topcoat: 2 x JOTAPROFF Primadekk 02 .
Ceilings discoloured by soot, nicotine etc.:	Primer : JOTUN Kvist- og sperregrunning . Topcoat: 2 x JOTAPROFF Primadekk 02 .

Maintenance

The product shall not be washed. Washing will cause stains.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint and washing water with paint residues must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Green Building Standards

The declared product meets the following requirements:

- The emission requirements for M1: Classification of Indoor Environment 2018
- Swan (2096 0002)
- Property criteria in BASTA (2016:A1)
- Accepted according to Building Evaluation Assessment Criteria (Byggvarubedömningens Bedömningskriterier) 4.0 (2016)
- Class B according to Bedömningskriterier (Assessment Criteria) 6.0 for SundaHus (2013)

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

- BREEAM® International v6.0 (2021)/BREEAM® International (2016)
- Hea 02: VOC exemplary emission (ISO 16000-series) and the VOC content for Interior matt walls and ceilings (Gloss <25@60°) (10 g/l).
 - Mat 01: Product-specific Type III EPD (ISO 14025;21930, EN 15804+A2) for Jotun A/S.

- BREEAM-NOR v6.0 (2022)
- Hea 02-02: Pattern valid level. VOC content for "Matt indoor wall and ceiling paint" (10 g/l) and emission requirements (ISO 16000 series).
 - Mat 02: Product-specific Type III EPD (ISO 14025, ISO 21930, EN 15804+A2) for Jotun A/S.
 - Mat 02: The product's safety data sheet confirms that the product does not contain any substances on the Norwegian priority list (A20 list) and REACH approval/authorisation list – Annex XIV, prohibitions and restrictions – Annex XVII and SVHC candidate list.

- BREEAM® NOR (2016)
- Hea 02: VOC content for "Matt indoor wall and ceiling paint" (30 g/l) (EU Directive 2004/42/CE) and emission requirements (ISO 16000 series).
 - Mat 01: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Jotun A/S.
 - Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional certificates and approvals may be available on request.
The EPDs are available at www.epd-norge.no

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.
Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

52593902, 52593864, 52593872

NOBB module number

42083524

Contact information

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Tel: 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.