

## LADY Interior Finish silkematt

### Product description

#### Type

Waterborne, silky matt acrylic paint with low odour, for indoor use in dry rooms. Brush quality.



#### Features and benefits


The product provides a smooth, nice surface. Remember that matte surfaces are more sensitive to scratching than glossy surfaces.

#### Recommended use

For panel and moulding.



### Product data

<b>Packaging size</b>	White: 2.7 L and 9 L. A-, B- and C-base: 2.7 L.
<b>Base availability</b>	White, A, B and C
<b>Tinting</b>	Bases must be tinted using <b>Jotun Multicolor</b> . Up to 10 % with <b>Jotun Multicolor</b> colorants.
<b>Colors</b>	White base may be used untinted as White.
<b>Gloss level</b>	10 silky matt
	 <p>Glansgradtabell for LADY Interior Finish silkematt</p> <p>0 Hel matt 10 100 Hel blank</p>
<b>Generic type</b>	Waterborne acrylic paint.
<b>Specific gravity</b>	1.1 - 1.5
<b>VOC for Ready-for-Use Mixture</b>	EU limit value for the product (cat. A/d): 130 g/l. The product contains max 80 g/l VOC.

## Application data

### Remarks

Contents of tins with different production numbers should be mixed. Stir well.

### Application equipment / methods

Brush, roller or spray.

### Guiding data for airless spray

<b>Nozzle tip</b>	0.20–0.36 mm (0.008–0.014")
<b>Spray angle degrees</b>	50–80°
<b>Pressure at nozzle</b>	15 MPa (150 kg/cm <sup>2</sup> )

The choice of nozzle tip / spray angle / pressure must be adapted to the relevant spray equipment and surface.

### Cleaning of painting tools

Water and **JOTUN Penselrens**.

### Thinner

The product is ready to use and must not be diluted.

### Spreading rate and film thickness

	Spreading rate per coat (m <sup>2</sup> /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
<b>Recommended:</b>	8 – 10	100 – 125	

### Conditions during application

Temperature of substrate and air must be minimum +10 °C.

### Cleaning of spillage

**JOTUN Spesial wipes** are recommended to clean spillage. **JOTUN Spesial wipes** are a convenient washing/cleansing wipe for use before and during paint work.

### Drying times

#### The drying time is measured by stated values:

<b>Relative Humidity (RH)</b>	50 %
<b>Air temperature</b>	23 °C
<b>Substrate temperature</b>	23 °C

<b>Surface (touch) dry</b>	1 h
<b>Recoatable, minimum</b>	4 h
<b>Fully cured</b>	4 weeks

## Directions for use

### Surface preparation

The substrate must be clean, sound and dry.  
Untreated yellowed paneling must be cleaned with **JOTUN Spesialrens gulnet panel**, 1:10. Sand lightly and remove the dust.  
Previously painted: Clean with **JOTUN Spesialvask før maling**. Use gloves. Sand down and remove dust.  
MDF and hard, smooth surfaces: Sand down and remove dust.

### Primer

Unpainted woodwork: 1-2 x **JOTUN Kvist- og sperregrunning**.

### Topcoat

2 x **LADY Interior Finish silkematt**. Light sanding between coats is recommended for best end result.

### Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spesialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

### Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

### Storage

In storage and in transport keep the container frost free and upright.

### Disposal of waste

Liquid paint and washing water with paint residues must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Must be empty and dry

## Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Green Building Standards

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

- Property criteria in BASTA (2018:A2)
- Swan (2096 0002)

BREEAM® NOR (2016)

- Hea 02: VOC content for Interior/exterior water based, trim and cladding paints for woods and metal (EU Directive 2004/42/CE) and emission demands (ISO 16000-series).
- Mat 01: Product-specific Type III EPD (ISO 14025, ISO 21930, EN 15804) for Scandinavia.
- Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Certificates and approvals may be available on request.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## Indoor environment / Emission

The product is recommended for indoor use only.

## Miscellaneous

### NOBB number

This document covers the following NOBB numbers:

44459096, 49546836, 44459100, 49546840, 44459115, 44459126

### NOBB module number

41830756

## Contact information

Jotun A/S  
P.O.Box 2021  
3202 Sandefjord  
Tel: 33 45 70 00

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).

# Technical Data Sheet

## LADY Interior Finish silkematt

---

