

## JOTUN Lim Standard DK

### Product description

#### Type

Pre-mixed waterborne adhesive for hanging wallpaper, fibre cloth, glass fibre and paper wallpaper in dry and heated rooms.

#### Features and benefits

The adhesive is suitable for application with an adhesive applicator when hanging wallpaper.

### Product data

<b>Packaging size</b>	5 and 15 liter
<b>Colours</b>	White
<b>Generic type</b>	Modified adhesive reinforced with an EVA copolymer dispersion. Creamy, thixotropic consistency.
<b>Solids by volume</b>	16 ± 2 volume%

### Application data

#### Remarks

Stir well before use.

#### Application equipment / methods

Roller, brush or adhesive applicator.

#### Cleaning of painting tools

Lukewarm water.

#### Thinner

May, if necessary be thinned with a small amount of water.

#### Film thickness per coat (µm)

		Wet (calculated)	Dry (calculated)
<b>Recommended</b>	- 4	250	40

### Conditions during application

The temperature of the air and substrate shall be 18-25°C.

## Drying times

Ensure good ventilation during the work. The fibreglass wallpaper / fibre cloth can be painted when the adhesive is completely dry.

## Directions for use

### Surface preparation

The substrate shall be clean, firm, dry, non-chalky and free from residual wallpaper, etc. Sealed/glossy, painted substrates should be cleaned with **JOTUN Specialvask før Maling**, sanded matt and dusted.

### Primer

Sealed/glossy, painted substrates should be primed with **JOTUN Heftgrunning Universal** or a suitable primer if necessary. Chalky or highly-absorbent substrates, e.g. filler, new mineral substrates, etc., should be primed using **JOTUN Microgrunder DK/JOTUN Microgrunder Extra DK** or a suitable primer. In the event of a need for adhesion to / priming of bare plaster, thinned adhesive can be applied.

### Adhesive

Woven fibreglass and fibre cloth: The adhesive should be stirred before use and uniformly applied e.g. using a roller, pencil or a glue machine before the hanging of fibre cloth and fiber glass wallcoverings. Hang the wallpaper in the wet adhesive. The wall covering can be painted with Jotun's appropriate primer or paint when the adhesive is completely dry.

Wall paper: The adhesive should be uniformly applied to the back of the wallpaper so that it can be absorbed and soften the wallpaper before hanging. The adhesive is well-suited to machine application. For certain wallpaper types, the adhesive can be applied to the wall and the wallpaper hung directly onto the adhesive. Ensure good ventilation during the work.

Avoid getting adhesive on the front side of the wallpaper. Immediately remove any residual adhesive with a damp cloth.

### Wall coverings

Please refer to the manufacturer's recommendations for further details.

### Storage

In storage and in transport keep the container frost free and upright. Shelf life of min. 1 year in unopened packaging when stored in a cool, dry place.

## Environmental labelling



The product is recognized by Miljømærkning Danmark, and conforms with the demands of the environmental label Svanen (the swan).

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

Product registration number: Not to be declared

Safety rules	
00-1	1993

## Contact information

Jotun Danmark A/S  
Jernet 6  
6000 Kolding  
Tlf.: +45 76 30 32 00  
Mailadresse: mail@jotun.dk

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.