

JOTUN Lim Ekstra DK

Product description

Type

Water-thinned adhesive for the hanging of fibreglass wallpaper and fibre cloth in dry, heated rooms.

Product data

Packaging size	5 and 15 liter
Colours	White
Generic type	Modified adhesive reinforced PVAc dispersion. Creamy, thixotropic consistency.
Solids by volume	20 ± 2 volume%
pH value	7

Application data

Remarks

Stir well before use.

Application equipment / methods

The adhesive is easy to apply with either a roller, pencil or airless

Cleaning of painting tools

Lukewarm water.

Spreading rate and film thickness

	Spreading rate per coat (m²/liter)
Recommended	3 - 5

Conditions during application

The temperature of the air and substrate shall be 15-30°C. Best result will be obtained at normal room temperature.

Drying times

Depending on room temperature and humidity. Ensure good ventilation during the work. The fibreglass wallpaper / fibre cloth can be painted when the adhesive is completely dry.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Dry to use	Normal ca 24 hours
------------	-----------------------

Directions for use

Surface preparation

The substrate shall be clean, firm, dry, non-chalky and free from residual wallpaper, etc. Sealed/glossy, painted substrates should be cleaned with **JOTUN Specialvask før Maling**, sanded matt and dusted.

Primer

Sealed/glossy, painted substrates should be primed with **JOTUN Heftgrunning Universal** or a suitable primer if necessary. Chalky or highly-absorbent substrates, e.g. filler, new mineral substrates, etc., should be primed using **JOTUN Microgrunder DK/JOTUN Microgrunder Extra DK** or a suitable primer.

Adhesive

Woven fibreglass and fibre cloth: The adhesive should be stirred before use and uniformly applied e.g. using a roller, pencil or airless before the hanging of fibre cloth and fiber glass wallcoverings. The adhesive must not be applied to a larger area than that upon which the fibreglass / fibre cloth can be hung while the adhesive is still wet. Hang the wallpaper in the wet adhesive. The wall covering can be painted with Jotun's appropriate primer or paint when the adhesive is completely dry. Ensure good ventilation during the work.

Immediately remove any residual adhesive with a damp cloth.

Wall coverings

Please refer to the fibreglass manufacturer's recommendations for further details.

Storage

In storage and in transport keep the container frost free and upright. Shelf life of min. 1 year in unopened packaging when stored in a cool, dry place.

Environmental labelling



The product is recognized by Miljømærkning Danmark, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Safety rules	
00-1	1993

Product registration number: Not to be declared

Contact information

Jotun Danmark A/S
Jernet 6
6000 Kolding
Tlf.: +45 76 30 32 00
Mailadresse: mail@jotun.dk

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This Technical Data Sheet supersedes those previously issued.

Jotun Danmark recommends that you consult our technical data sheet (TDS), safety data sheet (SDS) as well as data sheet for Operations and Maintenance for the product.

Please visit our website at www.jotun.dk to find a Jotun dealer near you.