

JOTUN Sparkel for treverk - Akryl

Product description

Type

Light acrylic filler.

Features and benefits

Dries quickly, is easy to sand and gives a smooth surface.

Recommended use

For filling of doors, mouldings and other woodwork.

Product data

Packaging size	0.4 L tube and 3 L pail
Colours	White
Generic type	Acrylic emulsion
Solids by volume	59 ± 2 volume%
Specific gravity	1.8
Filling properties	0-1 mm mm

Application data

Application equipment / methods

Trowel.

Cleaning of painting tools

Water

Thinner

Should normally not be thinned.

Product mixing ratio (by volume)

Single pack

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Cleaning of spillage

JOTUN Spezial wipes are recommended to clean spillage. **JOTUN Spezial wipes** are a convenient washing/ cleansing wipe for use before and during paint work.

Drying times

Thick layers, low temperature, high humidity and low air circulation will prolong the drying time.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature 23 °C

Substrate temperature 23 °C

Dust dry 30 min.

Surface (touch) dry 4 h

Recoatible, minimum 4 h

Dry to use 4 h

Directions for use

Surface preparation

Glossy surfaces must be cleaned with **JOTUN Spesialvask før maling** or a suitable cleaning agent, sanded and dedusted prior to filler application.

Primer

New woodwork to be primed with **JOTUN Kvist- og sperregrunning** before applying filler.

Filler

For sanding the putty, sandpaper is used.

To obtain best possible result, 2 layers of filler is required. Large damages/scratches must be filled several times, until the surface is smooth when the filler is dry.

Maintenance

Not applicable. The product is not used alone.

Storage

Frost free freight and storage.

Disposal of waste

Filler must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Contact information

Jotun A/S
Box 2021, NO-3202 Sandefjord
Tel: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.