

## JOTUN Sparkel for treverk - Oljebasert

### Product description

#### Type

Oil based filler for woodwork.

#### Features and benefits

It is extra strong and tolerates stresses. Is easy to sand and gives a smooth surface. Waterproof and frostsafe.

#### Recommended use

For filling of doors, mouldings and other woodwork. Can also be used on woodwork in wetrooms.

### Product data

<b>Packaging size</b>	1 L pail
<b>Colors</b>	Light grey
<b>Generic type</b>	Alkyd filler
<b>Solids by volume</b>	57 ± 2 volume%
<b>Specific gravity</b>	1.64
<b>Specific gravity</b>	
<b>Filling properties</b>	0-5 mm      mm
<b>Flash point</b>	49 °C

### Application data

#### Application equipment / methods

Steel trowel or filler knife bakelite.

#### Cleaning of painting tools

**JOTUN Penselrens** and water.

#### Product mixing ratio (by volume)

One component, ready for use.

#### Thinner

##### **JOTUN White Spirit**

Should normally not be thinned.

#### Conditions during application

Air and surface temperature must be above +10 °C during application.

### Drying times

Thick layers, low temperature, high humidity and low air circulation will prolong the drying time.

#### The drying time is measured by stated values:

<b>Relative Humidity (RH)</b>	50 %
<b>Air temperature</b>	23 °C
<b>Substrate temperature</b>	23 °C

<b>Dust dry</b>	1 h
<b>Paintable</b>	24 h

### Directions for use

Glossy surfaces must be cleaned with **JOTUN Spesialvask før maling**, sanded and dedusted prior to filler application.

New woodwork to be primed with **JOTUN Kvist- og sperregrunning** before applying filler.

Use sandpaper or felt trowel for sanding of fillers.

### Cleaning of spillage

**JOTUN Spesial wipes** is recommended to clean spillage. **JOTUN Spesial wipes** is a convenient washing/cleansing wipe for use before and during paint work.

### Maintenance

Not applicable. The product is not used alone.

### Storage

Cover the left over filler in the can with water before the lid is put on, to prolong the shelflife.

### Disposal of waste

Filler must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



### Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

### Miscellaneous

**Product code:** 191

**The first three characters of the Part Number:** 9JS

#### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.