

JOTUN Grunning for tapet

Product description

Type

White interior primer based on acrylic modified PVA (copolymer).



Features and benefits

Prevents blistering and lifting of the edges. The varying structure and absorption of wallpapers will influence application and consumption. Some textile wallpapers are not suitable for painting because some threads will loosen and create a shabby appearance.

Recommended use

To be used as a primer for water soluble paints on most textile and paper wallpapers, as well as new glass fibre and Eco wallpaper. The product is recommended for indoor use only.



Product data

Packaging size	3 L and 10 L
Colors	Greyish-white
Solids by volume	53 ± 2 volume%
Specific gravity	1.3
pH value	8.5 to 9.5
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/g): 30 g/l. The product contains max 1 g/l VOC.

Application data

Remarks

Stir well. Set a test patch with **JOTUN Grunning for tapet** before work starts.

Application equipment / methods

Apply with a roller and distribute uniformly.
Use brush for grooves.

Guiding data for airless spray

Nozzle tip	0.43-0.53 mm (0.017-0.021")
Spray angle degrees	50-80°
Pressure at nozzle	15 MPa (150 kg/cm ²)

The choice of nozzle tip / spray angle / pressure must be adapted to the relevant spray equipment and surface.

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Consumption

The consumption depends on what type of wallpaper to be treated.

Paper wallpaper: 10-15 m²/l

Textile wall paper: 2-6 m²/l (depending on the type of textile wallpaper).

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Ventilate during and after application.

Cleaning of spillage

JOTUN Spesial wipen are recommended to clean spillage. **JOTUN Spesial wipen** are a convenient washing/cleansing wipe for use before and during paint work.

Drying times

The recoating time must be prolonged at high humidity and/or low temperature, or large consumption of **JOTUN Grunning for tapet**. This to avoid odor.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Recoatable, minimum	12 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry: Dirty substrates must be cleaned before priming. Clean with **JOTUN Spesialvask for maling**.

Wallpaper that has come loose at the joints, along trims and in the corner, must be glued before treatment with **JOTUN Grunning for tapet**.

Make sure that there are no other loose spots. If yes, repair these by making a cut and glue it.

Primer

JOTUN Grunning for tapet should be applied by roller, evenly and not too thick.

Apply evenly to cover the entire substrate. Cutting in can be done by brush, but roller should be used as close to the trims etc. as possible to avoid shades in the final result. Ensure equal saturation between brush and roller.

Do not stop application in the middle of an area, but finish the whole area to avoid overlap.

Blistering can however occur after application of **JOTUN Grunning for tapet**. Correct these as mentioned above.

Topcoat

Alkyd based paint should not be used directly on textile wallpaper.
Recommended end treatment: **LADY Wonderwall, LADY Pure Color, LADY Balance, LADY Vegg 10, JOTUN Vegg og tak, JOTAPLAST Vegg, JOTAPROFF PVA/Akryl** or **SENS Vegg panel list 10/30**.

Maintenance

Must be overpainted within a short time. Hence no need for washing/maintenance.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Sorted as plastic when empty and dry.

Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.
Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

47150823, 47150812

NOBB module number

28945152

Contact information

Jotun A/S
P.O.Box 2021
3202 Sandefjord
Tel: 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.