

JOTUN Rullespartel Grov DK

Product description

Type

Pre-mixed, ready to use, coarse light filler.

Features and benefits

The filler has effective filling properties and is easy to work with so that a perfect result can be quickly achieved. It is very easy to sand down. The filler's consistency makes it suitable for application using a paint roller, and the texture can then be removed using a steel spatula.

Recommended use

For indoor use in dry rooms. Suitable for levelling concrete, plasterboard and previously treated walls and ceilings where the texture of fibreglass wallpaper, straw wallpaper, etc. shall be filled.

Product data

Packaging size	15 L
Generic type	EVA polymer dispersion with aluminium silicate and dolomite.
Specific gravity	1 ca
Particle size	0.3 mm max
pH value	ca.

Application data

Application equipment / methods

Long-haired paint roller, alternatively a trowel or traditional spray equipment.

Cleaning of painting tools

The tool should be cleaned with water before the filler dries. Dried filler can be removed by soaking in water. Product on the skin can be removed using soap and water.

Thinner

Shall not be thinned.

Spreading rate and film thickness

Film thickness per coat (μm)	
Wet (calculated)	Dry (calculated)

Comments: 1 m²/litre for 1 mm thick layer.

Conditions during application

The temperature of the air and substrate shall be at least 15-30°C upon application. Normal room temperature is recommended.

Drying times

Extremely dependent upon the applied film thickness, substrate, temperature, humidity and ventilation.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature	23 °C
Substrate temperature	23 °C

Dry to use	8-10 hours
Dried/cured for sanding	8-10 hours

Directions for use

Surface preparation

All substrates shall be firm, clean and free from dust and loose particles.

Filler

Can be applied in thicknesses of up to 6 mm. Thicker layers significantly extend the drying time. It can be advantageous to apply several thin layers in order to ensure full through-hardening. The filler must be fully cured between each application. Use sandpaper on water-thinned products when sanding the filler.

Storage

In storage and in transport keep the container frost free and upright. Shelf life of min. 1 year in unopened packaging when stored in a cool, dry place.

Environmental labelling



The product is recognized by Miljømærkning Danmark, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Product registration number: Not to be declared

Safety rules	
00-1	1993

Contact information

Jotun Danmark A/S
Jernet 6
6000 Kolding
Tlf.: +45 76 30 32 00
Mailadresse: mail@jotun.dk

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This Technical Data Sheet supersedes those previously issued.

Jotun Danmark recommends that you consult our technical data sheet (TDS), safety data sheet (SDS) as well as data sheet for Operations and Maintenance for the product.

Please visit our website at www.jotun.dk to find a Jotun dealer near you.