

Jotun Accelerator CO1P

Product description

This is Cobalt octoate dissolved in an organic solvent mixture. The product acts as an accelerator in combination with ketone peroxides for the cure of Jotun Baltoflake and Chemflake products.

Typical use

Recommended usage as per technical datasheet or application guide for the specific product to be applied.

Product data

Property	Test/Standard	Description
Flash point	ISO 3679 Method 1	180 °F (82 °C)
Density	calculated	0.9 kg/l

The provided data is typical for factory produced products, subject to slight variation depending on color.

Cobalt content (calculated): 1 %

Packaging (typical)

	Volume (liters)	Size of containers (liters)
Jotun Accelerator CO1P	1	1

The volume stated is for factory made colors. Note that local variants in pack size and filled volumes can vary due to local regulations.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

WARNING: Accelerators must never come in direct contact with peroxides.

Cobalt accelerators may react violently with organic peroxides!
It is not permitted to store or transport accelerators together with peroxides.

Shelf life at 73°F (23 °C)

Jotun Accelerator CO1P	12 month(s)
------------------------	-------------

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Note

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Color variation

When applicable, products primarily meant for use as primers or antifoulings may have slight color variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.
