

Marine Rubbing

Product description

Type

This is a state of the art rubbing liquid.

Features and benefits

It does not contain abrasives components, giving the surface a chemical cleaning. Specially designed for removal of scratches, oxidized surfaces, dirt and stains.

Recommended use

To be used for rubbing and polishing of gelcoat and two component paints.

Product data

	Volume (liters)	Size of containers (liters)
Marine Rubbing	0.5	0.5

The volume stated is for factory made colors. Note that local variants in pack size and filled volumes can vary due to local regulations.

Colors light beige

Density 0.98 g/cm³ calculated

pH value 8.5

Contents Contains: aliphatic hydrocarbons 15-30%, Nonionic surfactants < 5 %. in-can preservative

The provided data is typical for factory produced products, subject to slight variation depending on color.

Application data

The product can be applied by

Cotton, Rag, Sponge, 3M Pad: Recommended.

Cleaning of painting tools

Water

Product mixing ratio (by volume)

Single pack

Directions for use

Surface preparation

Surfaces with grease, oil or other contamination, wash with recommended Jotun Yachting detergent.

Pretreatment

Shake the can before use. Apply the product with a clean, soft and moist cloth. Machine application is recommended at a rotating speed of approximately 1000 - 1500 rpm. Polish to the desired effect. For manual polishing, rub by hand with circular movements, only smaller areas at the time. Polish to the desired effect. Complete with a clean microfibre cloth or polish paper.

Topcoat

Finish with a Jotun Yachting wax.

Additional information

Do not apply the product on hot surfaces or in direct sunlight. Avoid contact with plastic details.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Marine Rubbing 24 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Note

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Color variation

When applicable, products primarily meant for use as primers or antifoulings may have slight color variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Miscellaneous

Contact information

Jotun A/S
Box 2021
NO-3202 Sandefjord
Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.