

LADY Interior Finish halvblank

Product description

Type

Waterborne, semi gloss acrylic paint with low odour, for indoor use in dry rooms. Brush quality.



Features and benefits


The product provides a smooth, nice surface. The paint provides a washable and durable surface.

Recommended use

Intermediate and Topcoat on panels, MDF, furniture, doors, trims and mouldings.



Product data

Packaging size	According to the current price list.
Base availability	White, A, B and C
Tinting	Bases must be tinted using Jotun Multicolor . Up to 10 % with Jotun Multicolor colorants.
Colours	White base may be used untinted as White.
Gloss level	40 semi gloss
	
Generic type	Waterborne acrylic paint.
Specific gravity	1 - 1.3
Flash point	Closed cup: 72°C (161.6°F)
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/d): 130 g/l. The product contains max 80 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Brush, roller or spray.

Guiding data for airless spray

Nozzle tip	0.43-0.53 mm (0.017-0.021")
Spray angle degrees	50-80°
Pressure at nozzle	15 MPa (150 kg/cm ²)

Cleaning of painting tools

Water and **JOTUN Penselrens** or water and a suitable cleaning agent.

Thinner

The product is ready to use and must not be diluted.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended	8 - 10	100 - 125	

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Cleaning of spillage

JOTUN Spesial wipes are recommended to clean spillage. **JOTUN Spesial wipes** are a convenient washing/cleansing wipe for use before and during paint work.

Drying times

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Recoatable, minimum	4 h
Fully cured	4 weeks

Directions for use

Surface preparation

The substrate must be clean, sound and dry.
Yellowed wood has to be sanded and cleaned with **JOTUN Spesialrens gulnet panel** or a suitable cleaning solution. Sand lightly and remove the dust.
Previously painted: Clean with **JOTUN Spesialvask før maling**. Use gloves. Sand down and remove dust.
MDF and hard, smooth surfaces: Sand down and remove dust.

Primer

Unpainted woodwork: 1-2 x **JOTUN Kvist- og sperregrunning**. MDF and hard, smooth surfaces: 1 x **JOTUN Heftgrunning Universal**.

Topcoat

2 x **LADY Interior Finish halvblank** . Light sanding between coats is recommended for best end result.

Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spesialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

Management, Operation and Maintenance

Please refer to the Drift og Vedligeholdelse datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Product registration number: 4221151

Safety rules	
00-1	1993

Indoor environment / Emission

The product is recommended for indoor use only.

Contact information

Jotun Danmark A/S
Jernet 6
6000 Kolding
Tlf.: +45 76 30 32 00
Mailadresse: mail@jotun.dk

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This Technical Data Sheet supersedes those previously issued.

Jotun Danmark recommends that you consult our technical data sheet (TDS), safety data sheet (SDS) as well as data sheet for Operations and Maintenance for the product.

Please visit our website at www.jotun.dk to find a Jotun dealer near you.